NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/190
30 June 1997
SUPERSEDING
MIL-M-3946/14C
10 December 1993

DETAIL SPECIFICATION SHEET

MEDAL, CIVIL WAR CAMPAIGN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

REVERSE

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH metal finish chip Number 4.

DIMENSIONS:
DIAMETER: 1-1/4 inches (3.18 cm) (REF)
THICKNESS (At Rim): 0.085 inch ± 0.010 inch (0.216 cm ± 0.025 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:22Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The pendant ring shall be fabricated from 0.050 inch ± 0.002 inch (0.127 cm ± 0.005 cm) nominal diameter wire with the same material and finish as the pendant. The ring shall have an outside diameter of 0.200 inch ± 0.010 inch (0.508 cm ± 0.025 cm). The ring shall be hard soldered to the top center of the pendant as shown.

3. The ribbon for the pendant drape shall conform to MIL-DTL-11589/25.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0897)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:22Z
Check the source to verify that this is the current version before use.