INCH-POUND

MIL-H-27893E(GL)
10 April 1989
SUPERSEDING
MIL-H-27893D(GL)
4 February 1986

MILITARY SPECIFICATION

HARNESSES, PARACHUTIST'S. INDIVIDUAL EQUIPMENT PACK (“H” - TYPE)

This specification is approved for use by the U.S. Army Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of of Defense.

1. SCOPE

1.1 Scope. This specificatioon covers two types of general purpose harnesses, having an "H" design and made of nylon webbing. Each harness is equipped with quick-fit adapters, buckles and snaps to secure it around the load and to the T-10 parachute harness worn by the parachutist.

1.2 Classification. 1.2 Classification. The harnesses shall be of the following types as specified (see 6.2):

Type I - "H" Harness
Type II - H - Harness, Single Point Release

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to : U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:01Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues o these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

T-T-871	- Twine, Cotton, Wrapping
PPP-B-26	- Bag, Plastic, Polyethylene
PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-636	- Boxes, Shipping, Fiberboard

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitching

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads

(Unless otherwise indicated, copies of federal and military specificaitons, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publicaitons, form a part of this document to the extent specified herein. Unless otherwixe specified, the issues are those cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:01Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

11-1-147	- Harness Parachutist's, Individual Equipment Pack; ("H" - Type), Assembly and Details, Type I
11-2-3008	- Harness, Parachutist's Individual Equipment Pack; Single Point Release, Type II, Assembly
11-1-3009	- Harness
11-1-3010	- Strap, Leg, Release Assembly
11-1-3011	- Handle Release Assembly
11-1-3012	- Strap, Harness, Attaching

(Copies are available from the U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizationsthat prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials. Materials shall conform to the drawings listed in section 2, to the subsidiary specifications, standards and drawings applicable thereto, and as specified herein. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:01Z
Check the source to verify that this is the current version before use.

3.3 Construction and assembly. The construction shall conform to the requirements of this specification and to the designs, details, and dimensions shown or specified on the applicable drawings.

3.3.1 Stitching. All stitching shall conform to FED-STD-751.

3.3.1.1 Type 301 and 308 stitching. Ends of all type 301 stitching shall be backstitched or overstitched not less than 1/2 inch Past ends Of the defect in accordance with the required stitch pattern. Ends of type 308 stitching shall be secured by crowding a minimum of three stitches (accomplished by not allowing the materials to move) at the beginning and end of the stitching. Thread tension shall be maintained so that there will be no loose stitching resulting in the puckering of the material sewn. The lock shall be embedded in the materials sewn.

3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during the stitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch for box-x and W-W stitching) from the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch from the defective area, (1/2 inch for box-x and W-W stitching), continue over the defective area, and continue a minimum of 1 inch (1/2 inch for box-x and W-W stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.1.2 Repair of 308 stitching. Repairs of type 308 stitching shall be in accordance with 3.3.1.1.1a and 3.3.1.1.1b, except that the stitching shall overstitch the defective area a minimum of three stitches onto the existing stitches.

3.3.1.1.3 Automatic stitching. Automatic stitching machines may be used to perform any of the stitch patterns provided the requirements for the stitch pattern, stitches per inch, size and type of thread are met; and at least three or more tying, overlapping, or back stitches are used to secure the ends of the stitching.

3.4 Thread ends. All thread ends shall be trimmed to a maximum length of 1/4 inch.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:01Z
Check the source to verify that this is the current version before use.

3.5 Setting of grommets. Holes shall be prepunched to receive the grommets. Holes prepunched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommet shall be securely clinched without cutting the adjacent material.

3.6 Finishing of the jacketed wire rope ends. All wire rope ends shall be finished by either the melt method specified in 3.6.1 or by the dip method specified in 3.6.2 such that the ends are completely enclosed with the melted coating flush with the unmelted nylon jacket.

3.6.1 Melt method. Heat the wire rope end nylon jacket with a suitable electrical heating element so as to melt the nylon over the end to form a smooth round surface. Remove any melted residue on the jacket surface with a fine abrasive material such that the surface is not damaged and finishes smooth.

3.6.2 Dip method. Coat the wire rope end with a nylon II or nylon 6/6 powder. Heat the coated end for 10 seconds at 405 ± 15°F using either an induction coil (2 to 4-inch) with an automatic timer control or an electric melting pot with an automatic temperature control (see 6.5).

3.7 Repairs. Repairs such as mends, darns, patches or splices are not permitted on the harness.

3.8 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3, shall be removed from production and replaced with nondefective and properly matched components.

3.9 Workmanship. The finished and assembled harness shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4 . QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:01Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibiliuty for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examnined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4,4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether cut lengths, cut parts, markings for location of components, and location of assembled component parts are in accordance with specified requirements. Whenever nonconformance is noted, corrections shall be made to the parts affected and lot in process. Parts which cannot be corrected shall be removed from production.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:01Z
Check the source to verify that this is the current version before use.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of harnesses. The sample unit shall be one harness. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Webbing or tape	Not specified type or class.	101	
	Color not as specified.		201
	Any hole, cut, or tear.	102	
	Edge frayed, beaded, corded, or torn.		202
	Ends not seared as specified.	103	
Fastener tape	Cut or tear.	104	
	Hooks crushed affecting closure.	105	
	Any fastener tape reversed, i.e., pile tape attached where hook tape is required or visa versa.	106	
	Not specified type and color.		203
Cord	Not specified type and color.		204
	Ends not seared as specified.	107	
Hardware	Fractured, malformed, or bent.	108	
	Burrs or sharp edges.	109	
	Protective finish omitted or not as specified, any corroded area.	110	
	Not specified type, size or style.	111	
	Adapter attached with friction grip facing wrong direction.	112	
Plastic buckle	Not as specified.	113	
	Broken, cracked, chipped, or malformed, failing to serve intended purpose; burr, sharp edge or flash.	114	
	Color and finish not as specified.		205
	Not functioning properly, failing to effect a secure closure or open freely.	115	

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:01Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Jacketed wire rope	Not specified type or size.	116	
	Ends not nylon coated or wire material not completely enclosed.	117	
	Surface of nylon coated end not smooth or flush with unmelted jacketed surface.	118	
Swagging wire rope sleeve	Missing.	119	
	Not specified type or size.	120	
	Not swagged as specified.		206
	One sleeve swag omitted.		207
	Two sleeve swags omitted.	121	
	Swagged excessively tight, cutting wire rope material.	122	
	Swagged loosely, permitting sleeve to rotate freely.	123	
Brass grommets	Clinched excessively tight, cutting adjacent material.	124	
	Insecurely clinched to a degree that grommet may be detached from material.	125	
	Washer installed on incorrect side of material.		208
	Barrel split.		209
	Loosely clinched, permitting grommet to rotate freely within the hole.		210
	Washer omitted,	126	
Thread	Not specified type, class, or size.	127	
	Not specified color.		211
Open seams	1/2 inch or less.		212
	More than 1/2 inch.	128	
NOTE :	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur,		
Runoffs (see open seams)			

Source: https://assist.dla.mil -- Downloaded: 20261O-20T13:01Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Stitch type	Wrong seam or stitch type.	129	
Stitches and stitching	Stitching pattern not as specified.	130	
	Any row of stitching missing.	131	
	One stitch per inch under or over minimum and maximum specified.		213
	Two or more stitches per inch under or over minimum and maximum specified.	132	
	Thread breaks, bobbin runouts, or two or more consecutive skipped or run-off stitches not overstitched or restitched as specified.	133	
	Ends of stitching not backstitched or secured as specified.		214
	Tension loose resulting in loose top or bottom thread, or tight tension causing puckering of material at stitch line.	134	
	Needle chews or bunched stitching.	135	
Components and assembly	Any component part omitted or not as specified or required operation omitted (unless otherwise classified herein).	136	
	Any component misplaced or not assembled as specified.	137	
	Any darn, splice, or other unauthorized repair.		215
Identification marking	Omitted, illegible, incorrect, misplaced, or size of characters not as specified.	138	
	Color not as specified.		216
Cleanness	Dirt, grease or oil or foreign matter clearly noticeable.		217
	Thread ends not trimmed to 1/4 inch or less.		218

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:01Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and assembly	Any component missing, or not assembled or joined as specified.	139	

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of harnesses, The sample unit shall be one harness. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Harking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such a: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:01Z
Check the source to verify that this is the current version before use.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shalll be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, size, location, sequence, Or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each harness shall be compactly folded in such a manner that the it adapters and snap hooks are cushioned within the folds of the nylon webbing. Care shall be taken when folding the type II Harness so that the release wires are not bent back on themselves causing a permanent kink. The folded harness shall be securely tied with twine conforming to Type I-II, 8-ply of T-T-871 and then inserted in a close-fitting 0.003 inch thick polyethylene bag conforming to type I or II, grade A, style 1 of PPP-3-26. Prior to or during the closure operation, excess air within the bag shall be expelled.

5.1.2 Commercial. Each harness shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A packing. Forty harnesses preserved as specified in 5.1, shall be packed in a cleated-plyood box conforming to overseas type, style A or J, type 2 load of PPP-B-601. Closure and strapping shall be in accordance with PPP-B-601.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:01Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Forty type I harnesses or twenty type II harnesses. preserved a sspecified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V3C, V3S, or V4S of PPP-B-636, Closure shall be in accordance with PPP-B-636 except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Harnesses, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (ss 6.2), harnesses packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type I or Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Polyethylene bagged unit packs. Polyethylene bagged unit packs shall have the required information legible printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag soas to permit ready identification. The bag or label shall indicate the following instructions:

Stock Number
Nomenclature
Quantity

6. NOTES

(This section contains information of a general or explanatory nature that may be helpgul, but is not mandatory.)

6.1 Intended use. The harnesses are intended for use by individual parachutists for securing individual combat equipment during airborne jump operations. The harness with the secured load is attached to the parachutist harness D-rings with the attaching strap snaps.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:01Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, name, and date of this specification.
b. Type required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.3, and 6.3).
e. Levels of preservation and packing (see 5.1 and 5.2).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contractingofficer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Color samples. For access to standard shade samples of webbing, cord, and thread, and thread, address the contracting activity issuing the invitation for bias.

6.5 Source for heat sealing equipment. A source for the heat sealing equipment for forming the ends of the nylon jacketed wire rope (see 3.6.2-induction coil dip method) is Boyd Coatings Research Co. Inc., 51 Parmenter Road, Hudson, MA 01749.

6.6 Subject term (key word) listing.

Airborne jump operations
Combat equipment carrier
Quick release
T-10 parachute harness

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army - GL

Review activity:

Army - AV

Preparing activity:

Army - GL

(Project 1670-0767)

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-27893E(GL)	Harnesses, Parachutist's, Individual Equipment Pack ("H" - Type)

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026/10-20T13:01Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:01Z
Check the source to verify that this is the current version before use.