Review activities:
Navy - SH, OS
User activities:
Army - ME, EL
Navy - AS, YD, MC

FED. SUP CLASS
6240



MS part number	Industry number	Rated volts	Design amperes	Candle power (approx.)	Filament designation	Avg. life (hours)	Finish	Primary service
MS15612-1	1768	6	0.20	(F) 0.60	(F) C-2R	(F) 1000	Clear	Pilot and indicator
MS15612-2	335	28	0.04	0.34	C-2F	1000	Clear	Indicator
MS15612-3	1769	2.5	0.20	0.20	(F) C-2R	500	Clear	Indicator
MS15612-4	1767	2.5	0.20	0.20	C-2R	500	Clear	Pilot and indicator
MS15612-5	342	6	0.04	(F) 0.04	C-2V	1000	Clear	D.C.indicator light

NOTES:
1. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
2. Referenced documents shall be of the issue in effect on date of invitations for bid.

(G) CANCELED AFTER 19 MAY 1987.
NO SUPERSEDING STANDARD.

APPROVED 25 AUG 1954 REVISED (D) 29 MAY 1965 (E) 10 JUN 1966 (F) 17 AUG 1970 (G) 19 MAY 1987

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Project 6240-N383

P.A. SH Other Cust	TITLE LAMP, INCANDESCENT, T-1-3/4 MIDGET SCREW BASE	MILITARY STANDARD MS15612
Procurement Specification W-L-111	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 57 672 COORDINATED PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.
☆ U. S. GOVERNMENT PRINTING OFFICE: 1970-433-691/2052

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:49Z
Check the source to verify that this is the current version before use.