INCH-POUND

MS21960C
15 June 2000
SUPERSEDING
MS21960B
13 June 1975

DETAIL SPECIFICATION SHEET

BODY, CLUSTER FITTING, THREE-WAY, INTERNAL BOSS

This specification is approved for use by all Departments and Agencies
of the Department of Defense .




FIGURE 1. Body, cluster fitting.



AMSC N/A FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:42Z
Check the source to verify that this is the current version before use.

TABLE IA. Dimensions for low flow sizes.

| Low Flow Size | | Tube OD | Thread T SAE AS8879 | A | B | C ± .031 | D ± .031 | J | K |
|---|---|---|---|---|---|---|---|---|---|
| Al Alloy 7075 | Al Alloy 1/ 2014/2024 | | | | | | | | |
| W4L | -4L | .250 | .4375-20UNJF-3B | .312 | .500 | .688 | .406 | .625 | 1.062 |
| W5L | -5L | .312 | .500-20UNJF-3B | .344 | .500 | .750 | .438 | .625 | 1.094 |
| W6L | -6L | .375 | .5625-18UNJF-3B | .344 | .500 | .812 | .469 | .625 | 1.125 |

1/ Aluminum alloy 2014 and 2024 parts are cancelled. Use Aluminum alloy 7075 parts for new design. Cancelled parts may be used till stock is exhausted.

TABLE IB. Dimensions for high flow sizes.

| High Flow Size | | Tube OD | Thread T SAE AS8879 | A | B | C ± .031 | D ± .031 | J | K |
|---|---|---|---|---|---|---|---|---|---|
| Al Alloy 7075 | Al Alloy 1/ 2014/2024 | | | | | | | | |
| W4H | -4H | .250 | .4375-20UNJF-3B | .312 | .594 | .688 | .297 | .625 | 1.219 |
| W5H | -5H | .312 | .500-20UNJF-3B | .375 | .594 | .750 | .312 | .625 | 1.250 |
| W6H | -6H | .375 | .5625-18UNJF-3B | .406 | .594 | .812 | .375 | .625 | 1.312 |
| W8H | -8H | .500 | .750-16UNJF-3B | .422 | .594 | 1.125 | .625 | .750 | 1.500 |

1/ Aluminum alloy 2014 and 2024 parts are cancelled. Use Aluminum alloy 7075 parts for new design. Cancelled parts may be used till stock is exhausted.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:42Z
Check the source to verify that this is the current version before use.




# MOUNTING END DIMENSIONS

FIGURE 2. Mounting end.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:42Z
Check the source to verify that this is the current version before use.




# CONTOUR DIMENSIONS EXTERNAL

FIGURE 3. External contour.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:42Z
Check the source to verify that this is the current version before use.

TABLE II. Dimensions for contour and mounting end.

| Type Fitting | A ± .031 | B Max 1/ | C Max 2/ | D Max 2/ | F ± .0005 | G ± .004 | H ± .005 | J ± .010 | K ± .010 | L ± .004 | M ± .005 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Low Flow | .562 | .636 | .844 | .995 | .5000 | .664 | 1.000 | .797 | .312 | .249 | .143 |
| High Flow | .812 | .909 | 1.156 | 1.188 | .8125 | 1.045 | 1.188 | 1.078 | .375 | .283 | .175 |

1/ B radius is the max envelope dimension for forging draft, flash, and other projections on A radius.
2/ Dimensions C and D represent the max envelope which shall be large enough to meet final part dimensions.

REQUIREMENTS:

1. The requirements for acquiring the product described herein shall consist of this specification sheet and SAE AS4875.

2. Material: Aluminum alloy extrusion, 7075-T73 per AMS-QQ-A-225/9. Aluminum alloy forging, 7075-T73 per AMS-QQ-A-367.

3. Finish: See acquisition standard SAE AS4875. Aluminum alloy 7075 fittings shall be dyed brown.

4. All machined surfaces shall be finished to 250 µin $R_a$ maximum, unless otherwise specified. Surface finish shall be in accordance with ASME B46.1.

5. Fittings shall be free of all burrs and slivers.

NOTES:

1. Dimensions in inches. Unless otherwise specified, tolerances: decimals ± .010, angles ± 1/2°.

2. Dimensioning and tolerancing per ASME Y14.5.

3. Part Identification number (PIN)

Example of PIN: MS21960W4L






Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:42Z
Check the source to verify that this is the current version before use.

Custodians:
Air Force - 99
Navy - AS
DLA - CC

Review activities:
Air Force - 82
Navy - SA

Preparing activity:
DLA - CC

(Project 4730-0822)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:42Z
Check the source to verify that this is the current version before use.