FED. SUP CLASS
1630

SIZE	A ±0.062	B MIN	C ±0.031	D DIAMETER	F_R ±0.016	G MIN	H ±0.010	K MIN	J_R ±0.010	L ±0.125	r_R MIN	
30x8.8	7.000	0.813	3.500	15.000 $^{+0.015}_{-0.000}$	0.563	2.250	1.125	0.196	0.281	0.250	0.125	

Ⓐ NOTE 1: VALVE HOLE AND "L" DIMENSION REQUIRED ON TUBE TYPE AND CONVERTIBLE WHEELS ONLY. TUBELESS WHEELS REQUIRE A MACHINED BOSS, PER AND10050.

DIMENSIONS IN INCHES.
UNLESS OTHERWISE SPECIFIED, TOLERANCES:
FRACTIONS ±1/64; DECIMALS ±0.005; ANGLES ±0° 30'

APPROVED 25 APR 56 REVISED Ⓐ 5 MAR 64

Ⓐ Reviewer/User Activities: Air Force: OOA. Reviewer/User information is current as of the date of this document. For future coordination of changes to this document draft circulation should be based on the information in current DODISS.

Ⓒ This military standard is approved by the OOAMA, Department of the Air Force and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

THIS IS A DESIGN STANDARD AND SHALL NOT BE USED AS A PART NUMBER.

P.A. OOA Other Cust	TITLE: RIM CONTOUR - 30x8.8, TYPE VII, EXTRA HIGH PRESSURE, MAIN LANDING GEAR WHEEL	MILITARY STANDARD MS 24369(USAF)
Procurement Specification NONE	SUPERSEDES:	SHEET OF

DD FORM 1 SEP 57 672 LIMITED (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. GPO 806-074

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:53Z
Check the source to verify that this is the current version before use.