NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/303(IH)
18 November 2024

DETAIL SPECIFICATION SHEET
BADGE, QUALIFICATION MASTER COMBAT MEDICAL BADGES, U. S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.


Basic


Second Award


Third Award


Fourth Award

DASH NO.
-1: Basic, Silver-Gold, Regular Size
-2: 2nd Award, Silver-Gold, Regular Size
-3: 3rd Award, Silver-Gold, Regular Size
-4: 4th Award, Silver-Gold, Regular Size
-5: Basic, Silver-Gold, Dress Miniature Size
-6: 2nd Award, Silver-Gold, Dress Miniature Size
-7: 3rd Award, Silver-Gold, Dress Miniature Size
-8: 4th Award, Silver-Gold, Dress Miniature Size
-9: Basic, Regular Size, Subdued
-10: 2nd Award, Regular Size, Subdued
-11: 3rd Award, Regular Size, Subdued
-12: 4th Award, Regular Size, Subdued

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
1: -1 through -8: Nickel plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.
WREATH: 24K Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:32Z
Check the source to verify that this is the current version before use.

2: (-9 through -12): Dull, Flat Black and shall match TIOH Metal Finish Chip Number 21
WREATH: Dull, Flat Brown Enamel Finish and shall match TIOH metal Finish Chip Number 22.

DIMENSIONS:
HEIGHT (Overall):
-1, -9: 1 inch (REF)
-2, -4, -10, -12: 1-7/32 inches (REF)
-3, -11:1-13/32 inches (REF)
-5: 19/32 inch (REF)
-6, -8: 13/16 inch (REF)
-7: 25/32 inch (REF)

WIDTH (Overall):
-1, -2, -3, -9, -10, -11: 1-1/2 inches (REF)
-4, -12: 1-13/16 inches (REF)
-5, -6, -7: 7/8 inch (REF)
-8: 1 inch (REF)

THICKNESS: (At center cross)
-1 thru -4, -9 thru -12: 0.095 inch + .005 inch
-5 thru -8: 0.065 inch + .005 inch

ATTACHING DEVICE:
1. The attaching device shall be prong and wing type clutch.

2. The prongs shall be located on the reverse on the horizontal center line equidistant from each end and 1 inch $\pm$ 1/32 inch apart for regular size badges and 3/4 inch $\pm$ 1/32 inch apart for dress miniature size badges.

PIERCING: Piercing shall be as indicated in shaded areas.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.
2. -1 through -8: Silver Plated, Oxidized, Buffed Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14 and Wreath, Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7 may be used for commercial sale.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2025-032)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:32Z
Check the source to verify that this is the current version before use.