NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/306(IH)
17 December 2025

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, MARINER, BASIC, SENIOR AND MASTER, U. S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



BASIC



SENIOR



MASTER

DASH NO.
-1: Basic, Regular Size
-2: Basic, Miniature Size
-3: Senior, Regular Size
-4: Senior, Miniature Size
-5: Master, Regular Size
-6: Master, Miniature Size
-7: Basic, Regular Size, Subdued
-8: Senior, Regular Size, Subdued
-9: Master, Regular Size, Subdued

MATERIAL (-1 through -9) Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
1: -1 through -6: Nickel plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.
2: -7 through -9: Dull Flat Black Enamel and shall match TIOH Metal Finish Chip Number 21.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:33Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
BASIC:
HEIGHT:
-1: 2-inches (REF)
-2: 1-1/2 inches (REF)
WIDTH:
-1: 1-29/32 inches (REF)
-2: 1-7/16 inches (REF)
THICKNESS (at outer rim of helm):
-1: 0.121 inch ± 0.010 inch
-2: 0.105 inch ± 0.010 inch
SENIOR:
HEIGHT:
-1: 2-inches (REF)
-2: 1-1/2 inches (REF)
WIDTH:
-1: 2-1/32 inches (REF)
-2: 1-17/32 inches (REF)
THICKNESS (at outer rim of helm):
-1: 0.121 inch ± 0.010 inch
-2: 0.105 inch ± 0.010 inch
MASTER:
HEIGHT:
-1: 2-inches (REF)
-2: 1-1/2 inches (REF)
WIDTH:
-1: 2-1/32 inches (REF)
-2: 1-17/32 inches (REF)
THICKNESS (at outer rim of helm):
-1: 0.121 inch ± 0.010 inch
-2: 0.110 inch ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be prong and wing type clutch.

2. Three prongs shall be located on the reverse on a 1-3/4 inches diameter circle for -1 and approximately 1-1/4 inches diameter circle for -2. The prongs shall be spaced 120 degrees apart with the bottom prong located on the vertical center line 1/8 inch from the bottom.

OBVERSE: The shield with helm and wing shall be modeled. Shaded areas to be pierced.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercings shall be as indicated above in the shaded areas.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:33Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2026-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:33Z
Check the source to verify that this is the current version before use.