NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/308
17 April 2026

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, COMMANDERS, U.S. SPACE FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



MATERIAL: Red Brass 85/15 (UNS Alloy NO. C-230)

FINISH: Nickel Plated, Mirror-Like Polish and shall match The Institute of Heraldry Finish Chip number 16.

DIMENSIONS:
HEIGHT: 3/4 inch (REF)
WIDTH: 7/8 inch (REF)
THICKNESS (At thickest point): 0.095 ± 0.005 inch

ATTACHING DEVICE:
1. The attaching device shall be two prongs with wing type clutch.

2. Prongs shall be located on the reverse horizontal center line and centered on the contrail's wreath.

OBVERSE: The central delta and orbit, globe, wings, wreath of contrails, stars, and deltas to be modeled. The polestar at the center of the base to be raised and modeled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:33Z
Check the source to verify that this is the current version before use.



Prong Placement Indicators

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army – IH

Review activity:
DLA - CT

(Project No. 8455-2025-261)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:33Z
Check the source to verify that this is the current version before use.