MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

SWITCHES, SENSITIVE

TO ALL HOLDERS OF DOD-STD-35-138(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-7C(MI) HAVE BEEN REVISED AND SUPERCEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDE PAGE	DATE
Cove r	5 January 1979	(Reprinted without change)	
ii	14 January 1983	ii	5 January 1979
iii	14 January 1983	iii	5 January 1979
1	14 January 1983	1	5 January 1979
2	30 May 1980	(Reprinted without change)	
7	14 January 1983	7	5 January 1979
11	14 January 1983	11	5 January 1979
12	14 January 1983	12	5 January 1979
13	14 January 1983	13	5 January 1979
15	14 January 1983	15	5 January 1979
16	14 January 1983	16	5 January 1979
17	14 January 1983	17	5 January 1979
18	5 January 1979	(Reprinted without change)	
19	14 January 1983	19	5 January 1979
20	5 January 1979	(Reprinted without change)	
67	14 January 1983	67	5 January 1979
68	5 January 1979	(Reprinted without change)	
79	5 January 1979	(Reprinted without change)	
80	14 January 1983	80	5 January 1979
81	14 January 1983	81	5 January 1979
82	14 January 1983	82	5 January 1979
83	14 January 1983	83	5 January 1979
84	14 January 1983	84	5 January 1979
85	14 January 1983	85	5 January 1979
86	5 January 1979	(Reprinted without change)	
99	5 January 1979	(Reprinted without change)	
100	14 January 1983	100	5 January 1979
101	14 January 1983	101	5 January 1979
102	5 January 1979	(Reprinted without change)	
119	5 January 1979	(Reprinted without change)	
120	14 January 1983	120	5 January 1979
121	14 January 1983	121	5 January 1979
122	5 January 1979	(Reprinted without change)	
149	14 January 1983	149	5 January 1979
150	5 January 1979	(Reprinted without change)	

AREA EDS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

DOD-STD-35-138(MI)
Notice 2
14 January 1983

NEW PAGE	DATE	SUPERSEDE PAGE	DATE
223	14 January 1983	223	5 January 1979
224	14 January 1983	224	5 January 1979
225	14 January 1983	225	5 January 1979
226	14 January 1983	226	5 January 1979
227	14 January 1983	227	5 January 1979
228	14 January 1983	228	5 January 1979
229	14 January 1983	229	5 January 1979
230	14 January 1983	230	5 January 1979

2. THE FOLLOWING PAGES HAVE BEEN ADDED:

NEW PAGE	DATE	NEW PAGE	DATE

3. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

4. Holders of DOD-STD-35-7C(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT
Army-AV
Army-ER
Army-ME
Army-MR
Army-SG
Army-CR

User activity:
Army-AR

Preparing activity:
Army-MI

(Project EDS-A328)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

DOD-STD-35-138(MI)

5 January 1979
SUPERSEDING
SECTION 3
MIL-STD-35-6A(MI)
28 AUGUST 1973

MILITARY STANDARD

SWITCHES, SENSITIVE

AUTOMATED ENGINEERING DOCUMENT PREPARATION SYSTEM

AREA EDS

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE ARMY
U.S. ARMY MATERIEL
DEVELOPMENT AND READINESS COMMAND
ALEXANDRIA, VA 22333

Switches, Sensitive
Automated Engineering
Document Preparation System

DOD-STD-35-138(MI)

1. This Military Standard is approved for use by DARCOM, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U.S. Army Missile Research and Development Command, ATTN: DRSMI-RSDC, Redstone Arsenal, Alabama 35898, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

FOREWORD

1. The purpose of DOD-STD-35-138(MI) is to provide instructions for the preparation of Specification Requirements Sheets (SRS) in order to produce Military Specification Exceptions for sensitive switches.

2. In order to properly utilize the document, it is necessary to have a complete and thorough understanding of the DOD-STD-35.

3. It is important that the procedures described in the basic document (DOD-STD-35) be followed explicitly in order to produce a document suitable of procurement. Information which is standard for all dash-numbered parts has been included in the basic document. This information is not repeated in each dash-numbered part.

Supersedes page iii of 5 January 1979

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for sensitive switches.

1.2 Purpose. This military standard provides necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included-in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirement of AEDPS

1.4 Military Specification Exception Title Index. It is recommended that MIL-STD-1132, Selection and Use of Switches and Associated Hardware be reviewed prior to using this dash-numbered part book.

The title code for a MSE shall be selected form one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on a SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for a MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX.

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
SWITCH, SENSITIVE	014366	MIL-S-8805	GENERAL SPECIFICATION
		MIL-S-13484	AUTOMOTIVE 30 VDC MAX
		MIL-S–13625	AUTOMOTIVE 28 VDC MAX BEAM SELECTING
		MIL-S-22614	FIRE CONTROL EQUIPMENT
		MIL-S-24317	MULTISTATION
		MIL-S-83504	DUAL IN–LINE PACKAGE
		MS39058	24 VDC WATERPROOF
ACTUATOR, SENSITIVE SWITCH	014378	MIL-S-8805	GENERAL SPECIFICATION
SWITCH, PUSH	014362	MIL–S-8805	GENERAL SPECIFICATION
SWITCH, PUSH BUTTON	014379	MIL-S-8805	GENERAL SPECIFICATION

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

4. GENERAL REQUIREMENTS

4.1 Introduction. In order to properly prepare a SRS for Switches, Sensitive, it is necessary to use DOD-STD-35 in conjunction with this dash-numbered part. In the event the instructions or the writing methodology are not followed, an AEDPS edit routine will print error messages rather than the desired MSE document.

4.2 Specification Requirement Sheet (SRS). SRS requirements described in DOD-STD-35 are applicable to Switches, Sensitive.

4.3 Configuration.

4.3.1 Dimensions. SRS requirements for dimensions described in DOD-STD-35 are applicable to Switches, Sensitive.

4.3.2 Illustrations. Illustrations applicable to Switches, Sensitive are contained in Appendix A to this document.

4.4 Units of measure. The International System of Units (SI) or inch-pound units (U.S.), may be used to specify characteristics (e.g. weight, dimensions). Refer to ASTME380 for guidance in using SI. However, when different units of measure are available for specifying a characteristic, only one may be used, Both units of measure cannot appear in the same MSE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

TABLE III. TABULATION CANDIDATES.

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
2010	CONTACT ARRANGE-MENT (POLE)	2012	CONTACT ARRANGE–MENT (THROW)	2018	BUTTON COLOR
2328	MINIMUM OPERATING FORCE NEWTONS	2332	MINIMUM OPERATING FORCE OUNCES	2334	MINIMUM OPERATING FORCE POUNDS
2336	MAXIMUM OPERATING FORCE NEWTONS	2340	MAXIMUM OPERATING FORCE OUNCES	2342	MAXIMUM OPERATING FORCE POUNDS
2502	MAKE AND BREAK RESISTIVE DC LOAD VOLTS	2503	MAKE AND BREAK RESISTIVE DC LOAD AMPERES	2504	MAKE AND BREAK RESISTIVE AC LOAD VOLTS
2505	MAKE AND BREAK RESISTIVE AC LOAD FREQUENCY HERTZ	2506	MAKE AND BREAK RESISTIVE AC LOAD AMPERES	2526	MAKE AND BREAK INDUCTIVE DC LOAD VOLTS
2527	MAKE AND BREAK INDUCTIVE DC LOAD AMPERES	2528	MAKE AND BREAK INDUCTIVE AC LOAD VOLTS	2529	MAKE AND BREAK INDUCTIVE AC LOAD FREQUENCY HERTZ
2530	MAKE AND BREAK INDUCTIVE AC LOAD AMPERES	2550	MAKE AND BREAK MOTOR LOAD DC VOLTS	2551	MAKE AND BREAK MOTOR LOAD DC AMPERES
2552	MAKE AND BREAK MOTOR LOAD AC VOLTS	2553	MAKE AND BREAK MOTOR LOAD AC VOLTAGE FREQUENCY HERTZ	2554	MAKE AND BREAK MOTOR LOAD AC AMPERES

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

TABLE III. TABULATION CANDIDATES. (CONT)

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
2574	MAKE AND BREAK LAMP DC LOAD VOLTS	2575	MAKE AND BREAK LAMP DC LOAD AMPERES	2576	MAKE AND BREAK LAMP AC LOAD VOLTS
2577	MAKE AND BREAK LAMP AC LOAD FREQUENCY HERTZ	2578	MAKE AND BREAK LAMP AC LOAD AMPERES	2601	MAKE AND BREAK DRY CKT DC VOLTS
2602	MAKE AND BREAK DRY CKT DC AMPERES	2603	MAKE AND BREAK DRY CKT AC VOLTS	2604	MAKE AND BREAK DRY CKT AC VOLTAGE FREQUENCY HERTZ
2605	MAKE AND BREAK DRY CKT AC AMPERES	2701	CURRENT CARRYING RESISTIVE DC LOAD VOLTS	2702	CURRENT CARRYING RESISTIVE DC LOAD AMPERES
2703	CURRENT CARRYING RESISTIVE AC LOAD VOLTS	2704	CURRENT CARRYING RESISTIVE AC LOAD FREQUENCY HERTZ	2705	CURRENT CARRYING RESISTIVE AC LOAD AMPERES
2725	CURRENT CARRYING INDUCTIVE DC LOAD VOLTS	2726	CURRENT CARRYING INDUCTIVE DC LOAD AMPERES	2727	CURRENT CARRYING INDUCTIVE AC LOAD VOLTS
2728	CURRENT CARRYING INDUCTIVE AC LOAD FREQUENCY HERTZ	2729	CURRENT CARRYING INDUCTIVE AC LOAD AMPERES	2749	CURRENT CARRYING MOTOR LOAD DC VOLTS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

TABLE III. TABULATION CANDIDATE. (CONT)

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
2750	CURRENT CARRYING MOTOR LOAD DC AMPERES	2751	CURRENT CARRYING MOTOR LOAD AC VOLTS	2752	CURRENT CARRYING MOTOR LOAD AC VOLTAGE FREQUENCY HERTZ
2753	CURRENT CARRYING MOTOR LOAD AC AMPERES	2773	CURRENT CARRYING LAMP DC LOAD VOLTS	2774	CURRENT CARRYING LAMP DC LOAD AMPERES
2775	CURRENT CARRYING LAMP AC LOAD VOLTS	2776	CURRENT CARRYING LAMP AC LOAD FREQENCY HERTZ	2777	CURRENT CARRYING LAMP AC LOAD AMPERES
2801	CURRENT CARRYING DRY CKT DC VOLTS	2802	CURRENT CARRYING DRY CKT DC AMPERES	2803	CURRENT CARRYING DRY CKT AC VOLTS
2804	CURRENT CARRYING DRY CKT AC VOLTAGE FREQUENCY HERTZ	2805	CURRENT CARRYING DRY CKT AC AMPERES	3100	MINIMUM RELEASE FORCE OUNCES
3102	MINIMUM RELEASE FORCE POUNDS	3104	MINIMUM RELEASE FORCE NEWTONS	3106	MAXIMUM PRETRAVEL INCH
3108	MAXIMUM PRETRAVEL MILLIMETER	3110	MINIMUM OVERTRAVEL INCH	3112	MINIMUM OVERTRAVEL MILLIMETER

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

5.6 Keyword Code Index (KCI) and Standard Paragraphs. The KCI provides codes, to be entered on a SRS, that are unique for the type part covered by this dash-numbered part of DOD-STD-35. The left-hand page presents the information in outline form using keywords and codes. The right-hand page presents the words that will appear in the MSE. To find the code to be entered on the SRS, find the subject in the index at the back of this dash-numbered parts. Find the keyword on the KCI and its associated code. Enter, on the SRS, the code and the characteristic value required. After the part unique characteristics have been specified, refer to DOD-STD-35 when exceptions are required to Quality Assurance, Packaging, Notes, etc. Instructions are in DOD-STD-35 on how to enter any type characteristic value. Appendix B, Characteristic Code Index, provides a numerical list of codes used in this dash-numbered part. This index identifies the location of codes by page number.

5.6.1 Interrelationship of codes. The interrelationship of the codes is shown by the Indentation level of characteristic names on the KCI. The kind of characteristic value is shown by a colon, parentheses, period or underline. The paragraph, of which the code is a part, is shown by the standard paragraph adjacent to the code on a right-hand page. When a characteristic value entered with a code becomes part of the paragraph, the code is shown in the paragraph where the characteristic value will print. The MSE will contain the exact entry as supplied with the code, except for “X” entries.

5.6.2 Automatic MSE data. Some statements, such as Altitude and Temperature, will appear in the printed MSE without having to make additional entries. These statements are linked by data base logic to characteristic codes listed under them and will print when one of the codes listed is used. Other statements may print automatically depending on the type MSE selected. Explanations are noted on the KCI as required.

5.6.3 DOD-STD-35 Tables. The KCI of this document contains references to tables in Appendix A of DOD-STD-35. Most of the tables are in preprinted form and should be reproduced, applicable data entered, and attached to the SRS for submittal. Refer to DOD-STD-35 for a general explanation in the generation of tables.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
*REQUESTER'S NAME	0101
*COMPANY NAME/COMMAND	0102
*STREET/BUILDING	0103
*CITY, STATE, ZIP	0104
*PHONE NUMBER, INCLUDE AREA CODE, AUTOVON IF APPLICABLE	0105
*REQUESTER FSCM	1004
*CONTRACT NUMBER/OFFICE SYMBOL	1005
*BASE DOCUMENT	1006
*SYSTEM Application	1008
*GOVERNMENT DESIGN ACTIVITY FSCM	6369
*FORMAT (SELECT ONE)	
SIX SECTION DOCUMENT	0700
ONE SECTION DOCUMENT	0800
*CONTROL (SELECT ONE)	
SOURCE.	6873

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
0101	0101.
0102	0102.
0103	0103.
0104	0104.
0105	0105.
1004	USER FSCM 1004.
1005	CONTRACT NUMBER OR OFFICE SYMBOL 1005.
1006	THE COMPLETE REQUIREMENTS FOR PROCURING THE ITEM(S) DESCRIBED HEREIN SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT(S), 1006 EXCEPT AS SPECIFIED IN THIS DOCUMENT. IN THE EVENT OF CONFLICT, THIS DOCUMENT SHALL GOVERN.
1008	SYSTEM APPLICATION 1008.
6369	GOVERNMENT DESIGN ACTIVITY FSCM 6369.
0700	
0800	
	SOURCE(S).
6873	THE FOLLOWING SOURCE(S) SHOWN WITH THE PART NUMBER(S) IS/ARE THE ONLY APPROVED SOURCE(S) FOR THE ITEM(S) DESCRIBED BY THIS DOCUMENT. IDENTIFICATION OF THE APPROVED SOURCE(S) HEREIN IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM DESCRIBED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONTROL (CONT)	
SPECIFICATION.	6874
*SOURCE TABLE	
NOTE: REFER TO TABLE V OF DOD-STD-35.	
APERTURE CARDS REQUIRED.	0107
REVISION OF AEDPS DOCUMENT (NUMBER)	0108
SCOPE	
NOTE: THIS ENTRY IS AUTOMATIC AND DETERMINED BY THE TITLE CODE USED.	
PART NUMBER	
NOTE: AUTOMATIC WITH A SINGLE ITEM MSE.	
NOTE : AUTOMATIC WITH A MULTI-ITEM MSE.	
UNITS OF MEASURE (SELECT ONE)	
U.S.	6941
SI.	6942

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

6874 THE FOLLOWING SUGGESTED SOURCE(S) SHOWN WITH THEIR PART NUMBER(S) HAVE BEEN KNOWN TO MEET THE REQUIREMENT(S) OF THIS DOCUMENT. IDENTIFICATION OF THE 'SUGGESTED SOURCE(S) OF SUPPLY' HEREIN IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OF CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM(S).

0107

0108 0108.

SCOPE.

SCOPE. THIS DOCUMENT COVERS THE DETAILED REQUIREMENTS FOR TITLE CODE.

PART NUMBER. THE PART NUMBER FOR THE ITEM IS SUPPLIED BY COMPUTER.

PART NUMBER. THE PART NUMBER FOR THE ITEMS IS (THE SAME AS THE NUMBER OF THIS DOCUMENT) PLUS THE SUFFIX NUMBER FROM THE TABULATED CHARACTERISTIC TABLE. REVISION AND ACTIVITY SYMBOLS ARE NOT INCLUDED IN THE PART NUMBER.

6941 UNIT OF MEASURE. ALL UNITS OF MEASURE ARE IN INCH-POUND UNITS (U.S.) OR DEGREES UNLESS OTHERWISE SPECIFIED.

6942 UNIT OF MEASURE. ALL UNITS OF MEASURE ARE IN INTERNATIONAL SYSTEM OF UNITS (SI) OR DEGREES UNLESS OTHERWISE SPECIFIED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEMPERATURE RATING	
MAXIMUM OPERATING (DEGREES CELSIUS)	5069
MAXIMUM NONOPERATING (DEGREES CELSIUS)	5071
MAXIMUM SERVICE (DEGREES CELSIUS)	4905
MAXIMUM AMBIENT OPERATING (DEGREES CELSIUS)	5054
MINIMUM OPERATING (DEGREES CELSIUS)	5068
MINIMUM NONOPERATING (DEGREES CELSIUS)	5070
MINIMUM SERVICE (DEGREES CELSIUS)	4904
MINIMUM AMBIENT OPERATING (DEGREES CELSIUS)	5052
NOMINAL OPERATING (DEGREES CELSIUS)	5046
POWER RATING	
MINIMUM POWER (SELECT ONE)	
(WATTS)	7633
(KILOWATTS)	7632
(MILLIWATTS)	7633
(VOLTAMPERES)	7645

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

1877 THE FREQUENCY OF THE AC VOLTAGE SHALL BE 1877 HERTZ.

1878 THE TEST VOLTAGE SHALL BE 1878 VOLTS RMS SUPERIMPOSED ON
1879 A DC VOLTAGE OF 1879 VOLTS.

4908 DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4908.

4906 DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE. THERE SHALL BE NO EVIDENCE OF FLASHOVER, MECHANICAL DAMAGE, ARCING, OR INSULATION BREAKDOWN.

4894 THE LEAKAGE CURRENT SHALL BE NOT GREATER THAN 4894 MILLIAMPERE(S).

4901 ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE.

4884 DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4884.

6300 DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 301 OF MIL-STD-202.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DIELECTRIC WITHSTANDING VOLTAGE AT REDUCED BAROMETRIC PRESSURE (CONT)	
PER MIL-STD-202, METHOD 301. (CONT)	
*ALTITUDE PER METHOD 105 OF MIL-STD-202	
*TEST CONDITION (LETTER)	4886
*TEST VOLTAGE (SELECT ONE)	
(VOLTS, DC)	4885
(VOLTS, AC)	4849
POINTS OF VOLTAGE APPLICATION:	
BETWEEN TERMINATIONS TIED TOGETHER AND MOUNTING HARDWARE.	6311
BETWEEN TERMINATIONS TIED TOGETHER AND CASE.	63112
BETWEEN MUTUALLY INSULATED PARTS.	6292
BETWEEN ALL INSULATED PARTS AND GROUND.	6293
BETWEEN CURRENT CARRYING PARTS AND THE CASE.	6294
OTHER _____	3240
SPECIAL PREPARATION PER DOCUMENT (DOC DES)	4859

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1900	ENDURANCE, ELECTRICAL. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1900.
3902	ENDURANCE, ELECTRICAL. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1906	THE CONTACT RESISTANCE SHALL BE NOT GREATER THAN 1906 MILLIOHM(S).
1904	THE CONTACT RESISTANCE SHALL BE NOT GREATER THAN 1904 OHM(S).
3244	THE ITEM(S) SHALL REMAIN ELECTRICALLY AND MECHANICALLY OPERATIVE.
1910	THERE SHALL BE NO EVIDENCE OF MALFUNCTION.
1908	THE ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE(S).
3246	THE TEMPERATURE RISE SHALL BE NOT GREATER THAN 3246 DEGREES CELSIUS.
1912	ENDURANCE, ELECTRICAL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1912.
1914	ENDURANCE, ELECTRICAL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1914.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ENDURANCE, ELECTRICAL (CONT)	
PER DOCUMENT (CONT)	
OPERATIONAL CYCLES (QUANTITY)	1916
APPLIED VOLTAGE (SELECT ONE)	
(VOLTS, AC)	1918
(VOLTS, DC)	1920
LOAD (PERCENT OF RATED LOAD)	1922
LOAD (TYPE)	1924
TEST CYCLE RATE (CYCLES PER MINUTE)	1926
DUTY CYCLE	
(HOURS ON)	1927
*(HOURS OFF)	1929
ENDURANCE, MECHANICAL	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3600
AS FOLLOWS:	3602
REMAIN WITHIN SPECIFIED TOLERANCE.	3604
NO EVIDENCE OF MALFUNCTION.	3606
NO EVIDENCE OF DAMAGE.	3608

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

1916 THERE SHALL BE 1916 OPERATING CYCLES.

1918 THE APPLIED VOLTAGE SHALL BE 1918 VOLTS, AC.

1920 THE APPLIED VOLTAGE SHALL BE 1920 VOLTS, DC.

1922 THE LOAD SHALL BE 1922 PERCENT OF THE RATED LOAD.

1924 THE LOAD TYPE SHALL BE 1924.

1926 THE TEST CYCLE RATE SHALL BE 1926 CYCLES PER MINUTE.

1927 THE DUTY CYCLE SHALL BE 1927 HOUR(S) ON AND
1929 1929 HOUR(S) OFF.

3600 ENDURANCE, MECHANICAL. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3600.

3602 ENDURANCE, MECHANICAL. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

3604 THE ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE(S).

3606 THERE SHALL BE NO EVIDENCE OF MALFUNCTION.

3608 THERE SHALL BE NO EVIDENCE OF DAMAGE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Endurance MECHANICAL	
AS FOLLOWS: (CONT)	
MAXIMUM CONTACT RESISTANCE (SELECT ONE)	
(OHMS)	3250
(MILLIOHMS)	3252
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3610
PER DOCUMENT (DOC DES)	3612
OPERATING CYCLES (QUANTITY)	3614
TEST CYCLE RATE (CYCLES PER MINUTE)	3616
TEST TEMPERATURE (DEGREES CELSIUS)	3254
CONTACT MONITORING ____	3256
EXPLOSION	
REQUIREMETNS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1680
AS FOLLOWS:	1928
REMAIN ELECTRICALLY AND MECHANICALLY OPERATIVE.	1930
NO EXPLOSION WITHIN SWITCH OR CHAMBER.	1932

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3250	CONTACT RESISTANCE SHALL BE NOT GREATER THAN 3250 OHM(S).
3252	CONTACT RESISTANCE SHALL BE NOT GREATER THAN 3252 MILLIOHM(S).
3610	ENDURANCE, MECHANICAL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3610.
3612	ENDURANCE, MECHANICAL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 3612.
3614	THERE SHALL BE 3614 OPERATING CYCELS.
3616	THE TEST CYCLE RATE SHALL BE 3616 CYCLES PER MINUTE.
3254	THE TEST TEMPERATURE SHALL BE 3254 DEGREES CELSIUS.
3256	CONTACT MONITORING SHALL BE 3256.
1680	EXPLOSION, THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1680.
1928	EXPLOSION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1930	SWITCHES SHALL BE ELECTRICALLY AND MECHANICALLY OPERATIVE AFTER TEST.
1932	THERE SHALL BE NO EXPLOSION WITHIN THE SWITCH OR CHAMBER-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
EXPLOSION (CONT)	
AS FOLLOWS: (CONT)	
NO EXPLOSION IN CHAMBER WHETHER OR NOT EXPLOSION OCCURS IN SWITCH.	1934
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1674
PER MIL-STD-202, METHOD 109.	1936
LOAD (PERCENT OF RATED LOAD)	1938
LOAD (TYPE)	1940
CHAMBER TEMPERATURE (DEGREES CELSIUS)	1676
PLUS TEMPERATURE TOLERANCE (DEGREES CELSIUS)	1942
MINUS TEMPERATURE TOLERANCE (DEGREES CELSIUS)	1944
TEST VOLTAGE (SELECT ONE)	
(VOLTS AC)	1946
FREQUENCY (HERTZ)	1948
(VOLTS DC)	1950
FUNGUS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4760

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

1934 THERE SHALL BE NO EXPLOSION IN THE CHAMBER WHETHER OR NOT EXPLOSION OCCURS IN THE SWITCH.

1674 EXPLOSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE, DOCUMENT, EXCEPT 1674.

1936 EXPLOSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-STD-202, METHOD 109.

1938 THE LOAD SHALL BE 1938 PERCENT OF THE RATED LOAD.

1940 THE LOAD TYPE SHALL BE 1940.

1676 THE CHAMBER TEMPERATURE SHALL BE 1676 DEGREES CELSIUS.

1942 THE PLUS TEMPERATURE TOLERANCE SHALL BE 1942 DEGREES CELSIUS.

1944 THE MINUS TEMPERATURE TOLERANCE SHALL BE 1944 DEGREES CELSIUS.

1946 THE TEST VOLTAGE SHALL BE 1946 VOLTS AC.

1948 THE AC VOLTAGE FREQUENCY SHALL BE 1948 HERTZ.

1950 THE TEST VOLTAGE SHALL BE 1950 VOLTS DC.

4760 FUNGUS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4760.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FUNGUS (CONT)	
REQUIREMENTS (CONT)	
FUNGUS RESISTANT BY CERTIFICATION OR BY TEST.	4761
NO EVIDENCE OF FUNGUS GROWTH WHEN TESTED*	4762
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	4754
PER MIL-STD-810, METHOD 508.	4755
TEST PERIOD (DAYS)	4756
HUMIDITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	4798
NO EVIDENCE OF CORROSION OR PHYSICAL DAMAGE.	4799

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1377	THE MEASUREMENT ERROR AT THE INSULATION RESISTANCE VALUE REQUIRED SHALL BE NOT GREATER THAN 1377 PERCENT.
	POINTS OF MEASUREMENT SHALL BE AS FOLLOWS:
1497	BETWEEN THE TERMINATIONS TIED TOGETHER AND THE MOUNTING HARDWARE.
1498	BETWEEN THE TERMINATIONS TIED TOGETHER AND THE CASE.
11522	BETWEEN MUTUALLY INSULATED PARTS.
1523	BETWEEN ALL INSULATED PARTS AND GROUND.
1524	BETWEEN CURRENT CARRYING PARTS AND THE CASE.
1520	SPECIAL PREPARATIONS OR CONDITIONS SHALL BE IN ACCORDANCE WITH 1520.
1372	FIRST TEST TEMPERATURE SHALL BE 1372 DEGREES CELSIUS.
1381	SECOND TEST TEMPERATURE SHALL BE 1381 DEGREES CELSIUS.
1383	TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1383 DEGREES CELSIUS.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
INTERMEDIATE CURRENT SWITCHING	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1952
AS FOLLOWS:	1954
REMAIN WITHIN SPECIFIED TOLERANCES.	1956
MAXIMUM CONTACT RESISTANCE (SELECT ONE)	
(OHMS)	1958
(MILLIOHMS)	1960
MAXIMUM CONTACT VOLTAGE DROP (SELECT ONE)	
(VOLTS)	1962
(MILLIVOLTS)	1964
OPEN OR CLOSE IN PROPER SEQUENCE	3280
MAXIMUM CONTACT BOUNCE	3281
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1966
PER MIL-STD-202, METHOD 312.	1968

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1952	INTERMEDIATE CURRENT SWITCHING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1952.
1954	INTERMEDIATE CURRENT SWITCHING. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1956	THE ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE(S).
1958	THE CONTACT RESISTANCE SHALL BE NOT GREATER THAN 1958 OHM(S).
1960	THE CONTACT RESISTANCE SHALL BENOT GREATER THAN 1960 MILLIOHM(S).
1962	THE VOLTAGE DROP ACROSS CLOSED CONTACTS SHALL BE NOT GREATER THAN 1962 VOLT(S).
1964	THE VOLTAGE DROP ACROSS CLOSED CONTACTS SHALL BE NOT GREATER THAN 1964 MILLIVOLT(S).
3280	THE ITEM(S) SHALL OPEN OR CLOSE IN PROPER SEQUENCE.
3281	CONTACT BOUNCE SHALL BE NOT GREATER THAN 3281
1966	INTERMEDIATE CURRENT SWITCHING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1966.
1968	INTERMEDIATE CURRENT SWITCHING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 312 OF MIL-STD-202.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
INTERMEDIATE CURRENT SWITCHING (CONT)	
PER MIL-STD–202, METHOD 312. (CONT)	
MINIMUM VOLTAGE ACROSS OPEN CONTACT (SELECT ONE)	
PERCENT OF APPLIED LOAD VOLTAGE (PERCENT)	1970
(VOLTS, AC)	1972
(VOLTS, DC)	1974
NUMBER OF OPERATIONS (QUANTITY)	1976
CYCLING RATE (CYCLES PER MINUTE)	1978
PLUS CYCLING RATE TOLERANCE (CYCLES PER MINUTE)	1980
MINUS CYCLING RATE TOLERANCE (CYCLES PER MINUTE)	1982
CYCLE “ON” AND “OFF” DURATION	
“ON” (PERCENT OF CYCLE)	1984
“OFF” (PERCENT OF CYCLE)	1986
MONITORING OF CONTACTS FOR STICKING IS NOT APPLICABLE	1988

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2336	THE ACTUATING/OPERATING FORCE SHALL BE NOT GREATER THAN 2336 NEWTON(S).
2342	THE ACTUATING/OPERATING FORCE SHALL BE NOT GREATER THAN 2342 POUND(S).
2340	THE ACTUATING/OPERATING FORCE SHALL BE NOT GREATER THAN 2340 OUNCE(S).
3100	THE RELEASE FORCE SHALL BE NOT LESS THAN 3100 OUNCE(S).
3102	THE RELEASE FORCE SHALL BE NOT LESS THAN 3102 POUND(S).
3104	THE RELEASE FORCE SHALL BE NOT LESS THAN 3104 NEWTON(S).
3106	PRETRAVEL SHALL BE NOT GREATER THAN 3106 INCH.
3108	PRETRAVEL SHALL BE NOT GREATER THAN 3108 MILLIMETER(S).
3110	OVERTRAVEL SHALL BE NOT LESS THAN 3110 INCH.
3112	OVERTRAVEL SHALL BE NOT LESS THAN 3112 MILLIMETER(S).

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3114	MOVEMENT DIFFERENTIAL SHALL BENOT GREATER THAN 3114 INCH.
3116	MOVEMENT DIFFERENTIAL SHALL BE NOT GREATER THAN 3116 MILLIMETER(S).
3118	MOVEMENT DIFFERENTIAL SHALL BE NOT LESS THAN 3118 INCH.
3120	MOVEMENT DIFFERENTIAL SHALL BE NOT LESS THAN 3120 MILLIMETER(S).
3122	PLUNGER TRAVEL SHALL BE 3122 INCH.
3124	PLUNGER TRAVEL SHALL BE 3124 MILLIMETER(S).
3126	FULL OVERTRAVEL FORCE SHALL BE 3126 POUND(S).
3128	FULL OVERTRAVEL FORCE SHALL BE 3128 NEWTON(S),

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
OPERATING CHARACTERISTICS (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2344
PER DOCUMENT (DOC DES)	2346
LOW TEMPERATURE TEST TEMPERATURE (DEGREES CELSIUS)	2348
LOW TEMPERATURE TEST DURATION (HOURS)	2350
ROOM TEMPERATURE TEST TEMPERATURE (DEGREES CELSIUS)	2352
OVERLOAD	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2280
AS FOLLOWS:	2282
MAXIMUM CONTACT RESISTANCE (SELECT ONE)	
(OHMS)	2284
(MILLIOHMS)	2286

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SHORT CIRCUIT (CONT)	
REQUIREMENTS (CONT)	
AS FOLLOWS:	2386
THERE SHALL BE NO WELDING OR STICKING OF CONTACTS.	2388
REMAIN MECHANICALLY AND ELECTRICALLY OPERATIVE AFTER TEST.	2390
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2391
PER DOCUMENT (DOC DES)	2392
MAXIMUM APPLIED TEST CURRENT (AMPERES)	2393
OPEN CIRCUIT TEST VOLTAGE (VOLTS)	2394
FREQUENCY (HERTZ)	2395
LOAD (TYPE)	2396
TEST CYCLES (QUANTITY)	2397
METHOD (SELECT ONE)	
I.	3158
II.	3160

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
7003	186						
7004	186						
7005	186						
7021	70						
7022	40						
7023	40						
7024	40						
7345	42						
7572	30						
7573	30						
7574	30						
7576	30						
7577	30						
7578	30						
7580	32						
7629	188						
7630	188						
7631	20						
7632	20						
7633	20						
7645	20						

* U.S. GOVERNMENT PRINTING OFFICE: 1983-605-034/1868

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:06Z
Check the source to verify that this is the current version before use.