MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

PINS AND KEYS

TO ALL HOLDERS OF MIL-STD-35-32B(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-32B(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
3	27 SEPTEMBER 1985	(Reprinted without change)	
4	30 JUNE 1992	4	27 SEPTEMBER 1985
19	27 SEPTEMBER 1985	(Reprinted without change)	
20	30 JUNE 1992	20	27 SEPTEMBER 1985

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of MIL-STD-35-32B(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT
Army-AV
Army-ER
Army-ME
Army-MR
Army-SC
Army-CR

User activity:
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A413)

AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:55Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
		MS35676	STRAIGHT GROOVE BRASS
		MS35677	CENTER GROOVE, CARBON STEEL
		MS35678	CENTER GROOVE, CRES
		MS35679	CENTER GROOVE, BRASS
PIN, LOCK	160006	MIL-P-23460	SELF RETAINING, POSITIVE LOCK
		MS17984	SINGLE ACTING, BUTTON HANDLE
		MS17985	SINGLE ACTING, "T" HANDLE
		MS17986	SINGLE ACTING, "L" HANDLE
		MS17987	SINGLE ACTING, RING HANDLE
		MS17988	DOUBLE ACTING, "T" HANDLE
		MS17989	DOUBLE ACTING, "L" HANDLE
		MS17990	DOUBLE ACTING, RING HANDLE
		NAS1332	POSITIVE LOCKING, SINGLE AND DOUBLE ACTING
		NAS1333 THRU NAS1346	POSITIVE LOCKING, SINGLE ACTING
		NAS1353 THRU NAS1366	POSITIVE LOCKING, DOUBLE ACTING
PIN, SPRING	160008	MIL-P-10971	TUBULAR (COILED AND SLOTTED)
		MS16562	SLOTTED
		MS39086	HEAVY DUTY
		MS51923	STANDARD DUTY
		MS51987	COILED, LIGHT DUTY

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:55Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
		NAS561	SLOTTED AND COILED, HEAVY DUTY
		NAS1407	COILED
		MS9047	STEEL, PHOSPHATE FINISH
		MS9048	STEEL, CADMIUM PLATED
		MS171401 THRU MS171900	CRES
PIN, STRAIGHT, HEADED	160009	MIL-P-5673	STRAIGHT, HEADED
		MS20392	DRILLED SHANK
		MIL-P-22235	(CLEVIS PINS)
		MS35810	STEEL, CADMIUM OR ZINC PLATED
		MIL-P-14250	SLOTTED TEMPLET STAND
		MS9463	.124 DIAMETER
		MS9464	.186 DIAMETER
		MS9465	.248 DIAMETER
		MS9466	.311 DIAMETER
		MS9467	.373 DIAMETER
		MS9468	.436 DIAMETER
		MS9842	.0937 DIAMETER
		MS9843	.1249 DIAMETER
		MS9844	.1874 DIAMETER
		MS9845	.2499 DIAMETER
		MS9846	.3124 DIAMETER
		MS9847	.3749 DIAMETER
		MS9848	.4999 DIAMETER
		AN121601 THRU AN121650	.125 NOMINAL
		AN121651 THRU AN121700	.187 NOMINAL
		AN121701 THRU AN121750	.250 NOMINAL
		AN121751 THRU AN121800	.312 NOMINAL
		AN121801 THRU AN121850	.375 NOMINAL
		AN121851 THRU AN121925	.500 NOMINAL

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:55Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	CONFIGURATION.
1009	CONFIGURATION ILLUSTRATION(S). THE CONFIGURATION SHALL BE AS SHOWN IN ILLUSTRATION(S) 1009.
7572	ALL DIMENSIONS, UNLESS OTHERWISE SPECIFIED, SHALL BE IN INCHES OR DEGREES.
7577	ALL DIMENSIONS, UNLESS OTHERWISE SPECIFIED, SHALL BE IN MILLIMETERS OR DEGREES.
4950	ILLUSTRATION(S). ILLUSTRATION(S) 4950 SHALL APPLY TO AID IN THE DEFINITION OF PARAMETERS.
	MATERIAL(S). MATERIAL(S) SHALL BE AS SPECIFIED IN THE MATERIAL TABLE. (NOTE: THE COMPONENT REFERENCE NUMBER(S) ARE ONLY TO REFERENCE THE SAME COMPONENT WHEN TABLE CONTINUATION IS NECESSARY.)
	FINISH(S). FINISH(S) SHALL BE AS SPECIFIED IN THE FINISH TABLE. (NOTE: THE COMPONENT REFERENCE NUMBER(S) ARE TO REFERENCE THE SAME COMPONENT WHEN TABLE CONTINUATION IS NECESSARY.)

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 202610-23T20:55Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
METALS	
DISSIMILAR METALS.	7580
DESIGN AND CONSTRUCTION	
CONCENTRICITY: MAXIMUM PIN DEVIATION FROM SHAFT AXIS (SELECT ONE)	
U.S.	
(INCHES)	1566
SI	
(MILLIMETERS)	1567
MAGNETIC PERMEABILITY PER MIL-I-17214	
MAXIMUM (VALUE)	1572
HEAD SHANK, ROTATION PLAY	
MAXIMUM (DEGREES)	1564
SCREW THREADS (DES)	1570
PER (DOC DES)	1571

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:55Z
Check the source to verify that this is the current version before use.