REVIEWER: OL MD MI MR PS

USER: MD SM

PART NUMBER	PACKAGING
MS36426-1	5 gal pail
MS36426-2	55 gal drum

FED. SUP CLASS
6850

SAFETY PRECAUTIONS: DANGER! HAZARDOUS LIQUID. CAUSES SEVERE BURNS. RAPIDLY ABSORBED THROUGH SKIN.

Do not ingest. Vapor irritating to eyes. Avoid breathing vapor, use protective mask. Do not get in eyes, on skin, on clothing; in case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes; for eyes get medical attention. Remove and wash contaminated clothing before reuse.

INTENDED USE: For use in cleaning either copper or aluminum-alloy aircraft oil coolers.

MATERIAL: Single-phase liquid. Ready to use.

REQUIREMENTS: Qualification required. The compound sh[all] silicates (except ethyl silicate as a [binder]), inorganic acids, cyanides, inert fill[ers] and shall be equal to or superior [to] formula. Minimum flash point, 8[0] pour point, minus 20 degrees F.

CONTROL F[ORMULA]

(For information. Does not ne[cessarily] either compound or quant[ity]

Ingredient	Percent by Weight
95 percent ethyl alcohol--	----------10
Cresol USP----------	----------10
Methylene Chloride----	----------70
Potassium oleate --	----------8
Wetting agent (po[tassium] specificatio[n]	----------2

DIRECTIONS FOR USE: [Immerse] in a washing machine that has [agitation] caused by pressure and vacuum. [Connect] hooked up that the cleaning compound [flows] opposite direction to that of the flow of [oil] are installed on the plane. The oil [system] with any standard petroleum solvent to [remove] and sludge. The oil cooler should not be [filled] cleaning compound. The cooler shall then be [agitated] the cleaning compound to remove the carbon deposits, [varnish], gums, lead deposits, and foreign contamination. The [cooler] shall then be rinsed with a standard petroleum solvent. If [the] oil cooler is not to be brightened, it shall be filled with a [suit]able preservative oil and drained prior to use or storage; other wise, no preservative should be applied.

NOTES:
1. Referenced documents shall be of the issue in effect on date of invitations for bid.
2. Safety Precaution given is based on compounds of the Control Formula.

Ⓐ CANCELLATION

AMSC N/A

CANCELLED
CANCELLED AFTER 2 FEB 1989
NO SUPERSEDING STANDARD

APPROVED 12 March 1965 REVISED Ⓐ 2 FEB 1989

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This document has been approved by the Materiel Command, Department of the Army, and is mandatory for use by the Army. All other military activities are required to comply with the standard when cited.

P.A. MU	TITLE	MILITARY STANDARD
Other Cust	CLEANING COMPOUND, SOLVENT oil-cooler	MS36426(MU)
Procurement Specification MIL-C-6864	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:40Z
Check the source to verify that this is the current version before use.