
FED. SUP CLASS
4730

FIGURE 1




45° SINGLE Y-BRANCH
45° DOUBLE Y-BRANCH

(A) TABLE I. Dimensions (Straight Sizes).

Nominal Pipe Size	End to End A	Center to End B	Center to End C
1-1/4	5	3-1/4	1-3/4
1-1/2	5-1/2	3-5/8	1-7/8
2	6-1/2	4-3/8	2-1/8
2-1/2	7-1/8	5-3/8	2-1/2
3	9	6-3/16	2-13/16
4	10-7/8	7-11/16	3-3/16
5	12-15/16	9-3/16	3-3/4
6	14-7/8	10-3/4	4-1/8
8	18-13/16	13-9/16	5-1/4

(A) TABLE II. Dimensions (Reducing Sizes).

FIGURE 2



45° SINGLE Y-BRANCH
REDUCING SIZE
45° DOUBLE Y-BRANCH
REDUCING SIZE

Nominal Pipe Size	End to End A	Center to End B	Center to End C	Center to End D
1-1/2 x 1-1/8	5-1/4	3-7/16	3-1/2	1-3/4
2 x 1-1/2	5-7/8	4-1/8	4-1/16	1-13/16
2-1/2 x 1-1/2	6-7/16	4-5/8	4-9/16	1-7/8
2-1/2 x 2	7-1/16	5-1/8	4-15/16	2-1/8
3 x 1-1/2	6-5/8	5-1/16	4-15/16	1-11/16
3 x 2	7-3/8	5-3/8	5-5/16	2-1/16
3 x 2-1/2	8	5-13/16	5-11/16	2-5/16
4 x 1-1/2	7-3/16	6-1/16	5-3/4	1-7/16
4 x 2	7-11/16	6-5/16	6	1-11/16
4 x 3	9-1/4	7-3/16	6-7/8	2-3/8
5 x 2	8-1/4	7-3/16	6-7/8	1-3/8
5 x 3	9-13/16	7-7/8	7-7/8	2-3/16
5 x 4	11-3/8	8-1/2	8-7/16	2-15/16
6 x 2	8-7/16	8-1/16	7-9/16	7/8
6 x 3	10	8-3/4	8-5/16	1-11/16
6 x 4	11-7/8	9-3/8	9-1/16	2-13/16
6 x 5	13	10	9-13/16	3-3/16
8 x 4	11-7/16	11	10-7/16	1
8 x 6	14-15/16	12-3/8	11-7/8	3-1/16

(A) NOTES:

1. MATERIAL: Material shall be in accordance with ANSI B16.12.
2. COATING: Castings shall be in accordance with ANSI B16.12 and shall be uncoated, coated with a bituminous composition or zinc coated as specified by the MS part number.
3. DIMENSIONS: All dimensions are in inches and shall be in accordance with ANSI B16.12. Double Y-branches have the same dimensions as single Y-branches.
4. THREADED ENDS: The threaded ends shall be in accordance with ANSI B16.12. All drainage fittings having openings at 90 degree nominal angle shall be tapped with a pitch of 1/4 inch in one foot with the pitch in the direction shown in ANSI B16.12.
5. GENERAL:
   (a) Referenced documents shall be of the issue in effect on date of invitations for bid or requests for proposal.
   (b) For design feature purposes, this standard takes precedence over procurement documents referenced herein.
   (c) The US Government has a Federal Supply Cataloging system which establishes approved item names to catalog and standardized items used within the government. The Federal Supply Cataloging System's approved item name may not be the same name that is used in commercial or industrial organizations. Therefore, the government name and equivalent commercial name are listed here for fittings on this MS.

(A) DENOTES CHANGES

P.A		TITLE	MILITARY STANDARD
NAVY-YD Other Cust ARMY-ME (A)	International Interest	(A) Y-BRANCHES, 45°, STRAIGHT AND REDUCING, CAST-IRON THREADED DRAINAGE	MS90525
Procurement Specification ANSI B16.12 (A)		SUPERSEDES:	PAGE 1 OF 2

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 4730-0409

(A) User activities: Army - CE, Navy - MC, Air Force - 99

(A) Review activities: Army - , Navy - , Air Force - , DLA-CS

APPROVED 31 October 1972 REVISED (A) 11 January 1983

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

Fed. Gov. Nomenclature	Commercial Nomenclature
Lateral, drainage pipe	45 degree single Y-branch
Lateral, drainage pipe	45 degree double Y-branch
Lateral, drainage pipe	45 degree single Y-branch (reducing)
Lateral, drainage pipe	45 degree double Y-branch (reducing)

6. PART NUMBER: The MS part number is formed by combining the MS number with a dash after it, the size code number, the Y-branch style letter, and the coating identification number.

MS 90525 - XX X X
Size code number (see note 7)
Y-branch style letter (see note 8)
Coating identification number (see note 9)

7. SIZE: The nominal pipe size is designated by two digits (see table III). For reducing Y-branches, the first size given is for the run ends and the other size is for the reduced branch end(s).

TABLE III. Code Number to Size.

Code Number	Nominal Pipe Size	Code Number	Nominal Pipe Size
01	1 1/4	15	3 X 2
02	1 1/2	16	3 X 2 1/2
03	2	17	4 X 1 1/2
04	2 1/2	18	4 X 2
05	3	19	4 X 3
06	4	20	5 X 2
07	5	21	5 X 3
08	6	22	5 X 4
09	8	23	6 X 2
10	1 1/2 X 1 1/4	24	6 X 3
11	2 X 1 1/2	25	6 X 4
12	2 1/2 X 1 1/2	26	6 X 5
13	2 1/2 X 2	27	8 X 4
14	3 X 1 1/2	28	8 X 6

8. Y-BRANCH STYLE: The style of Y-branch is designated by a single letter (see table IV).

TABLE IV. Code Letter to Y-Branch Style.

Code Letter	Y-Branch Style
V	45 degree single Y-branch
W	45 degree double Y-branch
X	45 degree single Y-branch (reducing)
Y	45 degree double Y-branch (reducing)

9. COATINGS: The type of coating is designated by a digit (see table V).

TABLE V. Code Number to Coating.

Code Number	Coating
1	Uncoated
2	Bituminous composition
3	Zinc coated

APPROVED 31 October 1972
REVISED (A) 11 January 1983

User activities: Army - CE
Navy - MC
Air Force - 99

(A) Review activities: Army -
Navy -
Air Force -
DLA-CS

P.A	Investigations Interest	TITLE	MILITARY STANDARD
NAVY-YD Other Cust ARMY-ME (A)		(A) Y-BRANCHES, 45°, STRAIGHT AND REDUCING, CAST-IRON THREADED DRAINAGE	MS90525
Procurement Specification ANSI B16.12 (A)		SUPERSEDES:	PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.