MILITARY SPECIFICATION

FUZES, GRENADE, H.E. M218, M219 AND XM224
LEAD CUP ASSEMBLY FOR
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-50274 (MU), dated 12 November 1969.

Page 5

4.2.2.2: Delete in its entirety and substitute:

"4.2.2.2. Specific gravity of lead cup charge (for informational purposes only). Twenty-five (25) loaded lead cup assemblies shall be subjected to this test. Results of this determination, shall not affect acceptance of lead cup assembly. Test shall be performed as specified in 4.4.3, and report shall include all calculations."

Page 8

4.3.3.3: Delete in its entirety and substitute:

"4.3.3.3 Functioning test (See 3.4) Major Defect Code No. 11001. Eighty (80) loaded cup assemblies shall be selected (ten (10) randomly selected per hour) from each eight (8) hours production and subjected to this test. If two (2) or more fail to comply with requirement specified in 3.4, the eight (8) hours production represented by the sample shall be rejected. The test shall be performed as specified in 4.4.1."

4.3.3.4: Delete in its entirety and substitute:

"4.3.3.4 Weight of lead cup charge (See Dwg. 8833562) Major Defect, Code No. 10001. A sample of five (5) loaded lead cup assemblies shall be selected from each four (4) hours production and weight of charge shall be determined. If any sample fails to conform to the drawing requirements, the four (4) hours production shall be rejected."

4.3.3.5: Delete in its entirety.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No. 1330-A162

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:19Z
Check the source to verify that this is the current version before use.