INCH- POUND

MIL- P-50317B (AR)
AMENDMENT 1
27 August 1992

MILITARY SPECIFICATION

PROTECTOR, OVERVOLTAGE: 10548031 (+5 VOLT FILTER)

This Amendment forms a part of Military Specification MIL-P-50317B dated, 11 MAY 1990, and is approved for use by the U.S. Army Armament, Munitions and Chemical command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Delete the following military standard:

"MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2: Add the following drawing:

12950877 - Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete paragraph 3.3.1 in its entirety and substitute the following:

'3.3.1 Vibation. The +5 volt filter shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the M113 armored personnel carrier."

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGES 3 AND 4

3.3.3, 3.3.3.1 and 3.3.3.2: Delete paragraphs in their entirety and substitute the following:

"3.3.3 Altitude Operating. The +5 volt filter shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 5

3.8: Delete paragraph 3.8 in its entirety and substitute the following:

"3.8 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877"

PAGE 13

4.7.1.1: First sentence: Delete and substitute: "Vibration. This test shall be performed as specified in Method 514, Category 8, Procedure I, of MIL-STD-810 and paragraph 3.3.1 herein."

PAGE 14

4.7.1.2: First sentence: Delete '516.3' and substitute '516".

4.7.1.3: Delete paragraph 4.7.1.3 in its entirety and substitute the following:

"4.7.l.3 Altitude Operating. This test shall be performed as specified in Procedure II, Method 500, of MXL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

4.7.1.4.1: First sentence: Delete ‘501.2" and substitute “501”.

4.7.1.4.2: First sentence: Delete “502.2” and substitute "502".

4.7.1.5: First sentence: Delete “507.2” and substitute “507”.

PAGE 15

4.8: Delete paragraph 4.8 in its entirety and substitute:

“4.8 Soldering Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.8.”

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A809)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.