INCH POUND
MIL-R-50338B (ar)
AMENDMENT 1
25 September 1992

# "MILITARY SPECIFICATION

# REGULATOR, VOLTAGE: 10548034 AND 11727766

This Amendment forms a part of Military Specification MIL-R-50318B dated, 30 April 1990, and is approved for use by the U.S. Army Armament, Munitions and Chemical command and is available for use by all Departments and Agencies of the Department of Defense.

## PAGE 2

2.1: Delete the following military standard:

MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies

2.1.2: Add the following drawing:

'12950877 - Requirements for Soldering Electrical and Electronic Assemblies

## PAGE 3

3.3.1: Delete paragraph 3.3.1 in its entirety and substitute:

"3.3: Vibration The 15-volt regulator shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the Ml13 armored personnel carrier."



DISTRIBUTTON STATEMENT' A Approvedforpublic release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGES 3 AND 4

3.3.3, 3.3.3.1, and 3.3.3.2: Delete paragraphs in their entirety and substitute:

"3.3.3 Altitude operating. The 15-volt regulator shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 4

3.7: Delete paragraph 3.7 in its entirety and substitute:

"3.7 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 13

4.7.1.1: Delete first sentence of paragraph and substitute:

'4.7.1.1 Vibration. This test shall be performed as specified in Method 514, Category 8, Procedure I of MIL-STD-810 and paragraph 3.3.1 herein."

4.7.1.2: Delete '516.3 and substitute 516.

4.7.1.3: Delete paragraph 4.7.1.3 in its entirety and substitute:

'4.7.1.3 Altitude Operating This test shall be performed as specified in Procedure II, Method 500, of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3.

4.7.1.4.1: Delete "501.2 and substitute '501..

PAGE 14

4.7.1.4.2: Delete 502.2 and substitute '502-.

4.7.1.5: Delete '507.2 and substitute '507.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

**PAGE** 15

4.8: **Delete "4.8" in its entirety and substitute:**

"4.8 **Soldering.** Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.7."

**custodian :**
**Army-AR**

**Preparing activity:**
**Army-AR**

**(Project 1285 -A810)**



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.