INCH-POUND

MIL-R-50319B (AR)
AMENDMENT 1
09 October 1992

'MILITARY SPeCIFIcaTION

REGULAR, VOLTAGE: 10548034 AND 11727763

This Amendment forms a part of Military Specification MIIJ-R-50319B dated, 27 April 1990, and is approved for use by the U.S. Army armament, Munitions and Chemical command, and is available for use by all Department and Agencies of the Department of Defense.

PAGE 2

2.1.1: Delete the following military standard:

Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2: add the following drawing:

12950877 Requirements for Soldering Electrical and Electronic Assemblies"

PAGE 3

3.3.1: Delete paragraph 3.3.1 in its entirety and substitute:

'3.3.1 vibration The 25-volt regulator shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to the equivalent of 6000 miles of track-laying vehicle operational vibration as defined by MIL-STD-810 narrowband random-on-random data for equipment installed on the deck of the Ml13 armored personnel carriers

DISTRIBUTiON statement A Approvodforpublic release;distdbution Is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

PAGE 3

3.3.3, 3.3.3.1 and 3.3.3.2: Delete paragraphs **in their entirety and substitute:**

3.3.3 Altitude Operating. The 25-volt regulator shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered **at** 10,000 feet above sea level (20.6 **inches of Hg)**

PAGE 5

3.8: Delete paragraph 3.8 in its entirety and substitute:

'3.8 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

PAGE 12

4.7.1.1: Delete first sentence and substitute the following:

'4.7.1.1 Vibration. This test shall be performed as specified in Method 514, Category 8, Procedure I of MIL-STD-810 and paragraph 3.3.1 herein."

4.7.1.2: Delete "516.3" and substitute "516".

4.7.1.3: Delete paragraph 4.7.1.3 in its entirety and substitute:

"4.7.1.3 Altitude Operating This test shall be perfomed as specified in Procedure II, Method 500, *of MIL-*STD-810 . The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.

4.7.1.4.1: Delete ‘501.2” and substitute ‘501”.

4.7.1.4.2: Delete ‘502.2” and substitute ‘502”.

PAGE 13

4.7.1.5: Delete ‘507.2” and substitute 507

PAGE 14

4.8: Delete paragraph 4.8 in its entirety and substitute:

“4.8 Soldering Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.8.”

Custodian:
Army-AR

Preparing activity:
ARMY-AR
(Project 1285-A811)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:21Z
Check the source to verify that this is the current version before use.