[INCH-POUND]
A-A-1755B
October 12, 1993
SUPERSEDING
A-A-1755A
July 10, 1987

COMMERCIAL ITEM DESCRIPTION

STRAINER, CHINA CAP

The General Services Administration has authorized the use of this commercial item description as a replacement for Federal Specification RR-K-260, type IX, which has been canceled.

1. SCOPE

1.1 Scope. This commercial item description covers a china cap strainer with a cone shaped roller.

2. APPLICABLE DOCUMENTS

2.1 The documents referenced in this commercial item description shall be the issues in effect on the date of issuance of the invitation for bids or request for proposal unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Federal Standard:

FED-STD-376 - Preferred Metric Units For General Use By The Federal Government.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, TX 76102

DISTRIBUTION STATEMENT A : Approved for public release; distribution is unlimited.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

Copies of Federal standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA, and the GSA Specifications Unit (3FBP-W), Suite 8100, 470 E. L'Enfant Plaza, S.W., Washington, DC 20407.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Copies of military standards may be obtained from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

ASTM Standard:

E 29 - Standard Practice For Using Significant Digits In Test Data To Determine Conformance With Specifications.

Application for copies of ASTM standards should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.

NSF International:

Standard Number 2	-	Food Service Equipment.
Criteria C-2	-	Special Equipment and/or Devices.
Annual Listing	-	Food Service Equipment and Related Products, Components and Materials.

Application for NSF International documents should be addressed to the NSF International, 3475 Plymouth Road, P.O. Box 130140, Ann Arbor, MI 48113-0140.

3. SALIENT CHARACTERISTICS

3.1 Design and construction. The strainer body shall be formed from 0.0508 inch (1.3 mm) thick minimum sheet aluminum. The strainer shall have an inside diameter of 10 inches (254 mm) plus or minus 1/4 inch (6.4 mm). The strainer capacity shall be 5-1/2 quarts (5.2 liters), plus 10 percent, minus 5 percent. The strainer shall have multiple perforations with a minimum diameter of 5/64 inch (2.0 mm) each. The strainer shall have a cast aluminum or formed stainless steel handle provided with a hang-up hole. The strainer shall have hook(s) for hanging over edge of pot. The strainer shall be furnished with a cone shaped roller, rounded at the small end to match the radius at the bottom of the strainer. The roller shall be made from aluminum alloy, styrene, modified rubber, a suitable hardwood, or similar impervious materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

3.2 NSF International compliance. Prior to approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the items offered meet the applicable requirements of NSF International Standard No. 2 or Criteria C-2. NSF International compliance will not be required for the roller. Satisfactory evidence of this compliance may be any of the following:

(1) A listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished item, or

(2) A certification issued by NSF International under this special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory, acceptable to the contracting officer and the medical authority of the service for which the items are being procured, indicating that the item has been tested and conforms to NSF International Standard No. 2 or Criteria C-2. Acceptability of the testing laboratory by the medical authority shall be determined prior to initiation of procurement actions.

3.3 Marking. The strainer shall be marked with the manufacturer's name, trade name, or trademark of such known character that the source of manufacture may be readily determined.

3.4 Workmanship. The finished strainers, with rollers, shall be free from sharp edges, slivers, burrs, scratches, pits, tool marks, and other defects which may affect appearance or serviceability.

3.5 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580, as amended, to the maximum extent practicable.

3.6 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The values stated in parentheses are for informational purposes only.

3.7 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the specification preparing activity for changes to this document.

3.8 Commercial item. The use of the term "commercial item description" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Certification. The contractor shall certify, and maintain objective quality evidence, that the product offered meets this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. The contractor may use his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.3 Sampling. The levels of inspection and acceptable quality levels (AQL's) shall be in accordance with MIL-STD-105.

4.4 Lot formation. All strainers from the same manufacturer offered for delivery at one time shall be considered a lot for purposes of inspection.

4.5 Sampling for visual and dimensional examination. A random sample of strainers shall be selected from each lot in accordance with inspection level S-4, AQL 4.0 expressed in terms of defects per hundred units. The sample unit shall be one strainer with roller. The sample strainer shall be visually and dimensionally examined to verify compliance with table I and the remainder of this commercial item description. All dimensions are absolute as defined in ASTM E 29.

TABLE I - Examination for defects

Examine	Defect
Finish	Area of corrosion, stain, or discoloration
Construction and Workmanship	Dimensions not as specified. Construction not as specified. Scratch, tool mark, or pitted surface. Any sharp edge, sliver, or burr. Marking missing or illegible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

4.6 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate, and shipping containers (as applicable) for conformance with the packaging, packing, and marking required in the contract or order. Samples shall be selected in accordance with inspection level S-2, AQL 6.5, expressed in terms of defects per hundred units. The sample unit shall be one shipping container.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. The packaging, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should include the following information in procurement documents (if applicable):

a. Title, number and date of this commercial item description.
b. The packaging, packing, and marking required.

6.2 National Stock Number (NSN). The following NSN corresponds to this CID: 7330-00-815-1456.

Military Coordinating Activity:

Army - GL

Custodians:
Army - GL
Navy - SA
Air Force - 99

Civil Agency Coordinating Activity:

VA - OSS

Review Activities:
Army - MD, QM
Air Force - 84, 50

PREPARING ACTIVITY:

GSA - FSS

User Activity:
Navy - MC

(DoD Project 7330-0681)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.