MIL-I-38121A(USAF)
AMENDMENT 1
26 December 1963

MILITARY SPECIFICATION

INDICATOR, PRESSURE EGU-9/A

This amendment forms a part of Military Specification MIL-I-38121A(USAF) dated 5 September 1963.

Page 4, figure 1: Delete "1/8 DIVIDER TRIANGLE" and substitute "DIVIDER TRIANGLE 0.069 WIDTH, 0.06 HEIGHT".

Page 7, paragraph 3.8.2: Delete and substitute:

"3.8.2 DIAL TO GLASS DISTANCE.- The distance between the indicator dial and the inside of the glass nearest the dial shall not exceed 0.188 inch."

Page 7, paragraph 3.8.3.1: Under "Height or Length Inch ±1/64," opposite "0.10 Graduations," delete "5/32" and substitute "3/16" and opposite "0.02 Graduations," delete "5/64" and substitute "7/64". Under "Width of Linear Graduation Inch ±0.005," opposite "Counter numerals," delete "0.016" and substitute "0.020".

Page 8, paragraph 3.8.5, line 12: Delete "0.156 $^{+0.000}_{-0.031}$ inch" substitute "0.203 $^{+0.0156}_{-0.0310}$ inch overall".

Page 8, paragraph 3.9: Delete and substitute:

"3.9 ELECTRICAL RECEPTACLE.- The indicator shall be provided with an MS33678H-16S-1P electrical receptacle suitable for hermetic sealing. Pin connections shall be as follows:

Pin	Functions
A	Spare
B	Ground
C	Stator
D	Stator
E	Power (26V 400 cps)
F	5V light when required
G	5V light ground

Page 8, paragraph 3.11, line 2: Delete "0.75" and substitute "0.85".

FSC 6620

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:56Z
Check the source to verify that this is the current version before use.

Page 12, paragraph 4.6.2: In line 3, delete "115 ±2V" and substitute "26 ±1V". In subparagraph a, line 2, delete "(usually 30 to 50 millivolts)". In subparagraph b, lines 2 and 3: Delete "(approximately 104.8V)" and "(approximately 103.2V)".

Page 16, paragraph 4.6.15.1, line 2: Delete "level IV" and substitute "level III".

PAS/eld
SEMS

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:56Z
Check the source to verify that this is the current version before use.