INCH-POUND

MIL-I-38135B(USAF)
AMENDMENT 3
10 AUGUST 1992
SUPERSEDING
AMENDMENT 2
18 MARCH 1986

MILITARY SPECIFICATION

INDICATOR, INDICATED AIRSPEED
AVU-19/A, STANDBY

This amendment forms a part of MIL-I-38135B(USAF), dated 11 March 1971, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1 Add title: "Scope".

Delete "2.1" and add "2.1 Government Documents".

Add: "2.1.1 Specifications, Standards, and Handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

* Under SPECIFICATION, Federal delete "QQ-P-416"; "PPP-B-601"; "PPP-B-636"; and add: "PPP-C-795 Cushioning Material, Packaging (Flexible Closed Cell Plastic Film For Long Shipping Cycle Applications) and "PPP-B-1672, Shipping Reusable With Cushioning."

* Under SPECIFICATIONS, Military, add: "MIL-D-3464 Desiccants, Activated, Bagged, Packaging Use And Static Dehumidification"; Change title of MIL-C-5541 to read: "Chemical Conversion Coatings on Aluminum And Aluminum Alloy" and "MIL-C-83433 Coating, Aluminum, ION Vapor Deposited."

Add boxed paragraph to bottom center of page:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/TICLA Tinker AFB OK 73145-5990 using the Standardization document Improvement proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

* Under STANDARDS, Federal, add: "FED-STD-101 Test Procedures For Packaging Materials".

DISTRIBUTION STATEMENT. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil - Downloaded: 2026-10-21T14:57Z
Check the source to verify that this is the current version before use.

Under STANDARDS, Military, delete "MIL-STD-100" and add. "DOD-STD-100" with the same title. Delete "MIL-STD-143", "MIL-STD-1186", add. "MIL-STD-970 Standards and Specification, Order Of Precedence For The Selection Of", "MIL-STD-2073/1A DOD Materiel Procedures For Development & Application Of Packaging Requirements"; MS28105, change the title to read. "Cover Glass, Aircraft Instrument Dial" and add. "MS 20003 Indicator, Humidity, Card, Three-Spot Impregnated Areas".

* Add: "2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained."

* 3.2 Line 3 delete "MIL-STD-143" and add: "MIL-STD-970."

3.3.1 Line 4 add: "(see 6.5)."

PAGE 3

* 3.3.3 Line 2 delete "spray" and add. "fog".

Add. 3.3.4.1 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item.

PAGE 7

3.6 Line 4 delete "MIL-STD-100" and add. "DOD-STD-100."

PAGE 13

Delete "3.15.2" and add. "3.15.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the preparing activity. Cadmium plating must be avaided when satisfactory alternative processes can be used."

PAGE 14

Delete "4.1" entirely and add new: "4.1 Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. the Government reserves the right to perform any of the inspections set forth in his specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:57Z
Check the source to verify that this is the current version before use.

Add: "4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the government to accept defective material."

PAGE 16

4.5.2.2 n: Delete.

PAGE 17

4.6.2 Third sentence: Delete the first four words of the sentence and add: "With the source connections pinched off at the indicator...".

PAGE 21

4.6.23: Delete.

* Delete Section 5 in its entirety and add the following:

"5. PACKAGING

5.1 Preservation. Preservation shall be level "A" or "C" as specified (see 6.2).

5.1.1 Preservation-Packaging. Unless otherwise specified by the contracting activity, item shall be packaged in quantity unit pack (QUP) of one each. Each item will be provided a preservation method IIc IAW MIL-P-116.

5.1.2 Cleaning. Item shall be cleaned IAW MIL-P-116 C-1 process.

5.1.3 Drying. Immediately after cleaning, the item shall be dried following any one or combination of the drying procedures listed in MIL-P-116. The drying procedures employed shall not be injurious to the item.

5.1.4 Level A. Item shall be preserved IAW MIL-P-116 and MIL-STD-2073/1A to provide a method IIc.

5.1.5 Level C. Item shall be individually preserved in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the first receiving activity as specified in MIL-P-116 and MIL-STD-2073/1A.

5.2 Packing. Packing shall be level "A", "B", or "C" as specified (see 6.2).

5.2.1 Container-Cushioning. Intermediate container requirements shall conform to PPP-B-1672, weather-resistant, unless otherwise specified by the contracting activity. Intermediate containers shall be large enough to allow for

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:57Z
Check the source to verify that this is the current version before use.

application of sufficient cushioning material between the unit container and intermediate container. Cushioning material shall be sufficient in density and thickness in ensure shock transmission does not exceed peak values in G's established for the item.

5 2.2 Level A. Item will be preserved as specified in 5.1 and shall be packed in exterior containers conforming to PPP-B-1672, weather resistant, unless otherwise specified by the contracting activity. Exterior container shall be uniform, shape, size, and minimum tare and cube, consistent with the protection required Closure shall be in accordance with appropriate PPP-B-1672 procedures, as specified by the contractor, special packaging instruction (SPI) and contracting activity.

5.2.3 Level B Same as level 'A' unless otherwise specified by special packaging instructions (SPI) or the contracting activity

5 2 4 Level C Item will be packed in containers in such a manner as to afford adequate protection against physical damage during direct domestic shipment from the supply source to the first receiving activity These packs shall conform to MIL-STD-2073/1A

5.3 Marking Unit, intermediate, and exterior containers shall be marked IAW special markings required by the contractor, special packaging instructions (SPI), and MIL-STD-129.

5.4 Inspection and Test. Test of methods of preservation shall be accomplished in accordance with Section 4 of MIL-P-116 to ensure compliance with Section 5 of this specification. Packaging tests shall be conducted IAW rough handling as specified in FED-STD-101

* Under 6. NOTES add: '(This section contains information of a general or explanatory nature that may be helpful, but not mandatory)'

* Add: '6.2(d) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).'

Delete '6.5' and add:

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
AIR FORCE -99

Preparing Activity:
AIR FORCE -71

Project number·
6610-F342

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:57Z
Check the source to verify that this is the current version before use.