MILITARY SPECIFICATION

CABLES, TELEPHONE; SHIELDED
(INSIDE WIRING)

This amendment forms a part of Military Specification MIL-C-55357(EL), dated 13 October 1971, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1

1.2 Classification - Delete table in its entirety and substitute the following:

No. of pairs	Total number of conductors	Outside diameter of finished cables (max. average)
		Inches
3	6	0.43
6	12	.47
11	22	.58
16	32	.64
21	42	.70
26	52	.77
32	64	.82
51	102	.98
76	152	1.14
101	202	1.33

Page 2

3.1.1 Pair twist - Delete second sentence in its entirety and substitute the following:

"To minimize cross-talk, each pair in a concentric type cable shall have a twist with a length of lay different from any other pair in the cable; each pair in a unit type cable shall have a twist with a length of lay different from any other pair in that unit."

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:15Z
Check the source to verify that this is the current version before use.

Page 3

3.6.1 Layer type construction - At end of paragraph, add the following new sentence:

"Construction of the cable with layers wound in alternating directions is optional."

Page 4

3.6.2 Unit-type construction - Delete last sentence in its entirety and substitute the following:

"Units shall be divided into sub-units as shown in Figure 1."

3.7 Identification marker - Delete first sentence in its entirety and substitute the following:

"Each length of cable shall include a marker tape showing name of manufacturer, plant location, year of manufacture and sequentially numbered footage mark, stamped or printed at intervals of one foot."

Page 6

Table III. Shielding - Delete in its entirety and substitute the following:

(TABLE ON FOLLOWING PAGE)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:15Z
Check the source to verify that this is the current version before use.

Table III. Shielding.

No. of Pairs	Copper shield (inner)		Steel shield (outer)	
	No. of ends	Width, nom. (±5%)	No. of ends	Width, nom. (±5%)
3	12 14	0.035 .035	15 18	0.040 .040
6	14 15	.045 .045	12 18	.060 .040
11	18	.045	14 15	.075 .075
16	12 14	.075 .075	15 (12 (6	.075 .075) .040)
21	15 18	.075 .075	15 18	.075 .075
26	15 18	.075 .075	18	.075
32	18	.075	18	.075
51	12 14	.125 .125	14 15	.125 .125
76	15 (12 (6	.125 .125) .075)	18	.125
101	18	.125	18	.125

NOTE: Where more than one construction is shown above for a specific number of pairs, this denotes alternate constructions which are permitted, provided that the requirements of 3.8 and 3.10 are met.

3.10 Outer steel shield - At end of paragraph, add the following:
"(See 6.3)"

Page 8

3.13.7 Shield resistance - Immediately following "(See 4.5.2.7)", add the following sentence:

"Shield resistance shall vary in inverse proportion to the diameter beneath the shield".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:15Z
Check the source to verify that this is the current version before use.

Page 14

New Paragraph - Immediately following 6.2.1, add new paragraph as follows:

"6.3 Steel material for shielding. Steel material used for shielding is not inherently corrosion resistant. It is therefore recommended that this material be stored in vapor-proof wrapping prior to the manufacture of the cable in order to prevent corrosion of the material while in storage".

Custodian:
Army - EL

Preparing Activity:
Army - EL

Project No. 6145-A027

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:15Z
Check the source to verify that this is the current version before use.