MIL-C-63182A(AR)
26 AUGUST 1981
SUPERSEDING
MIL-C-63182
23 JANUARY 1981

MILITARY SPECIFICATION

CASE SECTION, BALLISTIC, REAR; MODIFIED

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions and the preparation for delivery criteria for CASE SECTION, BALLISTIC, REAR, used to train troops in the classroom.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS (see 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

8837375 - Environmental Testing Criteria for Shipping Containers.
9237673 - Case Section, Ballistic, Rear: Modified
9324779 - Packing and Marking for Drum Metal, Shipping for LLC Exchange Trainer

FSC: 1115

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The training warhead section shall comply with all requirements specified on the drawing (dwg) 9237673, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Environmental Test. The container and trainer within shall comply with the vibration and free fall drop requirements per dwg 8837375. Testing shall be as specified in 4.3.2.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

the contract or order, the suppliers may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 1 complete assembly (see dwg 9237673) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics		X
2. Vibration		X
3. Free fall drop		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation. The formation of an inspection lot and related functions shall be in accordance with Section 5, MIL-STD-105. A lot shall consist if parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the major characteristic Table II, inspected for all characteristics. If any characteristic in the sample are found to be defective, 100% inspection of the characteristic

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

that failed shall be required of the entire lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed. Subsequent acceptance, after correction of defects, will be based upon 100% reinspection of applicable characteristics.

Table II

Major Characteristic

Lot Size	Sample Size
1-25	100% inspection
26-30	25
31-35	26
36-40	27
41-45	28
46-50	29
51-55	30
56-60	31
61-65	32
66-70	33
71-75	34
76-85	35
86-95	36
96-110	37
111-130	38
131-156	39
157-190	40
191-240	41
241-340	42
341-520	43
521-1120	44
1121-and over	45

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-195. Inspection shall be conducted as follows:

4.3.2.1.1 Case Section, Ballistic Rear; Modified (dwg 9237673).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Potting compound is missing or insufficient at inserts (8).	Visual
102.	Incorrect alignment of bracket thru holes (8)	Gage
103.	Marking missing, incorrect, illegible (see 9237679).	Visual
104.	Protective finish damaged or missing exposing base metal.	Visual
105.	Any component part missing, damaged or incorrectly assembled.	Visual
106.	Incorrect torque on bracket mounting bolts (8) and top hat bolts (6).	Gage
107.	Serialization missing or improper (see 3.4)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6).	Visual

4.3.2.1.2 Packing and marking for drum metal shipping for LLC Exchange Trainer. (see dwg. 9324779).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Identification plate missing, NSN SER. NO; nomenclature, missing or illegible	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Major (cont)		
102.	Four bronze inch square patches missing or improperly located	Visual
103.	Container cushions not in accordance with dwg. 9324780	Visual
104.	Container support not in accordance with dwg. 9324781	Visual
105.	Painting peeling, scratched, inadequate coverage, wrong color	Visual
106.	Structural damage which will preclude use of container for its intended purpose.	Visual
107.	Marking illegible or does not agree with EML.	Visual
108.	Lead wire seal missing.	Visual
Minor: None defined.		

4.3.2.1.3 Preparation for delivery (see dwg. 9324779).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Packaging and packing not in accordance with dwg..	Visual
102.	Marking not in accordance with dwg.	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.10).	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
Test Load	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.4 Acceptance inspection equipment. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Test load. Assemble a simulated DOE trainer module to the skin mounting brackets and allow simulator to stand for 6 ± 1 minutes. Upon completion of this test examine the trainer for physical damage.

4.4.2 Environmental Test.

4.4.2.1 Vibration. The container, with trainer and simulated DOE module within, shall be placed on a suitable fixture and withstand sinusoidal vibration along each of its three (3) mutually perpendicular axes using a logarithmic sweep of 84 minutes per cycle (5-200-5Hz) with the following parameters:

Frequency (Hz)	Amplitude
5-7	1.0 inch dia.
7-92	2.5 g
92-110	.0058 inch da.
110-200	3.5 g

4.4.2.2 Free fall drop.

4.4.2.2.1 Flat. The container, with trainer and simulated DOE module within, shall be dropped free fall from a height of 36 inches onto a concrete or other similarly hard surface four (4) times, once on the top and bottom and twice on the side at points ninety (90) degrees apart. This test shall be repeated from a drop height of 24 inches.

4.4.2.2.2 Edge. The container, with trainer and simulated DOE module within, shall be dropped free fall from a

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

height of 36 inches onto a concrete or other similarly hard surface four (4) times. Two falls on the top edges 180° apart with one fall on the locking ring lug, and two falls 180° apart on bottom edges.

4.2.2.3 Flat on another container. The container, with the trainer and simulated DOE module within, shall be dropped free fall from a height of 36 inches across the longitudinal axis of a similar container.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The training warhead section shall be packaged in accordance with dwg 9324779 using the specified moisture barrier.

5.1.2 Level C. The training warhead section shall be packaged in accordance with dwg 9324779 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The training warhead section shall be packed in accordance with dwg 9324779.

5.3 Marking. Marking shall be as specified in accordance with dwg 9324779.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading of US Army Armament Research and Development Command (ARRADCOM) may also include drawings

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Project No. 1115-A076

Preparing activity:
Army-AR

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.