INCH-POUND
MIL-DTL-62069F(AT)
31 August 1998
SUPERSEDING
MIL-PRF-62069E(AT)
2 March 1996

DETAIL SPECIFICATION

CONTROL, DIRECTIONAL SIGNAL LIGHT, AUTOMOTIVE: 24 VOLT DC, SOLID STATE

This specification is approved for use by the U.S. Army Tank-automotive and Armaments Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers control and flasher units of the solid state type used on military vehicles.

1.2 Classification. For the purpose of this specification, components are classified as follows (see 6.2):

Unit 1	- Control Unit
Unit 2	- Flasher Unit

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirement documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC 2590

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

A-A-50588	- Lamp, T-3-1/4, Miniature Bayonet, Single Contact.
A-A-52463	- Lamp Bulbs, Incandescent, Miniature, Single and Double Contact, Bayonet Candelabra Base.

DEPARTMENT OF DEFENSE

MIL-B-11188/1	- Battery, Storage, Lead-Acid, Waterproof.

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-202	- Electronic and Electrical Component Parts, Test Methods for.
MIL-STD-462	- Measurement of Electromagnetic Interference Characteristics, Test Methods Standards for.

(Unless otherwise indicated, copies of the above specifications and standards are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

11613631	- Flasher, Solid State.
11613632	- Control Assy. Directional Signal (Waterproof).

(Copies of the drawings are available from the U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000.)

DEPARTMENT OF TRANSPORTATION (DOT)

Code of Federal Regulations, Title 10, Part 40.
Code of Federal Regulations, Part 49.

(Applications for copies should be addressed to the U.S. Department of Transportation, Superintendent of Documents, Government Printing Office, Washington, DC 20402).

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME B1.1	- Unified Inch Screw Threads (UN and UNR Thread Form) (DoD Adopted).

(Application for copies should be addressed to American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B117	- Standard Practice for Operating Salt Spray (Fog) Apparatus.

(Application for copies should be addressed to American Society for Testing and Materials, 100 Barr Harbor Dr., West Conshohocken, PA 19428.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE AS478 - Identification Marking Methods.

(Application for copies should be addressed to Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2) a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Materials. Materials shall be as specified herein, on applicable specifications, and on applicable drawings. Materials not specifically designated shall be suitable for use in the control and flasher units operating over an ambient temperature range from -65 to 160 degree Fahrenheit (°F) without any change in physical or dimensional properties that would result in operation of the units falling outside of the limits specified herein. Asbestos, cadmium, and radioactive material shall not be used in this item. Radioactive material is defined by Code of Federal Regulations, Title 10, Part 40, and as other radioactive material in which the radioactivity is greater than 0.002 microcuries per gram or 0.01 microcuries total activity for the item.

3.2.1 Potting compound. Potting compound, when used, shall be non-hygroscopic, shall comply with shock and vibration requirements specified herein, and shall not support fungus growth.

3.2.2 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.3 Design and construction. The control and flasher covered by this specification shall conform to the interface, volumetric, and mounting requirements of Drawings 11613632 and 11613631, respectively. This signal light control shall comply with all applicable Department of Transportation requirements found in part 49 of the Code of Federal Regulations.

3.3.1 Dissimilar metals. Except where necessary to complete an electrical circuit, contact between dissimilar metals which would encourage galvanic corrosion shall be avoided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

3.3.2 Standard parts. Military standard parts shall be used wherever possible, if repair parts are called out for the control and flasher.

3.3.3 Threaded parts. All screw threads shall conform to ASME B1.1.

3.3.4 Flash indicator lamp. The flash indicator lamp for the control unit shall conform to A-A-50588. The lamp indicator light opening shall be located as shown on Drawing 11613632. Luminescence from the lamp opening shall be a green color without glare that would blind the driver. Emitting surface shall have a minimum area equivalent to a 0.19 inches (in.) diameter circle.

3.3.4.1 Flash indicator lamp replacement. Replacement of the flash indicator lamp for the control unit shall be capable of being accomplished without removing the control unit from the steering column. Access for replacement shall be accomplished by removing the lens or by loosening the captive retaining devices permitting movement of a captive subassembly of the control unit. All components exposed during replacement of the bulb shall be captive (including seals). When the lens assembly or the captive subassembly of the control unit is located on the basic control unit housing, the operation of replacing the lamp shall not expose the switch contact or any other moving internal parts of the control unit to the entry of foreign matter, and the unit shall maintain the waterproofness requirement after lamp replacement.

3.3.5 Hazard warning switch. The control unit shall have a hazard warning switch in a location such that accidental operation shall be prevented. The hazard warning switching device shall disengage when the signal control lever is actuated.

3.4 Electrical.


3.4.1 Voltage rating. Control and flasher units shall be suitable for use in nominal 24 volt direct current (Vdc) electrical systems.

3.4.2 Current rating. Except as otherwise indicated, current carrying parts shall be able to withstand a continuous dc current of 10 amperes (A) without damage.

3.4.3 Load impedance. The flasher unit shall be operable with an inductive load of 0.20 millihenries placed in series with the lamp load.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

3.4.4 Flashing. The “flashing rate” and the “percent on time” of normally closed type flashers shall be within the unshaded area of the polygon below.



“Flashing rate” and “percent on time” shall be measured after the flasher has been operating for five consecutive cycles and shall be an average of at least three consecutive cycles. The “flashing rate”, as defined in 6.4.4, shall be not less than 60 nor more than 120 flashes per minute. The average “percent on time”, as defined in 6.4.5, shall be as indicated in the polygon above. When the control lever or hazard warning switch is returned to neutral position, the “turn off time”, as defined in 6.4.7, shall be less than 1.0 second.

3.4.5 Overload.

3.4.5.1 Control unit. The control unit shall not be adversely affected by the application of a simulated short circuit condition.

3.4.5.2 Flasher unit. The flasher unit shall not be adversely affected by the application of a simulated short circuit condition. The flasher unit shall be short-circuit protected internally and shall not contain a fuse or circuit breaker. Subsequent to the test, the flasher shall meet the requirements of 3.4.4.

3.4.6 Reverse polarity. The flasher unit shall meet the requirements of 3.4.4. The unit shall not be operational with reverse polarity.

3.4.7 Endurance. The control unit shall operate without malfunction and meet the requirements of 3.5.1 throughout the test. The flasher unit shall meet the requirements of 3.4.4 throughout the test.

3.4.8 Transient capability. After testing as specified in 4.4.3.5, the flasher unit shall meet the requirements of 3.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

3.4.9 Electromagnetic interference. The turn signal flasher and control unit shall conform to figure 1 for conducted emissions and figure 2 for radiated emissions.




FIGURE 1. Limit For UMO5 Conducted Emissions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.




FIGURE 2. Limit For UMO5 Radiated Emissions.

3.5 Mechanical.

3.5.1 Actuation. The force required to move the directional control lever from any position to an adjacent position shall be not less than 2 nor more than 4 pounds (lb). To move bthe hazard warning switch from any position to any adjacent position, the force shall be not less than 2 nor more than 7 lb.

3.5.2 Strength, control unit. The actuation lever shall withstand the test specified in 4.4.4.2, without any permanent distortion or other damage that would impair the functional operation of the control unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

3.6 Environmental.

3.6.1 High temperature.

3.6.1.1 Control unit. The control unit shall operate in a temperature of 160° ±5°F without malfunction. The control unit shall meet the requirements of 3.5.1 throughout the test.

3.6.1.2 Flasher unit. The flasher unit shall operate in a temperature of 160° ±5°F without malfunction. The flasher unit shall meet the requirements of 3.4.4 throughout the test.

3.6.2 Low temperature.

3.6.2.1 Control unit. The control unit shall operate in a temperature of -65° ±5°F without malfunction. The control unit shall meet the requirements of 3.5.1 throughout the test.

3.6.2.2 Flasher unit. The flasher unit shall operate in a temperature of -65° ±5°F without malfunction. The flasher unit shall meet the requirements of 3.4.4 throughout the test.

3.6.3 Shock. The control and flasher units shall evidence no loosened, distorted, or broken parts. The signal control lever shall not be displaced during the test. Subsequently, the control unit shall meet the requirements of 3.5.1 and the flasher unit shall meet the requirements of 3.4.4.

3.6.4 Vibration. The control and flasher units shall evidence no loosened, distorted, or broken parts. There shall be no oscillation of the control unit body about the cylinder axis, or displacement of the control lever. Subsequently, the control unit shall meet the requirements of 3.5.1 and the flasher unit shall meet the requirements of 3.4.4.

3.6.5 Waterproofness. The control and flasher units shall evidence no leakage or damage which would adversely affect performance. Subsequently, the control unit shall meet the requirements of 3.5.1 and flasher unit shall meet the requirements of 3.4.4.

3.6.6 Corrosion resistance. The control and flasher units shall show no evidence of corrosion that would adversely affect performance. Subsequently, the control unit shall meet the requirements of 3.5.1 and the flasher unit shall meet the requirements of 3.4.4.

3.7 Finish.

3.7.1 Appearance. The control unit shall have an olive drab finish and the flasher unit shall have an olive drab or black finish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

3.8 Marking. The control and flasher units shall both be marked in accordance with SAE AS478 and each shall include as a minimum the following :

a. 24 Vdc
b. Manufacturer's identification
c. Manufacturer's part number (P/N)
d. Serial number
e. Military part Number
f. Federal stock Number
g. US

3.9 Workmanship. Workmanship shall be of a quality which will assure a product free of burrs, rust, scratches, chips, sharp edges, loose or defective connectors, cracked insulation, faulty soldering or other defects which affect serviceability or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspection (see 4.3).

4.2 First article inspection. The first article sample (see 3.1) shall consist of four specimens each of the control and flasher unit. They shall be properly identified as representative of the units proposed to be delivered to the Government. First article sampling and testing is the responsibility of the manufacturer unless modified by the contract. Government surveillance of testing to assure examination for defects specified in 4.3.2 and testing as specified in table I is required.

4.2.1 Order of inspection. Inspection shall be in the order listed in table II and table III.

4.2.2 Failure. Failure of any first article specimen to pass any specified examination or test may be cause, at the option of the Government, for refusal to conduct additional testing until the faults revealed by the tests have been corrected.

4.3 Conformance inspection.

4.3.1 Sampling. Sampling shall be as specified in the contract (see 6.2).

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined for defects such as incorrect dimensions affecting interchangeability, incorrect luminescent area, improper finish, improper marking, and faulty workmanship. Examination shall be visual, tactile, or by measurement with standard inspection equipment (SIE).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

4.3.3 Conformance tests for flasher. Samples selected in accordance with 4.3.1 shall be subjected to the tests specified in table I in the order listed in table IV.

4.3.4 Conformance tests for control units. All (100%) control units shall be subjected to the tests specified in table I in the order listed in table IV.

TABLE I. Verification Methods.

Title	Requirement	Verification
Design and Construction	3.3 thru 3.3.5	4.4
Electrical	3.4	4.4.3
Voltage rating	3.4.1	4.4.3.2.1
Current rating	3.4.2	4.4.3.2.1
Load impedance	3.4.3	4.4.3.2.1
Flashing	3.4.4	4.4.3.1
Overload	3.4.5	4.4.3.2
Control unit	3.4.5.1	4.4.3.2.1
Flasher unit	3.4.5.2	4.4.3.2.2
Reverse polarity	3.4.6	4.4.3.3
Endurance	3.4.7	4.4.3.4
Transient capability	3.4.8	4.4.3.5
Electromagnetic interference	3.4.9	4.4.3.6
Mechanical	3.5	4.4.4
Actuation	3.5.1	4.4.4.1
Strength, control unit	3.5.2	4.4.4.2
High temperature	3.6.1	4.4.5.1
Control unit	3.6.1.1	4.4.5.1.1
Flasher unit	3.6.1.2	4.4.5.1.2
Low temperature	3.6.2	4.4.5.2
Control unit	3.6.2.1	4.4.5.2.1
Flasher unit	3.6.2.2	4.4.5.2.2
Shock	3.6.3	4.4.5.3
Vibration	3.6.4	4.4.5.4
Waterproofness	3.6.5	4.4.5.5
Corrosion	3.6.6	4.4.5.6

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

4.4 Verification methods. The types of verification methods included in this section are visual inspection, measurement, sample tests, full-scale demonstration tests, simulation, modeling, engineering evaluation, component properties analysis, and similarity to previously-approved or previously-qualified designs.

4.4.1 Verification alternatives. The manufacturer may propose alternative test methods, techniques, or equipment, including the application of statistical process control, tool control, or cost-effective sampling procedures, to verify performance. See the contract for alternatives that replace verifications required by the specification.

4.4.2 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed in accordance with the test conditions specified below (see 4.4.2.1).

4.4.2.1 Conditions. Tests shall be conducted under general laboratory conditions acceptable to the Government. Unless otherwise specified herein, all tests shall be conducted at ambient room air temperature. The ambient room temperature shall be maintained at 77° ±15°F. Unless otherwise specified herein, or in applicable specifications, test specimens shall be thermally stabilized for one hour prior to being subjected to tests.

TABLE II. Order of first article testing for control unit.

Specimen	Paragraph No.	Tests
1 and 2	4.4.4.1	Actuation
	4.4.3.2.1	Overload
	4.4.4.1	Actuation
	4.4.3.4	Endurance (Control unit)
	4.4.4.1	Actuation
	4.4.5.1.1	High temperature
	4.4.4.1	Actuation
	4.4.5.2.1	Low temperature
	4.4.4.1	Actuation
	4.4.3.4	Endurance (Warning switch)
	4.4.4.1	Actuation
	4.4.4.2	Strength, control unit
	4.4.5.5	Waterfproofness
	4.4.4.1	Actuation
3	4.4.4.1	Actuation
	4.4.3.2.1	Overload
	4.4.4.1	Actuation
	4.4.5.4	Vibration
	4.4.4.1	Actuation
	4.4.5.3	Shock

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

TABLE II. Order of first article testing for control unit - Continued.

Specimen	Paragraph No.	Tests
	4.4.4.1	Actuation
	4.4.4.2	Strength, control unit
	4.4.4.1	Actuation
4	4.4.4.1	Actuation
	4.4.5.6	Corrosion resistance
	4.4.4.1	Actuation

TABLE III. Order of first article testing for flasher unit.

Specimen	Paragraph No.	Tests
1	4.4.3.1	Flashing
	4.4.5.2.2	Low temperature
	4.4.3.1	Flashing
	4.4.5.1.2	High temperature
	4.4.3.1	Flashing
	4.4.3.4	Endurance
	4.4.3.1	Flashing
2	4.4.3.1	Flashing
	4.4.3.5	Transient capability
	4.4.3.1	Flashing
	4.4.3.2.2	Overload
	4.4.3.1	Flashing
	4.4.3.3	Reverse polarity
	4.4.3.1	Flashing
	4.4.5.4	Vibration
	4.4.3.1	Flashing
	4.4.5.5	Waterproofness
	4.4.3.2.2	Overload
	4.4.3.1	Flashing
3	4.4.3.1	Flashing
	4.4.5.3	Shock
	4.4.3.1	Flashing
	4.4.5.6	Corrosion resistance
	4.4.3.1	Flashing
	4.4.3.2.2	Overload
	4.4.3.1	Flashing
4	4.4.3.6	Electromagnetic interference

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

TABLE IV. Order of conformance tests.

Sample	Paragraph	Tests	
Flasher	4.4.4.1	Actuation	(See Note 1)
	4.4.3.1	Flashing	(See Note 2)
	4.4.3.2.2	Overload	(See Note 3)
	4.4.3.1	Flashing	(See Note 2)
	4.4.3.3	Reverse Polarity	(See Note 4)
	4.4.3.1	Flashing	(See Note 2)
Control Unit	4.4.4.1	Actuation	(See Note 1)
	4.4.3.1	Flashing	(See Note 2)
	4.4.5.5	Waterproofness	(See Note 5)
	4.4.3.1	Flashing	(See Note 2)
	4.4.4.1	Actuation	(See Note 1)

NOTE 1: Perform in accordance with 4.4.3.1 but actuate twice.
NOTE 2: Check each unit to 18, 24 and 30 V. Eliminate "Average flashing rate" and "percent on time" specified in 3.4.4.
NOTE 3: Short for approximately 15 seconds.
NOTE 4: Apply reverse polarity only once.
NOTE 5: Submerge in tap water one minute. Electrical operation not required. A continuous stream of bubbles from the unit shall be cause for failure.

4.4.3 Electrical.

4.4.3.1 Flashing. The flasher unit shall be subjected to test potentials of 18, 24, and 30 Vdc. The "turn off time" shall be determined at the specified test voltages.

4.4.3.2 Overload.

4.4.3.2.1 Control unit. The control unit shall be connected into a circuit with a switch, a 30 A circuit breaker and a 24 V power source. The power source shall consist of two fully charged batteries conforming to MIL-B-11188/1, Type 6TN, connected in series or an equivalent regulated power supply. With the switch in the "OFF" position, connect the positive battery terminal to the switch, connect the switch to the circuit breaker and connect the circuit breaker to terminal "D" of the control unit (unit in neutral position). Connect terminals "C" and "E" of the control unit to the negative terminal of the power source. The following test shall be performed:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

a. With the control unit in the left turn position, turn the test circuit switch to the "ON" position for one minute and then return to the "OFF" position for three minutes.
b. Repeat the cycle five times.
c. With the control unit in the right turn position repeat the above operations.
d. Subsequent to the above test, the flasher and control arm shall meet the requirements of the flashing test.

4.4.3.2.2 Flasher unit. The flasher unit shall be connected in a test circuit with one AA52463-B10 lamp, one circuit breaker (30 A), necessary wiring, and a power source using two type 6TN batteries connected in series. The batteries shall be fully charged in good condition, with the electrolyte having a corrected specific gravity reading of 1.280 ±0.005 at 77°F. The circuit breaker shall be connected between the power source and the flasher. The lamp shall be shorted with a 10 in. length of No.14 AWG wire for one minute. After removing the short, the flasher unit shall subjected to and pass the tests of 4.4.3.1.

4.4.3.3 Reverse polarity. Reverse polarity shall be applied to the flasher unit, using a circuit consisting of ten AA52463-B10 lamps, necessary wiring, and 28 volt dc power source. The reversed polarity shall be applied ten consecutive times for one minute, at two minute intervals. The flasher shall subsequently be subjected to and pass the tests of 4.4.3.1.

4.4.3.4 Endurance. The control unit shall be connected in the test circuit and cycled for 50,000 cycles as specified in 4.4.5.1.1, except the temperature shall be 77° ±15°F. The control unit shall then be cycled for 123 000 cycles in the same manner, except four AA52463-B10 lamps shall be removed from the load circuit, simulating removal of two lamps from the right rear position and two lamps from the left rear position. The flasher unit shall be cycled for 300 hours as specified in 4.4.5.1.2, except the temperature shall be 77° ±15°F. The endurance test shall be repeated on the hazard warning switch, except that the switch shall be cycled 5000 times and the cycling rate shall be two seconds "on" and two seconds "off". A cycle for the hazard warning switch shall consist of the lever movement from neutral to hazard warning position and return to neutral.

4.4.3.5 Transient capability. The flasher shall be subjected to a properly polarized transient voltage of 80 Vdc for 50 ±5 milliseconds duration. The voltage shall be applied to the input terminals of the flasher unit ten consecutive times at one minute intervals. The flasher unit shall subsequently be subjected to and pass the tests as specified in 4.4.3.1.

4.4.3.6 Electromagnetic interference. The control and flasher units shall be tested as specified in MIL-STD-462 (see 4.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

4.4.4 Mechanical.

4.4.4.1 Actuation. The control unit shall be mounted in a vise or other suitable means. With the lever in one extreme position, a force shall be gradually applied within 0.5 in. of the end of the lever in line with the direction of motion of lever until it actuates. A force shall again be gradually applied in the same direction until the lever actuates again. A force shall be applied to the control lever in the opposite direction until the lever is in neutral position, and again until the lever is in the original position. This procedure shall be repeated ten times. The average force necessary to actuate the control lever shall not exceed the limits specified in 3.5.1.

4.4.4.2 Strength, control unit. The control unit shall be mounted on a fixture equipped with a vertical bar 1.5 in. in diameter. The control unit shall be attached to the bar to simulate normal mounting on a vehicle steering column. With the lever hazard lock released and the lever in the farthest forward actuating position, a 70 pound force (lbf) shall be applied gradually in line with the actuation motion of the lever. The force shall be applied for two minutes at right angles to the lever at a point 1.5 in. from the end of the lever. The lever shall then be placed at the opposite end of the actuation range and a 70 lbf applied as before. The lever shall then be returned to the neutral position and the 70 lbf shall be applied in both directions perpendicular to the plane of normal lever actuation.

4.4.5 Environmental.

4.4.5.1 High temperature.

4.4.5.1.1 Control unit. The control unit shall be connected in a directional signal light circuit consisting of a flasher unit, ten AA52463-B10 lamps, 28 Vdc power source, and the necessary wiring. The control unit shall be stored in an ambient temperature of 160° ±5°F for 24 hours and then cycled for 1000 cycles at that temperature. Control unit cycling shall be conducted in the following sequence: 1 ±0.1 second in neutral position, 1 ±0.1 second in right turn position, 1 ±0.1 second (again) in neutral position, and 1 ±0.1 second in left turn position (15 cycles per minute). Cycling shall be accomplished by applying alternate force of not less than 2 lb or more than 4 lb to the end of the control lever in each direction of motion. The control unit shall conform to 3.5.1 during the test.

4.4.5.1.2 Flasher unit. The flasher unit shall be connected in the circuit specified in 4.4.5.1.1. The flasher unit shall be stored in an ambient temperature of 160° ±5°F for 24 hours and then cycled for 25 hours at that temperature. Cycling shall consist of 15 ±1 seconds “on” and 15 ± 1 seconds “off” while making and breaking the 10 ampere lamp load. The flasher shall conform to 3.4.4 during the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

4.4.5.2 Low temperature.

4.4.5.2.1 Control unit. The control unit shall be subjected to the test specified in 4.4.5.1.1, except that the ambient temperature shall be -65° ±5°F. The control unit shall conform to 3.5.1 during the test.

4.4.5.2.2 Flasher unit. The flasher unit shall be subjected to the test specified in 4.4.5.1.2, except that the ambient temperature shall be -65° ±5°F. The flasher unit shall conform to 3.4.4 during the test.

4.4.5.3 Shock.. The control and flasher units shall be subjected to the shock test specified in method 213 of MIL-STD-202 (see 4.4.1). Control and flasher units shall be mounted as in intended use. No load shall be connected to units during the test. A force of 50 gravity units shall be applied to the flasher unit once in the direction of each of the major axes (a total of three times). Fifty gravity units shall be applied to the control unit once in the direction of each of the three major axes, with the signal control lever in the up (right turn) position, and center (off) position, and the down (left turn) position (a total of nine times). Subsequent to the test, the control unit shall be subjected to and pass the tests of 4.4.4.1, and the flasher unit shall be subjected to and pass the tests in 4.4.3.1.

4.4.5.4 Vibration. The control and flasher units shall be subjected to the vibration test specified in method 201 of MIL-STD-202 (see 4.4.1). Control unit shall be securely mounted to a metal cylinder having a diameter within limits specified on 11613632 for the mounting clamp. The axis of the body of the control unit shall be perpendicular to the mounting clamp. The axis of the body of the control unit shall be perpendicular to the vibration table surface. Flasher unit shall be mounted as in intended operation. Vibration shall be applied to the control unit for 20 minutes in the direction of each of the major axes with the control lever in each position (a total of three hours of vibration). During vibration, control units shall be observed for oscillation of the control unit body about the cylinder axis, or displacement of the control lever. Vibration shall be applied to the flasher unit for one hour in the direction of each of the three major axes. Subsequently, the control unit shall be subjected to and pass the tests of 4.4.4.1 and the flasher unit shall be subjected to and pass the tests of 4.4.3.1.

4.4.5.5 Waterproofness. The control unit and flasher unit shall be submerged in a 5% saline solution with the uppermost surface a minimum of 1 in below the surface of the solution and installed in the chamber. The components shall be carefully observed during its entire period of submersion and shall be operated while submerged for 30 minutes at full rated current and voltage. The chamber shall be evacuated to a pressure of 6 psi below atmospheric so as to apply a minimum of 6 psi in internal pressure to all voids within the assembly. Air bubbles which are the results of air trapped in pockets on the exterior of the motor shall not be considered a leak.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

Subsequently, the control unit shall be subjected to and pass the tests of 4.4.4.1 and the flasher unit shall be subjected to and pass the tests of 4.4.3.1.

4.4.5.6 Corrosion resistance. The control unit and flasher unit shall be subjected to the salt spray test specified in ASTM B117. Subsequently, the control unit shall be subjected to and pass the tests of 4.4.4.1 and flasher unit shall be subjected to and pass the tests of 4.4.3.1.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature which may be helpful, but is not mandatory.)

6.1 Intended use. The control and flasher units covered by this specification are intended for use in directional control signal systems and hazard warning systems of military vehicles. This system should not be used for ambient temperatures above 165°F. This specification should not be used for procurement of control units for newly designed vehicles. Control units, for newly designed vehicles, should be self-cancelling by steering wheel rotation in accordance with Federal Motor Vehicle Safety Standards. These units are military unique because they have to operate over an ambient temperature range from - 65°F to 160°F.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Unit required (see 1.2).
c. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1 and 2.3).
d. When first article is required (see 3.1).
e. Sampling plan (see 4.3.1).
f. If inspection conditions should be other than as specified (see 4.4.2).
g. Packaging requirements (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

6.3 Definition of component terms.

6.3.1 Control unit. The control unit is the component mounted on the vehicle steering column, which includes the directional control, hazard warning switch, flash indicator lamp, and connector necessary for electrical connection to the vehicle electrical system. The control unit also includes the switching necessary for supplying positive voltage to the flasher unit when this unit is set in “right hand turn”, “left hand turn”, or “hazard warning” position.

6.3.2 Flasher unit. The flasher unit is the component which, while in operation, makes and breaks the directional signal light circuit at the prescribed rate and has no moving parts.

6.3.3 Hazard warning switch. The hazard warning switch is a driver-controlled device which causes all turn signal lamps to flash simultaneously to indicate the presence of a vehicular hazard to approaching drivers.

6.4 Definition of operation terms.

6.4.1 Flashing. “Flashing” of a directional control system is defined as the variation of the luminosity of each of the signal lamp bulbs from less than that noticeable to a person with normal or corrected 20/20 vision to a luminosity greater than 25 candle power to the original level.

6.4.2 On time. “On time” is defined as the time elapsed between the period when full voltage (18 to 30 volts dc) is applied to the load and full voltage is switched from the load.

6.4.3 Off time. “Off time” is defined as the time elapsed between the period when full voltage (18 to 30 volts dc) is switched from the load and full voltage is applied to the load.

6.4.4 Flashing rate. The “flashing rate” in flashes per minute is defined as follows:

$$\text{Flashing rate} = \frac{60}{\text{on time + off time (expressed in seconds)}}$$

Where computation is carried to the nearest tenth and “on time” and “off time” are consecutive and as defined in 6.4.2 and 6.4.3, respectively.

6.4.5 Percent on time. “Percent on time” is defined as follows:

$$\text{Percent on time} = \frac{\text{on time}}{\text{on time} \pm \text{off time (expressed in seconds)}} \times 100$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

Where computation is to be carried to the nearest tenth, and “on time” and “off time” are consecutive and as defined in 6.4.2 and 6.4.3, respectively.

6.4.6 Turn on (starting) time. “Turn on time” is defined as the time elapsed between an instant that the control lever is moved from neutral position into right hand (RH) or left hand (LH) position and the instant that the total current to the RH or LH tail lamps, as applicable, reaches two amperes.

6.4.7 Turn off time. “Turn off time” is defined as the time elapsed between an instant that the control lever is moved from RH or LH position into neutral position and the instant that all noticeable lamp luminosity ceases.

6.5 Subject term (key word) listing.

Electrical
Flasher
Hazard warning
Vehicle

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - AT

Preparing Activity:
Army - AT

(Project 2590-0265)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE *(YYMMDD)*
	MIL-DTL-62069F(AT)	980831

3. DOCUMENT TITLE

Control, Directional Signal Light, Automotive: 24 Volt DC, Solid State

4. NATURE OF CHANGE ***(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)***

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON *(If applicable)*	7. DATE SUBMITTED *(YYMMDD)*

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON
	(810) 574-8745 786-8745
c. ADDRESS *(Include Zip Code)* Commander U.S. Army Tank-automotive and Armaments Command ATTN: AMSTA-TR-E/BLUE Warren, MI 48397-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403 Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:14Z
Check the source to verify that this is the current version before use.