MILITARY SPECIFICATION

DELAY DETONATOR ASSEMBLY

(DWG. C-9207798)

This amendment forms a part of Military Specification MIL-D-50584 (MU), dated 30 September 1970.

a. Paragraph 4.3.3.3.-Delete the entire paragraph and substitute a new paragraph to read:

/ "4.3.3.3 Grenade functioning (See 3.3) Major defect (Code No. 11001).- Fifty (50) delay detonators shall be selected from each lot for this test. If two (2) or more delay detonators fail to comply with the requirement specified, the lot shall be rejected. If no delay detonator fails the test, the lot shall be accepted. If one (1) delay detonator fails the test, a second sample of fifty (50) delay detonators shall be selected from the same lot and subjected to the test. If the combined number of defects for both the first and second samples is two (2) or more, the lot shall be rejected. The test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4."

b. Paragraph 4.4.3.-Delete the entire paragraph and substitute a new paragraph to read:

"4.4.3 Grenade functioning.-The delay detonator selected for this test shall be assembled into grenades from an accepted lot. The grenades shall then be ejected from an approved avalauncher into the atmosphere with the elevation angle and direction of the avalauncher barrel adjusted to the position that will cause the grenade to strike near the center of the prepared impact area at a near-vertical angle. (weather conditions will necessitate changing of the barrel position). Observation shall be made to determine compliance with the requirements of 3.3. In addition, partial duds shall be disassembled in order to determine whether the delay detonator functioned properly. All information recorded shall be forwarded as specified in 6.5. Malfunctions not attributed to the delay detonator assembly shall be disregarded. Provision shall be made for replacement of such grenades. When it has been necesary to replace grenades, the reasons for such replacements and all data generated from the replaced grenades shall be included with the data forwarded."

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:30Z
Check the source to verify that this is the current version before use.

Paragraph 4.6.2.2.: Delete and substitute the following:

4.6.2.2 Vibration.- Perform this test utilizing the apparatus specified in Method 514.1 of MIL-STD-810 and in accordance with the vibratory conditions specified in 3.3.1.2. Following vibration exposure, perform the "MODE SELECT switch""Test and "RCVR-XMTR STATUS meter reading "test of MIL-T-50606 on the Tester-Receiver Transmitter, Laser: 10559600 to determine compliance of the tester with 3.3.1.2. Prior to performing this vibration test, the Tester-Receiver Transmitter, Laser: 10559600 shall have met all the requirements of MIL-T-50606."

Paragraph 4.6.2.3: Delete and substitute the following:

"4.6.2.3 Shock.- Perform this test utilizing apparatus specified in Method 516.1 of MIL-STD-810, in accordance with Procedure I therein, except that the conditions of 3.3.1.3 shall apply. Following vibration exposure, examine the carrying case and contents for damage to determine compliance with 3.3.1.2. Perform the "MODE SELECT switch" test and the "RCVR-XMTR STATUS meter reading "Test of MIL-T-50606 on the Tester-Receiver Transmitter Laser: 10559600 to determine compliance with 3.3.1.3. Prior to performing the shock test, the Tester shall have met all the requirements of MIL-T-50606."

Paragraph 4.6.2.4: Add the following:

"4.6.2.4 Post Environmental Tests.- Following completion of the listed environmental tests, perform electrical tests specified in the individual specifications or drawings (see 3.1), as applicable, on the remaining components and cables to determine compliance with 3.3.1.1, 3.3.1.2, amd 3.3.1.3."

Paragraph 6.1: Delete "the Laser Range Finder" and substitute "Laser Range Finder".

Custodian:

Army - MU

Preparing Activity

Army - MU

Project Number 4931-A128

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.