MIL-I-60347 (MU)
AMENDMENT 1
22 MAY 1973

MILITARY SPECIFICATION

IGNITER ASSEMBLY FOR CARTRIDGES, 90MM, AP-T, M318A1 and 90MM, TP-T, M353E1

This Amendment forms a part of Military Specification MIL-I-60347 (MU), dated 21 June 1965.

Paragraph 2.1: Specifications:

Add the following specifications:

"MIL-B-117 - Bags, Sleeves and Tubing, Interior Packaging

MIL-B-2427 - Boxes, Ammunition Packaging; Wood Nailed

MIL-F-50449- Filler, Sheet Form (for use in ammunition containers)

FED-STD-406- Plastics, Method of Testing

PPP-B-26 - Bag, Plastic Polyethylene"

Paragraph 2.1: Drawings:

Delete the following drawing:

"7549036 - Marking Diagram and Sealing of Container, Metal, Universal M25 for Shipment of Propellant and Explosives"

Add the following drawings:

"8796522 - Marking Diagram and Sealing for Wood Packing Boxes

8858577 - Marking Diagram and Sealing of Container, Metal, Universal M25 for Shipment of Propellants"

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

Paragraph 4.2.3.2 - Add reference to "dwg. 76-4-59."

Paragraph 4.2.2.3 - Delete "dwg. 7549036" and substitute "dwgs. 8858577 and 8796522."

Paragraph 5. - Delete and substitute:

"5. PREPARATION FOR DELIVERY

5.1 Packaging

5.1.1 Level A - Igniter Assemblies shall be packaged in barrier bags complying with the requirements of MIL-B-117 for a Type I, Style 1, Class E bag. Each barrier bag shall contain approximately 15 pounds of propellant. All excess air shall be exhausted from the bag and the bag closed by means of heat-sealing.

5.2 Packing

5.2.1 Level A - Two bags of propellant shall be packed in a nailed wood box conforming to MIL-B-2427, Type I, Class 1, Grade A requirements. All interior surfaces of the box shall be lined with filler sheets conforming to Specification MIL-F-50449. Additional fillers shall be added as necessary to provide a tight pack. Boxes shall be closed and strapped in accordance with instructions contained in the appendix of the box specification.

5.2.2 Level B - The igniters shall be packed in a metal wood box complying with drawing 76-4-59. The interior of the container shall be lined with a polyethylene bag constructed, tested and closed as specified in paragraph 5.2.2.1. Air pressure test specified in drawing 76-4-59 is not required.

5.2.2.1 Liners. Liners shall be made of conductive polyethylene or polyolefin sheet with a nominal thickness of .003 in. (tolerance - plus or minus 20%); surface resistivity shall not exceed 10^3 ohms per centimeter, when tested in accordance with Methods 4041 and 4052 of Standard FED-STD-406. Electrostatic bleed-off shall not exceed 2.00 seconds when tested in accordance with Method 4046 of Federal Test Method Standard 101B. Details of the liner shall comply with Type I or II, Style 1 of Specification PPP-B-26 except for the material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

After filling, the top of the bag shall be twisted and the twisted portion folded back on itself; it shall be fastened with a suitable tape or tie. The bag size shall be large enough to prevent strain on the bag if the container is dropped or rolled.

5.2 Marking - Exterior containers shall be marked in accordance with drawing 8796522 or 8858848 as applicable."

CUSTODIAN:
ARMY-MU

PREPARING ACTIVITY:
ARMY-MU

PROJECT NUMBER: 1315-A025

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.