MILITARY SPECIFICATION

NETWORK B" 10526468

This amendment forms a part of Military Specification MIL-N-60210(MU), dated 4 March 1965.

Paragraph 3.4.1.4, Line 5: Delete "minus 6 volts" and substitute "minus 5 volts"; Last line: Delete "minus 2.3 volts" and sbustitute "minus 3.5 volts".

Paragraph 3.4.5.4: Delete "state" and substitute "stage".

Delete paragraph 3.4.6.2 and substitute new paragraph 3.4.6.2.

"3.4.6.2 Selection and input diodes.- The selection and input diodes shall have a forward voltage drop more positive than -1.0 volt dc, with the following exceptions; The forward voltage drop of diodes CR4 and CR9 shall be more positive than -1.1 volt dc. The forward voltage drop of diodes CR2, CR3, CR6, CR7, CR8 and CR13 shall be more positive than -1.2 volt dc".

Delete paragraph 3.7 Electrical wiring in its entirety and substitute the following:

"3.5 Electrical wiring.- Wiring and connections shall be in accordance with electrical schematic, Drawing F10526471."

Table I, Characteristic 108, Test Procedures Column: Delete "4.5.3.3.1" and substitute "4.5.2.3.1"; Characteristic 121, Test Procedures Column: Delete "4.5.2.6.6" and substitute "4.5.2.6.5".

Table III, Characteristic 304, Test Procedures Column: Add "4.5.1.3.2"; Characteristic 308, Test Procedures Column: Delete "3.5.2.1.4" and substitute "4.5.2.1.4" and add: "4.5.1.5".

* Following paragraph 4.1.1, add paragraphs 4.1.2, 4.1.2.1 and 4.1.2.2.

"4.1.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) units manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected and a record of this inspection, including certificates of conformance for materials shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

* Paragraph 4.2.3: Add the following sentence: "No lots shall be accepted until control samples have been satisfactorily tested."

* Paragraph 4.3.2: Delete first sentence and substitute:

"Units shall be selected at random by a Government representative as control samples from each three (3) months production or portion thereof as follows:

3 units per first 100 produced
5 units per 200
7 units per 300
9 units per 400
10 units per 500
12 units per 700
15 units per 1000
and 2 units for each 100 items produced in excess of 1000."

Paragraph 4.4.1.1, Item 8, Description Column: Delete "Impednace" and substitute "impedance"; Item 13, Description Column: Delete "(Item) 11" and substitute "Item 10)".

* Delete paragraph 4.5.1.3.2 and substitute the following:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24-hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.3 to determine compliance with 3.3.4.1. In order to demonstrate this capability, the tests of 4.5.3 shall be performed a minimum of once each 6 hours of the 24-hour period. The final test shall be conducted during the final portion of the 24-hour period. Between tests, the board shall be electrically de-energized.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

* Delete paragraph 4.5.1.4 and substitute the following:

"4.5.1.4 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.2 for compliance with 3.3.6."

Paragraph 4.5.2.1.1.1: Delete and substitute:

"4.5.2.1.1.1 Forward voltage drop.- Connect Pin 7B to the minus 6 volt supply voltage through a 680 ohm, 1/2 watt ± 5% resistor and ground Pin 8B. The voltage measured from ground to Pin 7B shall be less positive than plus 0.5 volt. No other voltage shall be connected during this test."

Paragraph 4.5.2.1.2: Delete "in Pin 5B" and substitute "to Pin 5B".

Paragraph 4.5.2.1.2.2: Delete "temove" and substitute "remove".

Paragraph 4.5.2.1.3, line 6: Delete "minus 6 volts" and substitute "minus 5 volts". And in line 9: Delete "minus 2.3 volts" and substitute "minus 3.5 volts".

Paragraph 4.5.2.1.4, line 2: Delete "03" and substitute "of".

Paragraph 4.5.2.2.1.2, line 6: Delete "ah11" and substitute "shall".

Paragraph 4.5.2.2.4, line 2: Delete "4.5.2.2.1.3" and substitute "4.5.2.2.1.2". Also add at the end of 4.5.2.2.4, the following sentence: "At the end of these tests, remove the resistor load and power supplies connected in 4.5.2.2.1.2".

Paragraph 4.5.2.4.1.2: Delete sentence 4.

Paragraph 4.5.2.5.6, line 1: Delete "5B" and substitute "3B".

Paragraph 4.5.2.6.2: Insert the following sentence between the first and second sentences: "Connect a minus 3 volt supply voltage to Pin 56A. Delete the last sentence and substitute the following:

"The voltage measured at the pin specified in Column 2 of Table XV shall be as specified in Column 3 for compliance with 3.4.6.2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

Delete Table XV and substitute new Table XV.

"TABLE XV

1 Ground Pin	2 Measure Voltage at Pin	3 Voltage more positive than
55B	43B	-1.0
44B	43B	-1.0
57B	55A	-1.0
51B	55A	-1.0
26A	24B	-1.0
28B	24B	-1.0
TP1	24B	-1.0
26A	26B	-1.0
26B	25B	-1.0
49B	49A	-1.1
49A	25B	-1.0
41A	26B	-1.0
26B	25A	-1.0
49B	TP1	-1.2
57A	TP1	-1.2
TP1	25A	-1.0
28B	29B	-1.2
29B	29A	-1.0
34A	32A	-1.0
40A	32A	-1.0
32A	29A	-1.0
43A	29B	-1.2
29B	31A	-1.0
34A	33A	-1.0
33A	31A	-1.0
29B	36A	-1.0
40A	49A	-1.1
49A	36A	-1.0
29B	38A	-1.0
TP1	38A	-1.0
43A	45B	-1.2
41A	45B	-1.2
45B	TP3	-1.0
32A	TP3	-1.0
45B	46A	-1.0
57A	33A	-1.0
33A	46A	-1.0
45B	TP2	-1.0
49A	TP2	-1.0
45B	51A	-1.0
TP1	51A	-1.0"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.2.6.3; Line 5: Delete "26B" and substitute "24B".

Paragraph 4.5.2.6.4; Line 2: Delete "Table 1" and substitute "Table IV".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A138

*The outside margin has been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.