INCH-POUND

MIL-P-50791C (AR)
AMENDMENT 3
30 September 1991
SUPERSEDING
AMENDMENT 2
15 September 1988

MILITARY SPECIFICATION

PROJECTILE, 105MM, TPDS-T, M737
METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-P-50791C (AR), dated 8 May 1987, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* 2.2: American Society for Testing and Materials (ASTM):

Delete: "E18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials".

PAGE 4

* 3.5.2: Delete: "...in a counterclockwise direction (as viewed from the front of the metal parts assembly)".

PAGE 9

Table I Category IV, Line 10: Delete: "...after heat treatment...".

PAGE 16

* 4.4.2.4: Delete: "102 Hardness 0.40% 3.3 4.5.1.2".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

4.4.2.4: Under Notes, delete:

"After final heat treatment, two bodies from each heat treated lot or six tensile test specimens from every 1,000 ft. of heat treated steel alloy bar, shall be selected at random and subjected to this test."

and substitute:

"Two bodies from each stock material lot or six tensile test specimens from every 1,000 ft. of steel alloy bar, shall be selected at random and subjected to this test."

PAGE 19

4.4.2.5

* Category 110: Delete "110 Salt spray test 2 3.6 See Note".

* Delete Note: "If any subcaliber assembly fails to meet all the requirements of the drawing and TT-C-490, the lot shall be rejected. The actual subcaliber assembly shall be used in this test."

* Category 201: Delete "201 Paint thickness 0.65% 3.6 Gage".

PAGE 22

4.4.2.6: Delete:

"204 Location of slots 0.65% 3.1 Gage".

PAGE 24

4.4.2.7

* Category 114: Delete in its entirety.

* Category 115: Delete "...max..." and substitute "...min...".

* Category 210: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

PAGE 29

* 4.4.2.10: Delete:

"107 Presence of gap between sabot and base 0.40% 3.1 Gage".

PAGE 38

* 4.5.1.2: Delete in its entirety.

PAGE 49

* Figure 6: Delete "Tape" and substitute "Taped joint - location optional".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1315-AB27)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.