MILITARY SPECIFICATION

SABOT, 60MM PRACTICE: M3
ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-S-63385A(AR) dated 24 July 1981, and is approved for use by the U.S. Army Armament, Munition and Chemical Command and is available for use by all Department and Agencies of the Department of Defense.

PAGE 4

Table I, First Article Inspection, Under Flange Nut:
Delete "9311189 and substitute "9369936".

PAGE 5

Add: New Examinations:

"Pin Firing

Dwg. 9369935			
Examination for defects	5	3.2	4.4.2.9

Flange Nut Assy

Dwg. 9311189			
Examination for defects	5	3.2	4.4.2.10".

PAGE 11

4.4.2.5, Drawing Number block: Delete "9311189" and substitute "9369936".

Major 103: Delete examination and substitute "Diameter of thread relief".

Major 104: Delete examination and substitute "Small rear inside diameter".

Major 105: Delete examination and substitute "Depth of thread shoulder".

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

Add: Major defects as follows:

"109	Large rear inside diameter	0.40%	3.2	Gage
110	Depth of rear inside diameter	0.40%	3.2	Gage
111	Smal forward inside diameter	0.40%	3.2	Gage
112	Depth of forward inside diameter	0.40%	3.2	Gage".

Add: New 4.4.2.9, Page 16A included.

Add: New 4.4.2.10, Page 16B included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Pin, Firing				9369935
					NEXT HIGHER ASSEMBLY 9311189
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter aft of head		0.40%	3.2	Gage
102	Length from tip to aft face of head		0.40%	3.2	Gage
103	Overall length		0.40%	3.2	Gage
104	Location of groove aft end		0.40%	3.2	Gage
105	Width of groove		0.40%	3.2	Gage
106	Diameter of groove		0.40%	3.2	Gage
107	Profile of tip		0.40%	3.2	Gage
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Flange Nut Assembly		9311189
			NEXT HIGHER ASSEMBLY 9328601

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Firing pin does not move freely when depress from rear		0.40%	3.2	Manual
102	Parts missing		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A585)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.