
INCH-POUND
MIL-DTL-9419/2G
1 December 2025
SUPERSEDING
MIL-DTL-9419/2F
17 September 2019

DETAIL SPECIFICATION SHEET

SWITCHES, TOGGLE, FOUR POSITION ON, MOMENTARY, CENTER OFF (.600 DIA)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-9419.




TOGGLE STYLE A


FIGURE 1. Dimensions and configurations..

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:53Z
Check the source to verify that this is the current version before use.




TOGGLE STYLE B




TOGGLE STYLE C

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:53Z
Check the source to verify that this is the current version before use.




TOGGLE STYLE D



TOGGLE STYLE E

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:53Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .03 for two place decimals and ± 2 degrees on angles.
4. Housing and actuator color: Black, except for white markings as required on toggle styles B and D.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:53Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction: No snap feel, no manual breaking of welded contacts, silver plating may be used, contacts close in opposite direction of travel.

Dimensions and configurations: See figure 1.

Actuating lever: Two-piece metal mast with spring loaded electrical conductivity from the common terminal to the actuating lever.

Electrical ratings: 1 ampere inductive at 28 V dc. De-rated 50 percent at altitude (60,000 feet).

Actuating force: 16 ounces ±6 ounces (10 ounces ±3 ounces for style D).

Actuating lever travel: 15 degrees maximum from center.

Strength of actuating lever pivot, lever stop, and cap:

5 inch-pound torque.
50-pound load 45 degrees (20-pound load at 45 degrees for style D and E).
50-pound load to top of cap.
8-ounce drop at 4 inches.

Strength of terminals: 15 pounds.

Electrical endurance: Normal: 25,000 cycles.

Electrical overload: 2 amperes at 28 V dc for 100 cycles.

Seal: Military Part or Identifying Numbers (PINS) M9419/2-002, -003, and –005 shall be tested in accordance with MIL-STD-202-112, test condition C, leakage rate sensitivity (1 x 10^{-6} atm cc/s) and procedure I, II, III, or IV. For qualification, specimen numbers 3 and 4 shall be tested following acceleration (see table I).

Altitude: Except de-rate inductive load by 50 percent.

PIN: The PIN shall consist of the prefix M9419/2 followed by the appropriate three-digit PIN from table I.

Example: M9419/2-002 is a four position toggle, with style A cap and additional sealing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:53Z
Check the source to verify that this is the current version before use.

TABLE I. PIN's.

PIN M9419/2-	Cap style	Additional sealing in accordance with MIL-STD-202-112
001	A	
002	A	X
003	B	X
004	C	
005	D	X
006	E	

Referenced documents:
MIL-DTL-9419
MIL-STD-202-112

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2026-007)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T12:53Z
Check the source to verify that this is the current version before use.