
MILITARY SPECIFICATION SHEET

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL,
NONENVIRONMENTAL, STRAIGHT, CATEGORY 3B
(FOR MIL-C-5015 CRIMP, MIL-C-26482 SERIES 2, MIL-C-81703
SERIES 3 AND MIL-C-83723 SERIES III CONNECTORS)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the accessories described herein shall consist of this document and the latest issue of Specification MIL-C-85049.



STYLE E

FIGURE 1. Configurations and dimensions

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.

Dash number	For connector shell size (REF)				A +.000 -.045 Dia.(1.14)
	MIL-C-81703 Series 3	MIL-C-26482 Series 2	MIL-C-5015 Crimp	MIL-C-83723 Series III	Style E
-3	3				.669 (16.99)
-8		8	8S	8	.617 (15.67)
-10		10	10S, 10SL	10	.734 (18.64)
-12	7	12	12S & 12	12	.858 (21.79)
-14	12	14	14S & 14	14	.984 (24.99)
-16	19	16	16S & 16	16	1.112 (28.24)
-18	27	18	18	18	1.218 (30.94)
-20	37	20	20	20	1.345 (34.16)
-22		22	22	22	1.468 (37.29)
-24		24	24	24	1.593 (40.46)
-28			28		1.969 (50.01)
-32			32		2.219 (56.36)
-36			36		2.469 (62.71)
-40			40		2.719 (69.06)
-44			44		2.969 (75.41)
-48			48		3.219 (81.76)
-61	61				1.653 (41.99)

FIGURE 1. Configurations and dimensions - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.

Dash number	R +.000 -.062
-3	.540 (13.72)
-8	
-10	
-12	
-14	
-16	
-18	
-20	
-22	
-24	.540 (13.72)
-28	.702 (17.83)
-32	
-36	
-40	
-44	
-48	.702 (17.83)
-61	.540 (13.72)

NOTES:
1. Dimensions are in inches.
2. Dimensions apply after plating.
3. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
4. Metric equivalents are in parentheses.

FIGURE 1. Configurations and dimensions - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:
Dimensions and configuration: See figure 1.

The accessory shall consist of a coupling nut and follower. The nut shall be captivated to the follower and free to rotate.

Interface dimensions shall conform to MS3155.


Material and finish: See table I.

TABLE I. Material and finish.

Material	Finish
Aluminum alloy in accordance with MIL-C-85049	A,W 1/ N

1/ Not for Navy use.


Part number: See example below:



Qualification:
See MIL-C-85049, category 3B.
Bending moment not applicable.

QPL evaluating activity: Naval Weapons Support Center, Code 3064, Crane, IN 47522.

Supersession data:



Old	New
C	W
N	N
	A

Custodians:
Army - CR
Navy - AS
Air Force - 85

Review activities:
Army - MI, AR
Navy - EC
Air Force - 11
DLA - ES

Preparing activity:
Navy - AS

Agent:
DLA - ES

(Project 5935-3067-22)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-85049/31

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Engineering Center
Lakehurst, NJ 08733

POSTAGE AND FEES PAID
Navy Department
DOD-316

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Engineering Specifications and Standards Department (Code 93)
Naval Air Engineering Center
Lakehurst, NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.