INCH-POUND

MIL-C-85049/38C
19 December 1989
SUPERSEDING
MIL-C-0085049/38B(USAF)
26 January 1987 and
MIL-C-85049/38A
4 March 1983

MILITARY SPECIFICATION SHEET

CONNECTOR ACCESSORIES, ELECTRICAL, STRAIN RELIEF, STRAIGHT SELF-LOCKING AND NONSELF-LOCKING, CATEGORY 4C (FOR MIL-C-38999 SERIES III AND IV CONNECTORS)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the accessories described herein shall consist of this specification and the latest issue of MIL-C-85049.




FIGURE 1. Dimension and configuration (self-locking only).

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.


Shell sizes and dimensions

Connector shell size	Shell size code (REF)	C max overall length	D max	E wire bundle accommodation range		F max dia	G screw length	Screw threads	A max
				Min	Max				
9	A	1.10 (27.9)	.85 (21.6)	.098 (2.49)	.234 (5.94)	.858 (21.79)	.500 (12 70)	6-32	.91 (23 1)
11	B	1 10 (27.9)	.90 (22.9)	.153 (3.87)	.234 (5.94)	.984 (24.99)	.500 (12.70)	6-32	.91 (23.1)
13	C	1.20 (30.5)	1.10 (27 9)	.190 (4 83)	.328 (8.33)	1.157 (29.39)	.625 (15 88)	6-32	1 01 (25 70)
15	D	1.25 (31.8)	1.15 (29.2)	.260 (6.60)	.457 (11.61)	1.279 (32.49)	.750 (19.05)	6-32	1.06 (26 9)
17	E	1 35 (34.3)	1.30 (33.0)	.283 (7.19)	.614 (15.60)	1.406 (35.71)	.750 (19.05)	6-32	1 16 (29 5)
19	F	1 60 (40.6)	1.50 (38.1)	.325 (8.26)	634 (16.10)	1.516 (34.50)	750 (19.05)	8-32	1.41 (35 8)
21	G	1 70 (43.2)	1.60 (40.6)	343 (8.71)	.698 (17.73)	1.642 (41.70)	.875 (22.23)	8-32	1 51 (38 4)
23	H	1 85 (47.0)	1.70 (43.2)	.381 (9.66)	.823 (20.90)	1.768 (44.91)	1.000 (25.40)	8-32	1 66 (42 2)
25	J	1.95 (49.5)	1 80 (45.7)	418 (10.62)	853 (21 66)	1 869 (47.98)	1 125 (28 58)	8 32	1 76 (44 7)

NOTES:
1. Dimensions are in inches.
2. Dimensions apply after plating.
3. Metric equivalents are given for general information only
4. Millimeters are in parentheses

FIGURE 1 Dimensions and configurations (self-locking only) - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.






FIGURE 2. Dimensions and configurations (nonself-locking only)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.

Shell size	A max dia of coupling ring	F Wire bundle accommodation range		G max dia	L max	W ±.032 screw length	Screw size
		Min	Max				
9	.75 (19.1)	.098 (2.49)	.234 (5.94)	.85 (21.6)	1.10 (27.9)	.500 (12.70)	6-32
11	.85 (21.6)	.153 (3.87)	.234 (5.94)	.90 (22.9)	1.10 (27.9)	.500 (12.70)	6-32
13	1.00 (25.4)	.190 (4.83)	.328 (8.33)	1.10 (27.9)	1.20 (30.5)	.625 (15.88)	6-32
15	1.10 (27.9)	.260 (6.60)	.457 (11.61)	1.15 (29.2)	1.25 (31.8)	.750 (19.05)	6-32
17	1.25 (33.0)	.283 (7.19)	.614 (15.60)	1.30 (33.0)	1.35 (34.3)	.750 (19.05)	6-32
19	1.40 (38.1)	.325 (8.26)	.634 (16.10)	1.50 (38.1)	1.60 (40.6)	.750 (19.05)	8-32
21	1.50 (40.6)	.343 (8.71)	.698 (17.73)	1.60 (40.6)	1.70 (43.2)	.875 (22.23)	8-32
23	1.65 (43.2)	.381 (9.68)	.823 (20.90)	1.70 (43.2)	1.85 (47.0)	1.000 (25.40)	8-32
25	1.75 (45.7)	.418 (10.62)	.853 (21.67)	1.80 (45.7)	1.95 (49.5)	1.125 (28.58)	8-32

NOTES:
1. Dimensions are in inches.
2. Dimensions apply after plating.
3. Metric equivalents are given for general information only.
4. Millimeters are in parentheses.

FIGURE 2. Dimensions and configurations (nonself-locking only) - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Self-locking and nonself-locking styles:

Design and construction.

Dimensions and configuration: See figures 1 and 2.

Interface dimension shall conform to MIL-C-38999 series III and IV.

Accessories consist of a coupling nut and follower. The coupling nut shall be captivated to, and free to rotate on the follower. The accessories will not accommodate connectors using size 8, 4, 0 contacts. Figure 2 dimension F_{MAX} is applicable when end of screw is flush with BB or a maximum of two screws threads protrude.

Clamps shall have nc protrusions or sharp edges which may pinch cable.

Material and finish: See table I. Accessories shall be as shown in table I.

Clamp screw and lockwashers: 300 series corrosion-resistant steel, passivate.

TABLE I. Material and finish

Figure	Material	Finish
1	Aluminum alloy in accordance with MIL-C-85049	W 2/ N 1/
1	Corrosion resistant steel 300 series in accordance with QQ-S-763	S
2	Aluminum alloy in accordance with MIL-C-85049	A, W

1/ Not for Navy use. Air Force use is for space applications only. W is the preferred finish.
2/ W is not for use in space application.

Self-locking styles only:

Self locking device within the coupling nut shall be corrosion resistant material and shall provide a positive detent. Couplings with self-locking devices shall meet all the performance requirements specified herein for its specific category and the following additional tests.


Life cycle: The coupling with the locking device engaged shall be rotated sixty full turns in a clockwise direction and sixty full turns counter clockwise, prior to standard qualification testing. Cycle speed shall not exceed one full turn per second.

Locking: Coupling nut torque shall be 80 percent of coupling thread strength values given for medium and light duty accessories as specified in table III of MIL-C-85049. In table III when N/A appears, the values shall be 80 percent of those values used in qualification testing for coupling thread strength. Tolerance shall be ±5 inch pounds.

Vibration Backshells shall be subjected to test parameters of applicable connector specifications. The coupling torque shall be within +20, -10 inch pounds of the initial value.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.

Part number: See example below:



QUALIFICATION:

See MIL-C-85049, category 4C.

QPL evaluating activity: Naval Avionics Center, Code B/444, 6000 East 21st Street, Indianapolis, Indiana 46219-2189.

Parts qualified to MIL-C-85049/38A may be supplied for 1 year from the date of this document.

Revision letters are not used to denote changes due to the extensiveness of the changes.

CONCLUDING MATERIAL

Custodian:
Air Force - 85
Army - CR
Navy - AS

Review activities:
Air Force - 11, 15, 19, 99
DLA - ES

Civil agencies coordinating activity.
NASA - NA

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5935-3686-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:12Z
Check the source to verify that this is the current version before use.