
MILITARY SPECIFICATION SHEET

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL, STRAIGHT, SELF-LOCKING, SHIELD BAND TERMINATION, (RFI/EMI), SHRINK BOOT ACCOMMODATION, CATEGORY 3B (FOR MIL-C-38999 SERIES III AND IV CONNECTORS)

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation. MIL-C-85049




NOTE Ribbed, internal knurl or surface roughness R_a 125-250 in accordance with ANSI B46 1 See figure 2 for selective plating details

FIGURE 1 Configuration and dimensions

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:14Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm	Inches	mm
044	1 12	562	14 27	829	21 06	1 157	29 39
130	3 30	583	14 81	858	21 79	1 279	32 49
140	3 56	625	15 88	895	22 73	1.350	34 29
250	6 35	684	17 37	938	23 83	1 406	35 71
.312	7.92	707	17 96	957	24 30	1 516	38 51
395	10 03	730	18 54	984	24 99	1 642	41 71
438	11 13	750	19 05	1 000	25 40	1 768	44 91
457	11 61	770	19 56	1 083	27 51	1 889	47 98
500	12 70	812	20 62	1 145	29 08		

NOTES
1. Dimensions are in inches
2. Metric equivalents are given for general information only and are based upon 1 00 (25 4 mm)
3. Cadmium/nickel interface shall be coated with polysulfide sealant

FIGURE 2 Selective plating

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:14Z
Check the source to verify that this is the current version before use.

TABLE I. Shell size and dimensions.

Accessory shell size	Shell size code (ref)	A max dia	B dia ± 010 entry size		C dia ref	
			02	03	02	03
9	A	858	N/A	.250	N/A	.395
11	B	.984	N/A	.312	N/A	.457
13	C	1.157	312	.438	457	.583
15	D	1.279	.438	.562	.583	.707
17	E	1 406	500	.625	645	770
19	F	1 516	.625	750	770	895
21	G	1.642	.625	.812	770	957
23	H	1 768	688	938	829	1.083
25	J	1 889	.750	1 000	.895	1.145

REQUIREMENTS

Design and construction.

Dimensions and configuration See figure 1 and table I

Interface dimensions Shall conform to MIL-C-85049

Coupling nut. Shall be captivated to the adapter body and free to rotate

Material and finish In accordance with MIL-C-85049 and table II herein

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:14Z
Check the source to verify that this is the current version before use.

TABLE II Material and finish

Finish	Material
G - Electroless nickel 1/ (space grade) N - Electroless nickel 1/ P - Cadmium olive drab over electroless nickel (selective plating, see figure 2) W - Cadmium olive drab	Aluminum alloy
J - Cadmium olive drab L - Cadmium olive drab over electroless nickel (selective plating, see figure 2) 2/ M - Electroless nickel	Composite

1/ Not for Navy use Limited to space applications for Air Force use
2/ Must meet the requirements, and pass tests for finish J

Vibration Backshells shall be subjected to test parameters of applicable connector specifications The coupling torque shall be within +20, -10 inch-pounds of the initial value

Additional tests for finishes J, L, and M shall be as follows

Ozone exposure Backshells shall be tested in accordance with MIL-STD-1344, method 1007

Sample Each sample shall consist of one backshell

Sample preparation Not applicable

Failure Blistering, or pealing of the plating constitutes a failure Any condition which adversely affects the function of the backshell also constitutes a failure

Fluid immersion (see table III) Backshell shall be tested in accordance with MIL-STD-1344, method 1016

TABLE III Test fluids

Sample number	Test fluid (method 1016 of MIL-STD-1344)
1	d
2	e
3	a
4	b
5	f
6	g
7	c
8	l
9	h
10	i
11	j
12	k


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:14Z
Check the source to verify that this is the current version before use.

Sample Each sample shall consist of one backshell

After immersion the backshells shall meet the coupling strenght requirements of MIL-C-85049

Thermal vacuum outgassing (finish G)· Backshell shall not emit vacuum condensable, noxious or toxic gasses when tested in accordance with ASTM E595 Total mass loss (TML) shall not be greater than 1.0 percent and collected volatile condensable materials (CVCM) shall not be greater than 10 percent. Data listed in NASA Reference Publication 1124 Revised may be used in lieu of actual test data for application materials

Part or Identifying Number (PIN) See example below:



QUALIFICATION

Qualification See MIL-C-85049, category 3B

QPL evaluating activity Naval Air Warfare Center, Code B/444, 6000 East 21st Street, Indianapolis, IN 46219-2189

CONCLUDING MATERIAL

Custodians
Army - CR
Navy - AS
Air Force - 85

Review activities
Army - AR, MI
Navy - EC, MC, OS
Air Force - 11, 15, 19, 99
DLA - ES

Preparing activity
Air Force - 85

Agent
DLA - ES

(Project 5935-3760-07)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:14Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE AIR FORCE
2750 LOG/ES
STANDARDIZATION
CUSTOMER SATISFACTION INQUIRY

TELEPHONE - COM 513-296-5517 DSN 986-5517
FAX - COM 513-296-8783 DSN 986-8783

VERY DISSATISFIED	DISSATISFIED	SOMEWHAT DISSATISFIED	SOMEWHAT SATISFIED	SATISFIED	VERY SATISFIED	NOT APPLICABLE
1	2	3	4	5	6	7

(PLEASE ENTER THE VALUE THAT YOU FEEL IS APPROPRIATE)

I. STAFF

1. PROVIDERS QUALIFICATIONS/COMPETENCE ☐

2. PROVIDERS PROFESSIONALISM ☐

	TIMELINESS	QUALITY
3. PROVIDERS RESPONSE TO YOUR INITIAL REQUEST	☐	☐

II. PRODUCT

	TIMELINESS	QUALITY
1. INITIAL DRAFT	☐	☐
2. REVISION/AMENDMENT SATISFIED YOUR REQUIREMENT	☐	☐

III. COMMENTS/SUGGESTIONS

(CONSTRUCTIVE COMMENTS OR SUGGESTIONS APPRECIATED)

MIL-C-85049/88

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:14Z
Check the source to verify that this is the current version before use.

"Please Fold and Tape"

Firs
Clas

Official Business

DEPARTMENT OF THE AIR FORCE
2750 LOG/ES
GENTILE STATION
1060 HAMILTON ST
DAYTON, OHIO 45444-5400

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:14Z
Check the source to verify that this is the current version before use.