MILITARY SPECIFICATION

BOXES, SETUP, Mailing, Dental

This limited coordination Military specification has been prepared by the Defense Personnel Support Center based upon currently available technical information, but it has not been approved for promulgation as a coordinated document. It is subject to modification. However, pending its promulgation as a coordinated Military specification, it may be used in procurement.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers setup boxes, suitable for use in mailing dental models, try-ins, and finished prosthetic products between the laboratory and installations serviced by the laboratory.

1.2 Classification.

1.2.1 Sizes. Setup boxes shall be of the following sizes, as specified (see 6.1 and Table I):

Size 1 - Large
Size 2 - Small

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-636 Box, Shipping, Fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:07Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

TECHNICAL ASSOCIATION OF THE PULP AND PAPER INDUSTRY (TAPPI)

TAPPI T401m	Fiber Analyses Paper and Paperboard.
TAPPI T402os	Standard Conditioning and Testing Atmospheres for Paper, Board, Pulp Handsheets and Related Products.
TAPPI T411os	Thickness (Calipher) of Paper and Paperboard.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, Dunwoody Park, Atlanta, GA 30341.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Paperboard. The paperboard used in the fabrication of the boxes shall be natural sulfate fiber, laminated, kraft board of 0.060 + 0.002, -0.004 inch thickness. As an alternate paperboard may be composed of 70% sulfate and 30% reworked kraft. Tests for fiber analyses and thickness shall be conducted as indicated in 4.4.2 and 4.4.3 respectively.

3.1.1.1 Bursting strength. The minimum bursting strength of the paperboard shall be 300 points, when tested as specified in 4.4.4.

3.1.2 Metal fastenings. The edge stays and staples for use in metal fastenings shall be fabricated of steel suitable for the purpose. The metal edge stays shall be not less than 1 inch (in.) in width and 0.010 in. in thickness and shall be painted with a suitable paint. Staples shall be suitably plated or coated to render them corrosion-resistant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:07Z
Check the source to verify that this is the current version before use.

3.2 Construction. The setup boxes shall be fabricated of paperboard as specified in 3.1.1. The boxes shall be of full-telescope design, consisting of a base and a cover, each being of one-piece construction. The inside depth of the cover shall be the overall depth of the base. Both the cover and base shall be crease-scored to give additional strength. The cover shall be made with two thumb notches or cutouts located on opposite sides. Boxes constructed with butted joints shall be accurately cut and scored so that the assembled parts fit closely without undue binding. Boxes constructed with lapped joints shall be slotted and scored, and when set up, the flaps shall not overlap. Metal fasteners shall pass through all of the pieces to be fastened and shall be clinched.

3.2.1 Joints. The joints of the boxes shall be either butted or lapped, unless a special type is specified (see 6.1).

3.2.1.1 Butted joints. The edge of both base and cover shall meet at the joints and shall be secured by means of metal edge stays (see 3.1.2). The stays shall extend 1/8- to 1/4-in. from the ends of the joints.

3.2.1.2 Lapped joints.

3.2.1.2.1 Base. The flaps shall be extensions of the ends and shall meet at the inside center of the sides. The fastening shall be accomplished by means of three staples (see 3.1.2) on both sides, one near each corner and one in the middle, overlapping both ends of the flaps and fastening them together.

3.2.1.2.2 Cover. The flaps shall be extensions of the sides and shall meet at the inside center of the ends. The fastening shall be accomplished by means of three staples (see 3.1.2) on each end, one staple near each corner and one in the middle, overlapping both ends of the flaps and fastening them together.

3.3 Dimensions. The base of the box shall meet the inside dimensions specified in Table I. A tolerance of $\pm 10\%$ is permissible.

Table I Dimensions (inside)

Size	Length (in.)	Width (in.)	Height (in.)
1	6	4	3-3/4
2	4-1/8	3-7/16	2-9/16

3.4 Identification marking. Each box shall be permanently and legibly marked on an exterior surface of the cover with the name or registered trademark of the manufacturer, box size and the words, "RE-USE CONTAINER."

Source: https://assist.dla.mil -- Downloaded: 202640-21T10:07Z
Check the source to verify that this is the currentversion before use.

3.5 Workmanship. Workmanship shall be first class throughout. The setup boxes shall be well made and accurately manufactured in accordance with good commercial practice and shall be free from imperfections which may impair their utility. The parts shall be cut square and be creased and slotted in such a manner that in assembly they will fit closely without undue binding. There shall be no surface breaks due to creasing or other causes. In the setup boxes, there shall be no visible cracks in the fastenings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of 3 years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificate of quality. Certificate of quality, supplied by the manufacturer of the paperboard, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the item identification, the name of the material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105 and Table II.

Source: https://assist.dla.mil -- Downloaded: 202640-21T10:07Z
Check the source to verify that this is the currentversion before use.

Table II Sampling for examination

	Inspection level	AQL (percent defective)
For visual examination		
Major defects	II	1.0
Minor defects	II	2.5

4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105 and Table III. The unit of product for test shall be the basic paper which shall be traceable to the lot number.

Table III Sampling for tests

Characteristic	Requirement	Test procedure	Inspection level
Fiber analyses	3.1.1	4.4.2	S-2
Thickness	3.1.1	4.4.3	S-2
Bursting strength	3.1.1.1	4.4.4	S-2

4.3 Examination. The dental boxes shall be examined to determine compliance with all requirements contained in this specification.

4.3.1 Classification of defects. Examination shall be conducted in accordance with Table IV.

Table IV Classification of defects

Categories	Defects
Major	
101	Base or cover not one piece.
102	Base and cover not completely crease-scored.
103	Metal fasteners not clinched and securing all necessary pieces.
104	Folds not free of tears.
105	Staples not plated or coated.
Minor	
201	Thumb notches (or cut-out) not present.
202	Flaps (lapped joints) not free of overlap.
203	Identification marking and re-use phrase omitted or not on cover of exterior surface.
204	Lapped joints not secured with minimum number of staples (sides or ends).
205	Edge stays not painted.

* Examination shall not be restricted to the classified possible defects listed above.

4.3.2 Dimensional examination. The boxes shall be examined for defects in dimensions. Any dimension not within the tolerance specified shall be classified as a defect.

Source: https://assist.dla.mil -- Downloaded: 202610-21T10:07Z
Check the source to verify that this is the current version before use.

4.4 Tests.

4.4.1 Conditioning. Before testing, the paperboard samples shall be conditioned to atmospheric conditions as described in TAPPI T402os.

4.4.2 Fiber analyses. Fiber analyses shall be conducted in accordance with TAPPI T401m.

4.4.3 Thickness. Thickness shall be determined as indicated in TAPPI T411os.

4.4.4 Bursting strength.

4.4.4.1 Apparatus (Mullen or Cady type). The bursting strength test consists essentially of clamping the fiberboard between two surfaces having concentric circular apertures of approximately 1 square inch area (1.20 in. diameter) and then applying hydraulic pressure through a rubber diaphragm secured to one of the circular apertures so as to burst a hole through the board exposed to the opening. The pressure required to burst the board is recorded by means of a pressure gauge calibrated to read in pounds per square inch. Either a hand or a motor-driven tester may be used. The hydraulic system of the tester shall be filled with glycerine and maintained free from entrapped air when in use.

4.4.4.2 Bursting strength method. The bursting strength of fiberboard shall be determined as follows: After conditioning as required in 4.4.1, the board shall be clamped firmly in the machine to prevent slipping. Pressure shall be applied by action of motor drive or hand wheel. The wheel of the hand driven testing machine shall be turned at a uniform speed of approximately two revolutions per second. If the board slips during a test, the result shall be disregarded. Six punctures shall be made, three from each side of the board. To comply with this specification, the average of the six tests shall not fall below the strength requirements specified in 3.1.1.1.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be Level A, B or C as specified (see 6.1).

5.1.1 Unit of issue. One box, as specified, constitutes one unit of issue.

5.1.2 Level A.

5.1.2.1 Unit package. Forty eight units of Size 1 or 96 units of Size 2 shall be packed in a box of appropriate size and design constructed in accordance with PPP-B-636, class weather-resistant, grade V3c. Closure, waterproofing and strapping shall be as specified in the appendix of the box specification. Special requirements of applicable table shall apply.

Source: https://assist.dla.mil -- Downloaded: 20261O-21T10:07Z
Check the source to verify that this is the current version before use.

5.1.3 Level B.

5.1.3.1 Unit package. Forty eight units of Size 1 or 96 units of Size 2 shall be packed in a box of appropriate size and design constructed in accordance with PPP-B-636, class domestic. Closure shall be as specified in the appendix of the box specification.

5.1.4 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.2 Packing. No overpacking is required.

5.3 Marking.

5.3.1 Unit package. Each unit package shall be marked as required for the exterior container in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. National Stock Number (NSN).
c. Size required (see 1.2.1).
d. Type of joint if other than specified (see 3.2.1).
e. Selection of applicable level of packaging (see 5.1).

6.2 This specification covers the following items as listed in the Federal Supply Catalog:

National Stock No.	Item Identification
8115-00-511-5750	BOX, SETUP, Mailing, Dental, Large
8115-00-511-5775	BOX, SETUP, Mailing, Dental, Small

Custodians:
Army - GL
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 8115-0383
is

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:07Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-B-37173 (DSA-DM)

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:07Z
Check the source to verify that this is the current version before use.

FOLD

Defense Personnel Support Center
2800 South 20th Street
Philadelphia, PA 19101

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304

Commander
Defense Personnel Support Center
ATTN: DPSC-ATT
2800 South 20th Street
Philadelphia, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:07Z
Check the source to verify that this is the current version before use.