MILITARY SPECIFICATION

CASE, MEDICAL INSTRUMENT AND SUPPLY SET, NYLON, NON-RIGID, NO. 8

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a nylon cloth case suitable for mounting on an individual's pistol belt or attaching to parachute or gear harness.

2. APPLICABLE DOCUMENTS

2.1 Specifications, standards, and drawing. The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

V-T-285	Thread, Polyester
PPP-B-636	Boxes, Shipping, Fiberboard

Military

MIL-W-4088	Webbing, Textile, Woven Nylon.
MIL-T-5038	Tape, Textile and Webbing, Textile, Reinforcing, Nylon.
MIL-H-9890	Hardware, Individual Load Carrying Equipment: and Hardware, Miscellaneous.
MIL-L-10547	Liners, Case and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.
MIL-F-10884	Fasteners, snap.
MIL-E-20652	Eyelets, Metallic, with washers.
MIL-F-21840	Fastener Tapes, Hook and Pile, Synthetic.
MIL-C-43128	Cloth, Plain Weave, Nylon· Water Repellent, OG-106.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-751	Stitches, Seams, and Stitchings.

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

DRAWING

Defense Personnel Support Center (DPSC)

1343	Case, Medical Instrument and Supply Set, Nylon, Non-rigid, No. 8.

(Copies of specifications, standards, and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

THE COLOR ASSOCIATION OF THE UNITED STATES, INC.

Department of Defense Standard Shades for Sewing Threads, 1968

(Application for copies should be addressed to the Color Association of the United States, Inc. 200 Madison Avenue, New York, N.Y. 10016.)

3 REQUIREMENTS

3.1 Component parts. The case shall consist of a back and flap piece, a box-pocket piece, two curtain type snap fasteners, two keepers with slide, a hook and pile loop and two eyelets and washers.

3.2 Materials. Except where otherwise specified, materials shall conform to the applicable portions of the specifications, standards, and drawing specified herein, and as described in 3.3 and shall be capable of meeting the requirements specified therein. In addition, the metals shall conform to the chemical requirements of their applicable specifications when tested as specified in section 4. When materials to be used are not specifically designated, those used shall be of the highest commercial quality, and entirely suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.

3.2.1 Cloth, nylon. The nylon cloth shall be olive green No. 106, water repellent, conforming to MIL-C-43128.

3.2.2 Webbing, nylon. The 2-1/4 inch wide nylon webbing shall be Type VIIIc of MIL-W-4088.

3.2.2.1 Color and finish. The nylon webbing shall be dyed olive drab number 7 to approximate the standard shade.

3.2.3 Tape, nylon. The binding tape shall be OD-7, conforming to type III of MIL-T-5038.

3.2.4 Thread, polyester. The thread for all stitching, except overedge stitching, shall be type I, class 1, subclass B, size F, of V-T-285. Size B thread shall be used on overedge stitching. Thread shall be dyed Olive Drab Shade S-1, C. I. 66022, except that the colorfastness requirements and test methods shall be limited to weathering only.

3.2.5 Fasteners, snap, curtain style. Snap fasteners shall be style 1, finish 2, black, of MIL-F-10884.

3.2.6 Fasteners, hook and pile. The hook and pile fasteners shall be olive green No. 106 in color and conform to Types 1 or 2, of MIL-F-21840.

3.2.7 Keeper, with slide. The keeper, with slide, shall conform to the requirements for Type X of MIL-H-9890.

3.2.8 Eyelets and Washers. The eyelets and washers shall conform to MIL-E-20652 and shall be eyelet No. 4094 and washer No. 4096.

3.3 Construction. The construction of the case shall conform to the requirements specified herein and to those shown on Defense Personnel Support Center Drawing 1343.

3.3.1 Stitching, machine. All stitching shall conform to FED-STD-751 as follows:

For all stitching except overedge stitching, type 301, 8 to 10 stitches per inch.

For overedge stitching (single operation optional), type 503 or 504, 8 to 10 stitches per inch.

For joining seams and overedge stitching (simultaneous operation optional), type 301 in combination with 503, 504 or 502, 8 to 10 stitches per inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.

All edges of joining seams shall be overstitched together. There shall be no lubrication of the thread by any means, prior to or during sewing. Any of the operations requiring box, box with cross stitch, W stitching, straight line tacking or any other design of stitching cited in this specification may be performed with an automatic stitching machine provided the requirements for stitch pattern, stitches per inch, size, and types of thread are met; and at least three or more tying, overlapping, or back stitches are used to secure the ends of stitching.

3.3.1.1 Type 301 stitching. Thread breaks in stitching shall be overstitched not less than 1 inch at each break. Stitching shall be backstitched not less than 1 inch at the ends, except where ends are turned under in a hem or held down by other stitching Thread tension shall be maintained so that there will be no loose stitching, and the lock will be imbedded in the materials sewed.

3.3.1.2 Overedge stitching. Thread breaks in overedge stitching shall be overstitched not less than 3/4 inch at each break. Thread tension shall be maintained so that there will be no loose stitching.

3.3.2 Attaching of snap fasteners. Holes for snap fasteners, male and female, shall be kept to the minimum diameter required for forcing fastener into place and for proper securing. The male and female fasteners shall be properly spaced and aligned as shown on the drawing to provide neat and secure closure.

3.3.3 Fusing of nylon webbing. All ends of nylon webbing shall be fused after cutting.

3.4 Marking for identification. Each case shall be legibly and permanently marked with black waterproof ink or paint in accordance with the drawing.

3.5 Workmanship. Workmanship shall be first class throughout. Complete cases shall be well made and free from defects which detract from their appearance or may impair their serviceability

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the nylon cloth, webbing, tape, thread, hardware, and fasteners, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identiy has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Quality conformance inspection. The examinations and tests required to assure conformance of those items or lots of items to be offered for acceptance are classified as specified in tables I and II (see 4.2.1 and 4.3.1) and 4.4.

4.2.1 Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105. The inspection levels and acceptable quality levels shall be as indicated in table I. Unit of product for examination purposes shall be one case.

Table I. Sampling for Visual Defects

	Inspection level	AQL (defects per 100 units)
Major	II	2.5
Total (Major and Minor combined)	II	6.5

4.2.2 Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, Inspection Level S-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.

4.2.3 Sample unit usage. Where feasible, the same sample unit shall be used for the determination of two or more test characteristics.

4 3 Examination.

4.3.1 Case examination. The case shall be examined for defects including, but not limited to, those listed in table II

Table II. Classification of Defects

Categories	Defects
Major	
101	Any component missing.
102	Any required operation omitted or improperly performed.
103	Any hole, cut, tear, mend, patch or unauthorized splice.
104	Any needle chew
105	Any weakening defect such as smash, multiple float, or loose slub that may develop into a hole
106	One or more spots or stains of any obviously permanent nature.
107	Any seam twisted or puckered as to impair appearance or serviceability.
108	Seam type other than specified
109	Stitch type other than specified
110	Less than 8 stitches per inch.
111	One or more required rows of stitching omitted.
112	Any open seam 1/4 inch or more.
113	Raw edge
114	Webbing with frayed or scalloped edge.
115	Exposed end of webbing not seared.
116	Curtain fastener broken or malformed
117	Any burr or sharp edge on hardware.
118	Finish on hardware omitted
119	Not hook and file fastener specified.
120	Hook and pile fastener does not effect a secure closure
121	Any marking omitted, incorrect, or illegible.
Minor	
201	One or more removable noticeable spots or stains
202	Thread ends not trimmed
203	Any part of case pleated, twisted, or caught in any unrelated row of stitching.
204	Any broken or skipped stitch, not amounting to an open seam, occurring twice or more in the same row of stitching. Open seam less than 1/4 inch.
205	Any end of stitching backstitched less than specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.

Table II Classification of Defects (Cont'd)

Categories	Defects
Minor	
206	Finish on hardware not uniform.
207	Loop not opened by pull on webbing to which hook fastener had been sewn.
208	Any markings not located as specified.

4.3.2 Dimensional defects During this examination, any measurement deviating from the normal dimensions and tolerances of the finished case specified in the drawing shall be scored as a size measurement defect The sample unit for this examination shall be one completely fabricated case. The lot size shall be expressed in units of one case The sample size shall be selected in accordance with inspection level S-3 of MIL-STD-105. The acceptable quality level shall be 4.0 (defects per 100 units).

4.3.3 Preparation for delivery. An examination shall be made to determine whether the packaging, packing, and marking comply with the requirements of Section 5. Defects shall be scored as specified in Table III. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 and the acceptable quality level shall be 4.0 defects per hundred units.

Table III Examination of preparation for delivery

Examination	Defect
Containers	Not as specified.
Quantity	Quantity in interior packages and shipping containers not as specified
Packaging and packing materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, tape improperly applied, or containers distorted.
Marking	Omitted, incorrect, illegible, improper location, sequence, or method of application

4.4 Tests Tests shall be conducted to determine compliance with the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging Packaging shall not be required.

5.1.1 Unit of issue. Each case constitutes one unit of issue.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Twenty four (24) cases shall be neatly folded and packed flat in a snug- fitting box constructed in accordance with PPP-B-636, type CF, class weather-resistant. Closure, strapping and waterproofing shall be as specified in the appendix of the box specification.

5.2.2 Level B. Twenty four (24) cases shall be neatly folded and packed flat in a snug-fitting box constructed in accordance with PPP-B-636, type CF, class domestic. Closure shall conform to method II as specified in PPP-B-636.

5.2.3 Level C The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, constructed as to insure acceptance and safe delivery called for in the contract or purchase order.

5.3 Marking Marking shall be as specified in MIL-STD-129.

6. NOTES

6.1 Intended use. This item is designed as a carrying case to contain a plastic insert, NSN 6545-00-125-5527, that is the inner container for the components of NSN 6545-00-823-8165, FIRST AID KIT, INDIVIDUAL.

6.2 Ordering data. Procurement documents should specify the following:

a Title, number and date of this specification
b National Stock Number
c. Selection of applicable level of packing (see 5.2).

6.3 This specification covers the following item listed in the Federal Supply Catalog

National Stock Number	Item Identification
6545-00-180-6239	CASE, MEDICAL INSTRUMENT AND SUPPLY SET, Nylon, Non-rigid, No. 8.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DSA-DM

Project No. 6545-0019
cs

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FOI UT ALONG THIS LINE)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5. PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements All users of military standardization documents are invited to provide suggestions This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems Enter in block 6 any remarks not related to a specific paragraph of the document If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 4966 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Personnel Support Center
ATTN: DPSC-LS
2800 South 20th Street
Philadelphia, PA 19101

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T10:08Z
Check the source to verify that this is the current version before use.