MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, COAXIAL, 0.0865 INCH (2.20 mm) DIAMETER, SEMIRIGID, 50 OHMS

This amendment forms a part of Military Specification Sheet MIL-C-17/133b, dated 17 January 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

TABLE I, add the following new part numbers:

Part number	Inner conductor	Dielectric core	Outer conductor 1/	Weight, per 1,000 feet (maximum)
M17/133-00012	Solid, silver-coated copper-clad steel diameter .0201 ±.0005 inch.	Type F-1 diameter, .066 ±.002 inch.	Seamless aluminum tubing 7/ diameter, .0865 ±.001 inch.	7.5
M17/133-00013	Same as above	Same as above	Seamless aluminum tubing 7/ diameter, .0865 +.002 -.001 inch tin plated in accordance with MIL-T-10727, type I, .0003 minimum inch thick.	8.0
M17/133-00014	.0201 ±.0005 inch diameter. 4/	Same as above	Seamless aluminum tubing 7/ diameter, .0865 ±.001 inch.	7.5
M17/133-00015	Same as above	Same as above	Seamless aluminum tubing 7/ diameter, .0865 +.002 -.001 inch tin plated in accordance with MIL-T-10727, type I, .0003 minimum inch thick.	8.0
M17/133-00016 5/ 6/	Solid, silver-coated copper-clad steel diameter .0201 ±.0005 inch.	Same as above	Copper tubing, diameter, 3/ .0865 +.002 -.001 inch silver plated in accordance with QQ-S-365, Type II, Grade A, 300µ inches, minimum.	15.8
M17/133-00017 5/ 6/	.0201 ±.0005 inch diameter. 4/	Same as above	Copper tubing, diameter, 3/ .0865 +.002 -.001 inch silver plated in accordance with QQ-S-365, Type II, Grade A, 300µ inches, minimum.	15.8

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

PAGE 3

TABLE I, Part number M17/133-00011, delete note "3/" and substitute note "6/".

TABLE I, at the end of footnote 2/, add the following sentence:

"33,000 psi, minimum, 30 percent elongation, maximum."

Table I, following footnote 6/, add:

7/ The tensile strength (outer conductor) shall be 15,500 psi, maximum, 40 percent elongation minimum measured over 2 inches."

PAGE 4

Eccentricity, delete "8.5 percent, maximum" and substitute "8 percent, maximum."

PAGE 5

Figure 2. Power rating and attenuation, delete and substitute the following:

"1. M17/133-RB405, 00001, 00002, 00003, 00006 through 00009, 00012, 00013 and 00016.
2. M17/133-00004, 00005, 00010, 00011, 00014, 00015 and 00017."

PAGE 6

Bendability, add the following: "Mandrel diameter .140 inch maximum for -00012 through -00015."

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, ME, MI
Navy - AS, MC, OS, SH
Air Force - 17, 19, 99
DLA - ES, IS

Preparing activity:
DLA - ES

(Project 6145-2076)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.