INCH-POUND
MIL-C-17/133D
AMENDMENT 3
19 October 2000
SUPERSEDING
AMENDMENT 2
1 March 1994

MILITARY SPECIFICATION SHEET

CABLE, RADIO FREQUENCY, COAXIAL, 0.0865 INCH (2.20mm)
DIAMETER, SEMIRIGID, 50 OHMS

This amendment forms a part of MIL-C-17/133D, 17 January 1992, and
is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* Table I, add the following new part numbers:

Part number	Inner conductor	Dielectric core	Outer conductor 1/	Weight, per 1,000 feet, (maximum)
M17/133-00012	Solid, silver-coated Copper-clad steel Diameter, .0201 ± .0005 Inch.	Type F-1 diameter, .066 ± .002 inch.	Seamless aluminum tubing 7/ diameter, .0865 ± .001 inch	7.5
M17/133-00013	Same as above	Same as above	Seamless aluminum tubing 7/ Diameter, .0865 +.002 -.001 inch Tin Plated in accordance with ASTM-B545, .0003 Minimum inch thick	. 8.0
M17/133-00014	.0201 ± .0005 inch diameter. 4/	Same as above	Seamless aluminum tubing 7/ diameter, .0865 ± .001 inch	7.5
M17/133-00015	Same as above	Same as above	Seamless aluminum tubing 7/ Diameter, .0865 +.002 -.001 inch Tin Plated in accordance with ASTM-B545, .0003 Minimum inch thick.	8.0
M17/133-00016	Solid, silver-coated Copper-clad steel Diameter, .0201 ± .0005 Inch.	Same as above	Copper tubing, diameter 3/ .0865 + .002 inch, -.001 inch, silver plated in accordance with QQ-S-365, Type II, Grade A, 300µ inches, Minimum.	15.8
M17/133-00017	.0201 ± .0005 inch diameter. 4/	Same as above	Copper tubing, diameter 3/ .0865 + .002 inch, - .001 inch, silver plated in accordance with QQ-S-365, Type II, Grade A, 300µ inches, Minimum.	15.8

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

Part number	Inner conductor	Dielectric core	Outer conductor	Weight, per 1,000 feet (maximum)
M17/133-00018	Solid, silver-coated Copper-wire Diameter, .0201 ± .0005 Inch.	Type F-1 diameter, .066 ± .002 inch.	Copper tubing 2/ 3/ Diameter .0865 +.002, -.001 inch, 90/10 tin-plated in accordance with SAE-AMS-P-81728, .0003 inch thick minimum.	15.7

PAGE 3

Table I, Part number M17/133-00011, delete note "3/" and substitute "6/".

Table I, at the end of footnote 2/, add the following sentence:

"33,000 psi, minimum, 30 percent elongation, maximum."

Table I, following footnote 6/, add:

"7/ The tensile strength (outer conductor) shall be 15,500 psi, maximum, 40 percent elongation minimum measured over 2 inches."

PAGE 4

Eccentricity, delete "8.5 percent, maximum." And substitute "8 percent, maximum."

PAGE 5

Figure 2, Power rating and attenuation, delete and substitute the following:

"1. M17/133-RG405, 00001, 00002, 00003, 00006 through 00009, 00012, 00013, 00016 and 00018.
2. M17/133-00004, 00005, 00010, 00011, 00014, 00015 and 00017."

PAGE 6

Bendability, add the following: "Mandrel diameter .140 inch maximum for –00012 through –00015."

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

Review activities:
Army – AR, AT, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99

Preparing activity:
DLA – CC

(Project 6145-2274-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.