INCH - POUND


MIL-DTL-17/133E
26 July 2006
SUPERSEDING
MIL-C-17/133D
17 January 1992

DETAIL SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, COAXIAL, 0.0865 (2.20 mm) DIAMETER, SEMIRIGID, 50 OHMS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-17.



Inches	mm
.0003	0.008
.0005	0.013
.001	0.03
.002	0.05
.0201	0.511
.066	1.68
.086	2.18
.0865	2.197

* Metric conversion for table I

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 1. Configuration.

AMSC N/A FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

TABLE I. Description.

Part or Identifying Number (PIN)	Inner conductor	Dielectric core	Outer 1/ conductor	Weight, per 1,000 feet (maximum)
M17/133-RG405	Solid, silver-coated, copper-clad steel .0201 ±.0005 inch	Type F-I diameter .066 ±.002 inch	Copper tubing, diameter .0865 ±.001 inch 2/	15.3
M17/133-00001	Same as above	Same as above	Copper tubing tin plated in accordance with ASTM B545, .0003 inch, minimum thick, diameter .0865 +.002 -.001 inch 2/ 3/	15.8
M17/133-00002	Solid, silver -coated, copper wire, diameter .0201 ± .0005 inch	Same as above	Copper tubing diameter .0865 ± .001 inch 2/	15.2
M17/133-00003	Same as above	Same as above	Copper tubing tin plated in accordance with ASTM B545, .0003 inch, minimum thick, diameter .0865 +.002, -.001 inch 2/ 3/	15.7
M17/133-00004	.0201 ±.0005 inch, diameter 4/	Same as above	Copper tubing, diameter .086 ±.001 inch. 2/	15.4
M17/133-00005	Same as above	Same as above	Copper tubing diameter, .086 +.002, -.001 inch, tin plated in accordance with ASTM B545, .0003 inch minimum thick. 2/ 3/	15.9
M17/133-00006 5/ 6/	Solid silver-coated, copper-clad steel .0201 ±.0005 inch.	Same as above	Copper tubing diameter .0865 ±.001 inch	15.3
M17/133-00007 5/ 6/	Same as above	Same as above	Copper tubing tin plated in accordance with ASTM B545, .0003 inch minimum thick. Diameter .0865 +.002, -.001 inch. 3/	15.8

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

TABLE I. Description – Continued.

PIN	Inner conductor	Dielectric core	Outer conductor	Weight, per 1,000 feet (maximum)
M17/133-00008 5/ 6/	Solid silver-coated copper wire, diameter .0201 ±.0005 inch.	Type F-1 diameter .066 ±.002 inch.	Copper tubing diameter .0865 ±.001 inch.	15.2
M17/133-00009 5/ 6/	Same as above	Same as above	Copper tubing tin plated in accordance with ASTM B545, .0003 inch minimum thick. diameter .0865 +.002, -.001 inch. 3/	15.7
M17/133-00010 5/ 6/	.0201 ±.0005 inch diameter 4/	Same as above	Copper tubing, diameter .086 ±.001 inch.	15.4
M17/133-00011 2/ 6/	.0201 ±.0005 inch, diameter 4/	Same as above	Copper tubing tin plated in accordance with ASTM B545, .0003 inch minimum thick. diameter .086 +.002, -.001 inch. 3/	15.9
M17/133-00012	Solid, silver coated Copper-clad steel, diameter, .0201 ±.0005 inch.	Same as above	Seamless aluminum tubing, diameter, .0865 ±.001 inch 7/	7.5
M17/133-00013	Same as above	Same as above	Seamless aluminum tubing, diameter, .0865 +.002 -.001 inch, tin plated in accordance with ASTM B545, .0003 inch minimum thick 3/ 7/	8.0
M17/133-00014	.0201 ±.0005 inch diameter. 4/	Same as above	Seamless aluminum tubing, diameter, .0865 ±.001 inch 7/	7.5

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

TABLE I. Description – Continued.

PIN	Inner conductor	Dielectric core	Outer conductor	Weight, per 1,000 feet (maximum)
M17/133-00015	Same as above	Same as above	Seamless aluminum tubing, diameter, .0865 +.002 -.001 inch, tin plated in accordance with ASTM B545, .0003 inch minimum thick 3/ 7/	8.0
M17/133-00016	Solid, silver coated Copper-clad steel, diameter, .0201 ±.0005 inch.	Same as above	Copper tubing, diameter .0865 +.002 -.001 inch, silver plated in accordance with ASTM B700, Type 2, Grade A, 300µ inches, minimum 3/	15.8
M17/133-00017	.0201 ±.0005 inch diameter. 4/	Same as above	Same as above	15.8
M17/133-00018	Solid, silver coated Copper wire, diameter, .0201 ±.0005 inch.	Same as above	Copper tubing, diameter .0865 +.002 -.001 inch, 90/10 tin-plated in accordance with SAE-AMS-P-81728, .0003 inch thick, minimum 2/ 3/	15.7

1/ Welded outer conductor in accordance with ASTM B447 and MIL-DTL-17 is optional.
2/ Hard outer conductor required. 33,000 psi, minimum, 30 percent elongation, maximum.
3/ The outer diameter dimension is after plating.
4/ Nickel - coated, copper-clad steel wire, conforming to ASTM B559, class N 40 HS two percent with uniform and continuous silver coating, 40 microinches minimum thick. Wire shall be drawn to final size after plating.
5/ Tensile strength (outer conductor): 35,000 pounds per inch^2 , maximum, 40 percent elongation minimum measured over two inches.
6/ These PIN's are for soft outer conductor cables only.
7/ The tensile strength (outer conductor) shall be 15,000 psi, maximum, 40 percent elongation minimum, measured over 2 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

ENGINEERING INFORMATION:

Continuous working voltage: 1,500 V rms, maximum.

Operating frequency: 20 GHz, maximum.

Velocity of propagation: 69.5 percent, nominal.

Power rating: See figure 2.

Operating temperature range: - 40°C to + 125°C.

Inner conductor properties:

DC resistance (maximum at 20ºC): 2.57 ohms per 100 feet for class A wire.
6.57 ohms per 100 feet for class HS wire.

Elongation: 15 percent minimum for class 40 A wire.
1.0 percent minimum for class 40 HS wire.

Tensile strength: 90,000 Lb/in^2 minimum for class 40 HS wire.

Tensile strength (outer - conductor): 35,000 pounds per inch^2, maximum, 40 percent elongation minimum measured over two inches (not applicable to M17/133-RG405 through -00005) in accordance with ASTM E8.

Engineering notes: This cable is useful in critical RF performance applications (see connector series SMA in accordance with MIL-PRF-39012). This cable is generally manufactured in 20 - foot length. Different lengths are available.

REQUIREMENTS:

Dimensions, configuration, and descriptions: See figure 1 and table I.

Environmental and mechanical:

Eccentricity: 8 percent, maximum.

Adhesion of conductors:

Inner conductor to core: 4 pounds minimum, 25 pounds maximum.

Outer conductor to core: 4 pounds minimum.

Aging stability: Not applicable.

Stress crack resistance: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

Outer conductor integrity: Four specimens, approximately 2 feet long, shall be cut from the sample unit. The specimens shall be suspended in a heat chamber without touching one another or the walls of the chamber and conditioned for 1 hour 30 minutes minimum at the specified maximum operating temperature ±5ºC. Heated air shall be circulated so as to maintain a uniform test temperature. After the conditioning period, the specimens shall be removed from the heat chamber and conditioned at room ambient temperature for 4 hours minimum. The specimen shall then have one end immersed into molten solder to a depth of 0.5 inch minimum for 15 seconds minimum. The molten solder temperature shall be +230°C minimum. After the conditioning period, the specimens shall be removed from the molten solder and conditioned at room ambient temperature for 1 hour minimum. Examine the specimens for cracks, flaws, or other damage in the outer conductor material.

Cold bend: Not applicable.

Dimensional stability: +125°C ± 5°C.

Core to jacket: .015 inch, maximum.

Contamination: Not applicable.

Bendability: Mandrel diameter: .25 inch, maximum (except dash numbers - 00006 through -00011, mandrel diameter shall be .100 inch, maximum). Mandrel diameter .140 inch maximum for -00012 through -00015. Performance may degrade after being subjected to the mandrel test.

Flammability: Not applicable.

Weight: See table I.

Electrical:

Test frequency: 500 MHz to 20 GHz.

Spark test: Not applicable.

Voltage withstanding: 5,000 V rms.

Insulation resistance: Not applicable.


Corona extinction voltage: 1,500 V rms, minimum.

Characteristic impedance: 50.0 ± 1.5 ohms.

Attenuation: See figure 2.

Structural return loss: See figure 3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.




Maximum attenuation ———————— (Test requirements shall be as noted as line indicated on graph)
Maximum power - - - - - - - - - - - At 25ºC at sea level.

1. M17/133-RG405, -00001, -00002, -00003, 00006 through -00009, -00012, -00013, -00016 and 00018.
2. M17/133-00004, -00005, -00010, -00011, -00014, -00015 and -00017.

Attenuation			Power
MHz	dB 1	dB 2	Watts
500	15	25	180
1000	22	34	130
5000	50	65	54
10000	80	90	35
20000	130	130	20

FIGURE 2. Power rating and attenuation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.



Structural Return Loss	
MHz	dB
500	28
5000	23
20000	15

FIGURE 3. Minimum structural return loss cable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

SWR	Reflection coefficient	Return loss dB
17.3910	.8913	1
8.7242	.7943	2
5.8480	.7079	3
4.4194	.6310	4
3.5698	.5623	5
3.0095	.5012	6
2.6146	.4467	7
2.3229	.3981	8
2.0998	.3548	9
1.9250	.3162	10
1.7849	.2818	11
1.6709	.2512	12
1.5769	.2239	13
1.4985	.1995	14
1.4326	.1778	15
1.3767	.1585	16
1.3290	.1413	17
1.2000	.1259	18
1.2528	.1122	19
1.2222	.1000	20
1.1957	.0891	21
1.1726	.0794	22
1.1524	.0708	23
1.1347	.0631	24
1.1192	.0562	25
1.1065	.0501	26
1.0725	.0447	27
1.0829	.0398	28
1.0738	.0356	29
1.0653	.0316	30

FIGURE 3. Minimum structural return loss cable – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

Capacitance: 32 pF per foot, maximum.

Capacitance stability: Not applicable.

Capacitance unbalance: Not applicable.

Transmission unbalance: Not applicable.

Phase stability: Not applicable.

Mechanically induced noise voltage: Not applicable.

Time delay: Not applicable.

PIN: See table II.

Supersession data: See table II.

TABLE II. Cross - reference of PIN.

PIN	Superseded PIN or type designation
M17/133-RG405	RG-405/U

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-17, this document references the following:

ASTM B447
ASTM B545
ASTM B559
ASTM B700
ASTM E8
MIL-PRF-39012
SAE-AMS-P-81728

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA - CC

Preparing activity:
DLA - CC

(Project 6145-2005-007)

Review activities:
Army – AT, AV, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:16Z
Check the source to verify that this is the current version before use.