MIL-C-17/135A
AMENDMENT 2
18 July 1985
SUPERSEDING
AMENDMENT 1
12 October 1982

MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, TRIAXIAL, DIAMETER
0.500 INCH, 50 OHM, WATERBLOCKED AND NON-WATER BLOCKED

This amendment forms a part of Military Specification Sheet MIL-C-17/135A, dated 22 September 1980, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* ENGINEERING INFORMATION, Inner conductor properties, following entry for Elongation, add:

"Tensile strength: Not applicable."

* REQUIREMENTS, Environmental and mechanical, following entry for Outer conductor integrity, add:

"Cold bend: -55°C ±2°C."

PAGE 5

* REQUIREMENTS, Electrical, entry for Spark test: Delete "8,000 Vrms, minimum" and substitute "8,000 V rms +10%, -0%."

REQUIREMENTS, Electrical, entry for Voltage withstanding, delete and substitute the following:

"10,000 V rms minimum applied between the inner and outer conductors with the outer conductor grounded; 500 V dc applied between the outer conductor and the extra shield with the extra shield grounded."

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modification, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES, IS

User activities:
Army - AR, ME
Navy - AS, MS, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - CR

(Project 6145-0911-29)

FSC 6145

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:17Z
Check the source to verify that this is the current version before use.