MILITARY SPECIFICATION SHEET

CABLE, RADIO FREQUENCY, FLEXIBLE COAXIAL,
95 OHMS, M17/137-00001

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the cable described herein shall consist of this document and the latest issue of Specification MIL-C-17.




FIGURE 1. Configuration.

TABLE I. Description.

Components	Construction details
Inner conductor	Seven strands of silver-coated, annealed-copper-covered, steel wire, .004 inch each. Overall diameter: 0.012 inch ±0.001.
Dielectric core	Type F-1: Solid extruded PTFE. Diameter: 0.102 inch ±0.003.
Outer conductor	Single braid of AWG #38, silver-coated copper wire. Diameter: 0.124 inch maximum. Coverage: 91.0% nominal Carriers: 16 Ends: 7 Picks/inch: 12.0% ±10
Jacket	Type XIII: PFA. Diameter: 0.141 inch ±0.004.

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:18Z
Check the source to verify that this is the current version before use.




FIGURE 2. Power rating @ 25°C sea level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:18Z
Check the source to verify that this is the current version before use.

ENGINEERING INFORMATION:

Continuous working voltage: 1,100 Vrms, maximum.
Operating frequency: 3 GHz, maximum.
Velocity of propagation: 69.5 percent, nominal.
Power rating: See figure 2.
Operating temperature range: -55° to +200°C.
Weight: 2 pounds per 100 feet, maximum.

Inner conductor properties:
DC resistance (maximum at 20°C): 24.45 ohms per 100 feet.
Elongation: 10 percent, minimum.
Tensile strength: 50 kilo/inch^2,minimum.
Engineering notes: This cable useful in high temperature applications. (See connector series "TNC", and "BNC" per MIL-C-39012.)

REQUIREMENTS:

Dimensions, configuration, and descriptions: See figure 1.

Environmental and mechanical:
Visual and mechanical examination: Applicable.
Eccentricity: 10 percent, maximum.
Adhesion of conductors:
Inner conductor to core: 1.5 pounds, minimum; 4 pounds, maximum.
Stress crack resistance: +250° ±5°C.
Cold bend: -55° ±2°C.
Dimensional stability: +200° ±5°C.
Inner conductor from core: .250 inch, maximum.
Inner conductor from jacket: .187 inch, maximum.
Flammability: Applicable.

Electrical:
Spark test: 2,000 Vrms, minimum.
Voltage withstanding: 2,000 Vrms, minimum.
Corona extinction voltage: 1,500 Vrms, minimum.
Characteristic impedance: 95 ohms ±5.
Attenuation: 17.0 dB per 100 feet maximum at .4 GHz.
Capacitance: 15.4 pF per foot, maximum.

Part number: M17/137-00001.

Custodians:
Army: EL
Navy - EC
Air Force - 99

Review activities:
Army - MI
Navy - SH
Air Force - 17, 85, 11
DLA - ES, IS

User activities:
Army - ME, AT, AR
Navy - AS, OS, MC
Air Force - 19

Preparing activity:
Army - EL

Agent:
DLA - ES

(Project 6145-0703-18)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R355

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-C-17/137 CABLE , RADIO FREQUENCY, FLEXIBLE COAXIAL, 95 OHMS, M17/137-00001

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   a. GIVE PARAGRAPH NUMBER AND WORDING

   b. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:18Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Electronics Command
ATTN: DRSEL-RD-TS
Fort Monmouth, NJ 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:18Z
Check the source to verify that this is the current version before use.