MILITARY SPECIFICATION SHEET

CABLE, RADIO FREQUENCY, FLEXIBLE, COAXIAL,
50 OHMS, M17/138-00001

This amendment forms a part of Military Specification Sheet MIL-C-17/138A, dated 27 April 1981, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

REQUIREMENTS, Environmental and mechanical, preceeding entry for Adhesion of conductors, add:

"Eccentricty: 10 percent, minimum."

REQUIREMENTS, Environmental and mechanical, following entry for Outer conductor integrity, add:

"Cold bend: -55°C ±2°C."

REQUIREMENTS, Electrical, entry for Spark test: Delete "2,000 Vrms, +25 percent,-0 percent and substitute "2,000 V rms +10%, -0%."

REQUIREMENTS, Electrical, entry for Voltage withstanding: Delete the word "minimum" and substitute "+10%, -0%."

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES, IS

User activities:
Army - AT, ME
Navy - AS, MC, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - CR

(Project 6145-0911-31)

FSC 6145

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:18Z
Check the source to verify that this is the current version before use.