INCH-POUND

MIL-M-28787/46C(SH)
AMENDMENT 2
7 January 1992
SUPERSEDING
AMENDMENT 1
6 September 1983

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

COUNTER, BINARY, DIGITAL, KEY CODE ZBY

This amendment forms a part of Military Specification MIL-M-28787/46C(EC), dated 1 September 1982, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense

PAGES 4, 5, 6, AND 7

TABLE I, Class II table heading Delete "100°" (four places) and substitute "85°" (four places).

PAGE 4

* TABLE I, Test conditions C1-C23, Min columns under 25 ± 5°C, class I and class II: Delete "-0 4" (five places) and substitute "-1.5" (five places)

* TABLE I, Test conditions C1-C23, Max columns under 25 ± 5°C, class I and class II· Delete "-1.5" (five places) and substitute "-0.4" (five places)

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:41Z
Check the source to verify that this is the current version before use.

PAGE 5

* TABLE I, Test condition M1, Min columns under class I and class II Delete "-228" (four places) and substitute "-336" (four places).

* TABLE I, Test condition M1, Min column under 25 ± 5°C Delete "-228" (one place) and substitute "-336" (one place).

* TABLE I, Test condition M1, Max columns under class I and class II. Delete "-336" (four places) and substitute "-228" (four places).

* TABLE I, Test condition M1, Max column under 25 ± 5°C Delete "-336" (one place) and substitute "-228" (one place)

* TABLE I, Test conditions N1-N15, Test type column Delete "X" and substitute "S".

PAGE 8

* 4.4.2. Delete and substitute the following

"4.4.2 Order of testing. Test conditions A through KK shall be performed in any order with the following exceptions Test conditions A, B, C, D, and N are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, or N are part of a sequence of tests, the order of testing shall be as follows A, B, C, D, and N where applicable, followed by the remaining tests in the sequence."

* 4.5.1: Delete the third sentence and substitute the following:

"When electrical testing is called for at the end of each temperature stabilization period, test conditions E through M, P, and R through KK shall be performed in the order specified in 4 4.2 using the initial limits for applicable operating temperature "

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:41Z
Check the source to verify that this is the current version before use.

* 4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests E through M, P, and R through KK shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I Following the return of the module to 25 ± 5°C, electrical tests E through M and P through KK shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I "

6.4 Delete and substitute the following

"6.4 Cross reference of classification. Military Specification MIL-M-28787/46 supersedes Department of the Navy, Naval Electronic Systems Command Drawing No 28687-0102-869 Part number M28787/46-1 supersedes part numbers 0102-869 and M28787/46."

6.5, second line. Delete "100°C" and substitute "85°C"

PAGES 21 AND 22

* TABLE VI, Test conditions C1 through C23, Min column Delete "-0.4" (two places) and substitute "-1.5" (two places)

* TABLE VI, Test conditions C1 through C23, Max column Delete "-1.5" (two places) and substitute "-0 4" (two places)

PAGE 36

* TABLE XII, Test condition M1, Min column Delete "-228" (one place) and substitute "-336" (one place).

* TABLE XII, Test condition M1, Max column: Delete "-336" (one place) and substitute "-228" (one place).

PAGE 38

* TABLE XIII, Test conditions N1 through N15, B to pin column Delete "12" (one place) and substitute "21" (one place)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:41Z
Check the source to verify that this is the current version before use.

MIL-M-28787/46C(SH)
AMENDMENT 2

NOTE. The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH

(Project 5963-N796)

Agent NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:41Z
Check the source to verify that this is the current version before use.