INCH-POUND

MIL-M-28787/65A
AMENDMENT 2
31 December 1992
SUPERSEDING
AMENDMENT 1
20 December 1983

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DECODER, DIGITAL, KEY CODE AHA

This amendment forms a part of Military Specification MIL-M-28787/65A(EC), dated 17 January 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

*4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through W shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and F are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, or F are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, and F where applicable, followed by the remaining tests in the sequence."

*4.5.1: Delete and substitute the following:

"4.5.1 Operating temperature tests. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through W in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions E, G through U, and W shall be performed in the order specified in 4.4.2 using the initial limits for applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:49Z
Check the source to verify that this is the current version before use.

*4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests E, G through U, and W shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests E, G through U, and W shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 5

*TABLE I, Test conditions D1-D24, Test type column: Delete "X" and substitute "S".

*TABLE I, Test conditions F1-F14, Test type column: Delete "X" and substitute "S".

PAGE 9

TABLE I, Test conditions V2-V5, V7-V10, V12-V14, Max columns: Delete "15" (four places) and substitute "20" (four places).

PAGE 13

FIGURE 2, NOTE 4: Add "Amplitude = 4 ± 1 V."

PAGE 36

*TABLE XI, Test condition J1, Connect B to pin column: Delete "5" (one place) and substitute "3" (one place).

PAGE 57

*TABLE XIV, Test conditions P163, P164, P167, and P168, Connect A to pin column: Delete "3" (four places) and substitute "23" (four places).

PAGE 70

*TABLE XIV, Test conditions Q163 and Q164, Connect A to pin column: Delete "3" (two places) and substitute "23" (two places).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:49Z
Check the source to verify that this is the current version before use.

PAGE 71

*TABLE XIV, Test conditions Q167 and Q168, Connect A to pin column: Delete "3" (two places) and substitute "23" (two places).

PAGE 85

TABLE XVIII, Test conditions V2 through V5, V7 through V10, and V12 through V14, Max column: Delete "15" (three places) and substitute "20" (three places).

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - SH
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0113)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:49Z
Check the source to verify that this is the current version before use.