MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MULTIPLEXER, DIGITAL, KEY CODE BHL

This amendment forms a part of Military Specification MIL-M-28787/66B(EC), dated 3 December 1982, and is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

TABLE I, Test conditions Q1-Q24, Max columns: Delete "22" (two places) and "25" (two places) and substitute "24" (two places) and "27" (two places), respectively.

TABLE I, Test conditions Q25-Q33, Max columns: Delete "35" (two places) and "38" (two places) and substitute "38" (two places) and "41" (two places), respectively.

PAGE 7

TABLE I, Test conditions R73-R96, Max columns: Delete "33" (two places) and "37" (two places) and substitute "36" (two places) and "40" (two places), respectively.

PAGE 11

6.4, Propagation delay time (t_{PHL}), D to $\overline{Q}$, out-of-phase, C_L = 50 pF: Delete "25" and substitute "27".

6.4, Propagation delay time (t_{PHL}), S to $\overline{Q}$, out-of-phase, C_L = 50 pF: Delete "38" and substitute "41".

6.4, Propagation delay time (t_{PLH}), D to Q, in-phase, C_L = 50 pF: Delete "37" and substitute "40".

PAGE 39

TABLE XI, Test condition K5, A to pin column: Delete "24".

PAGES 51 and 52

TABLE XV, Test conditions Q1 through Q24, Max column: Delete "22" (two places) and substitute "24" (two places).

PAGES 52 and 53

TABLE XV, Test conditions Q25 through Q33, Max column: Delete "35" (four places) and substitute "38" (four places).

PAGES 67, 68, and 69

TABLE XV, Test conditions R73 through R96, Max column: Delete "33" (four places) and substitute "36" (four places).

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N597)

FSC 5963

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:50Z
Check the source to verify that this is the current version before use.