INCH-POUND

MIL-M-28787/66B (SH)
AMENDMENT 2
26 October 1990
SUPERSEDING
AMENDMENT 1
16 January 1984

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MULTIPLEXER, DIGITAL, KEY CODE BHL

This amendment forms a part of Military Specification MIL-M-28787/66B (SH), dated 3 December 1982, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* TABLE I, Test conditions D1-D6, Test type column: Delete "X" and substitute "S"

* TABLE I, Test conditions J1-J32, Test type column Delete "X" and substitute "S"

PAGE 5

TABLE I, Test conditions Q1-Q24, Max columns: Delete "22" (two places) and "25" (two places) and substitute "24" (two places) and "27" (two places), respectively.

TABLE I, Test conditions Q25-Q33, Max columns Delete "35" (two places) and "38" (two places) and substitute "38" (two places) and "41" (two places), respectively

PAGE 7

TABLE I, Test conditions R73-R96, Max columns Delete "33" (two places) and "37" (two places) and substitute "36" (two places) and "40" (two places), respectively.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:50Z
Check the source to verify that this is the current version before use.

PAGE 9

* 4 4 2 Delete and substitute the following

"4 4.2 Order of testing Test conditions A through W shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and J are stress tests and shall be performed only at 25 ± 5°C If test conditions A, B, C, D, or J are part of a sequence of tests, the order of testing shall be as follows A, B, C, D, and J where applicable, followed by the remaining tests in the sequence "

* 4 5 1, sixth line Delete "D through V" and substitute "E through H, K through M, N1–N6, P1–P6, Q1–Q36, Q73–Q108, Q145–Q162, R1–R36, R73–R108, R145–R162, and V".

* 4 5.3, third and fourth line and sixth line. Delete "D through V" (two places) and substitute "E through H, K through M, N1–N6, P1–P6, Q1–Q36, Q73–Q108, Q145–Q162, R1–R36, R73–R108, R145–R162, and V" (two places)

PAGE 11

6 4 Propagation delay time (t_{PHL}), D to $\overline{Q}$, out-of-phase, C_L = 50 pF· Delete "25" and substitute "27"

6 4: Propagation delay time (t_{PHL}), S to $\overline{Q}$, out-of-phase, C_L = 50 pF: Delete "38" and substitute "41".

6 4: Propagation delay time (t_{PLH}), D to Q, in-phase, C_L = 50 pF Delete "37" and substitute "40".

PAGE 39

TABLE XI, Test condition K5, A to pin column· Delete "24"

PAGES 51 and 52

TABLE XV, Test conditions Q1 through Q24, Max column Delete "22" (two places) and substitute "24" (two places)

PAGES 52 and 53

TABLE XV, Test conditions Q25 through Q33, Max column: Delete "35" (four places) and substitute "38" (four places)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:50Z
Check the source to verify that this is the current version before use.

PAGES 67, 68, and 69

TABLE XV, Test conditions R73 through R96, Max column Delete "33" (four places) and substitute "36" (four places)

NOTE The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment

Preparing activity
Navy - SH

(Project 5963-N749)

Agent NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:50Z
Check the source to verify that this is the current version before use.