INCH-POUND

MIL-M-28787/67B (SH)
AMENDMENT 1
19 June 1991

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MULTIPLEXER, DIGITAL, KEY CODE JHD

This amendment forms a part of Military Specification MIL-M-28787/67B (EC), dated 1 June 1982, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions D1-D6, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions E1-E6, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions E1-E6, Min columns: Delete "-6" (four places) and substitute "-130" (four places).

TABLE I, Test conditions E1-E6, Max columns: Delete "-130" (four places) and substitute "-6" (four places).

TABLE I, Test conditions G1-G32, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions G1-G32, Min columns: Delete "-0.4" (four places) and substitute "-1.5" (four places).

TABLE I, Test conditions G1-G32, Max columns: Delete "-1.5" (four places) and substitute "-0.4" (four places).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:50Z
Check the source to verify that this is the current version before use.

PAGE 5

TABLE I, Test conditions L1-L30, Min columns: Delete "-0.01" (four places) and substitute "-0.40" (four places).

TABLE I, Test conditions L1-L30, Max columns: Delete "-0.40" (four places) and substitute "-0.01" (four places).

TABLE I, Test condition L31, Min columns: Delete "-0.01" (four places) and substitute "-1.60" (four places).

TABLE I, Test condition L31, Max columns: Delete "-1.60" (four places) and substitute "-0.01" (four places).

TABLE I, Test condition L32, Min columns: Delete "-0.01" (four places) and substitute "-0.80" (four places).

TABLE I, Test condition L32, Max columns: Delete "-0.80" (four places) and substitute "-0.01" (four places).

TABLE I, Test conditions N7-N12, Min columns: Delete "20" (four places) and substitute "15" (four places).

PAGE 8

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through W shall be performed in any order with the following exceptions. Test conditions A, B, C, D, E, and G are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, E, or G are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E, and G where applicable, followed by the remaining tests in the sequence."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:50Z
Check the source to verify that this is the current version before use.

4.5.1: Delete the third sentence and substitute the following:

"When electrical testing is called for at the end of each temperature stabilization period, test conditions F and H through V shall be performed in the order specified in 4.4.2 using the initial limits for applicable operating temperature."

* 4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests F and H through V shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests F and H through V shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 26

TABLE VII, Test conditions E1 through E6, Min column: Delete "-6" (one place) and substitute "-130" (one place).

TABLE VII, Test conditions E1 through E6, Max column: Delete "-130" (one place) and substitute "-6" (one place).

PAGES 49 AND 50

TABLE IX, Test conditions G1 through G32, Min column: Delete "-0.4" (two places) and substitute "-1.5" (two places).

TABLE IX, Test conditions G1 through G32, Max column: Delete "-1.5" (two places) and substitute "-0.4" (two places).

PAGES 62 AND 63

TABLE XIII, Test conditions L1 through L30, Min column: Delete "-0.01" (two places) and substitute "-0.40" (two places).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:50Z
Check the source to verify that this is the current version before use.

TABLE XIII, Test conditions L1 through L30, Max column: Delete "-0.40" (two places) and substitute "-0.01" (two places).

PAGE 63

TABLE XIII, Test condition L31, Min column: Delete "-0.01" (one place) and substitute "-1.60" (one place).

TABLE XIII, Test condition L31, Max column: Delete "-1.60" (one place) and substitute "-0.01" (one place).

TABLE XIII, Test condition L32, Min column: Delete "-0.01" (one place) and substitute "-0.80" (one place).

TABLE XIII, Test condition L32, Max column: Delete "-0.80" (one place) and substitute "-0.01" (one place).

PAGE 67

TABLE XV, Test conditions N7-N12, Min column: Delete "20" (one place) and substitute "15" (one place).

Preparing activity:
Navy - SH

(Project 5963-N769)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:50Z
Check the source to verify that this is the current version before use.