INCH-POUND

MIL-M-28787/68A
AMENDMENT 1
31 December 1992

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE LHH

This amendment forms a part of Military Specification MIL-M-28787/68A(EC), dated 12 October 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions D1-D8, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions E1-E8, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions F1-F28, Test type column: Delete "X" and substitute "S".

PAGE 7

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through Y shall be performed in any order with the following exceptions. Test conditions A, B, C, D, E, and F are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, E, or F are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E, and F where applicable, followed by the remaining tests in the sequence."

4.5.1, line 5: Delete "D through X" and substitute "G through X".

4.5.3, line 3: Delete "D through X" and substitute "G through X".

4.5.3, line 6: Delete "D through Y" and substitute "G through Y".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:51Z
Check the source to verify that this is the current version before use.

PAGE 64

FIGURE 25, Item C01 box: Delete "C01" and substitute "C06".

FIGURE 25, NOTE 3, first line: Delete "C01" and substitute "C06".

FIGURE 25, NOTE 3, second line: Delete "Frequency = 120 Hz." and substitute "Frequency = 1 KHz."

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0114)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:51Z
Check the source to verify that this is the current version before use.