INCH-POUND

MIL-M-28787/70B(SH)
AMENDMENT 1
7 June 1991

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

COUNTER, BINARY, DIGITAL, KEY CODE FHA

This amendment forms a part of Military Specification MIL-M-28787/70B(EC), dated 2 August 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense

PAGE 3

4 4.2 Delete and substitute the following.

"4.4.2 Order of testing Test conditions A through EE shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and F are stress tests and shall be performed only at 25 ± 5°C If test conditions A, B, C, D, or F are part of a sequence of tests, the order of testing shall be as follows. A, B, C, D, and F where applicable, followed by the remaining tests in the sequence "

4 5 1 Delete and substitute the following

"4 5 1 Operating temperature tests The operating temperature tests shall be conducted in accordance with MIL-M-28787 Before starting these tests, test conditions A through EE in table I shall be performed in the order specified in 4 4.2 using the initial limits at 25 ± 5°C ambient When electrical testing is called for at the end of each temperature stabilization period, test conditions E and G through DD shall be performed in the order specified in 4 4 2 using the initial limits for the applicable operating temperature At all other times during the operating temperature tests, the module shall be operating in the test circuit shown on figure 2 "

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:52Z
Check the source to verify that this is the current version before use.

PAGE 9

4 5 3 Delete and substitute the following

"4.5.3 Life test The life test shall be conducted in accordance with MIL-M-28787 The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests E and G through DD shall be performed in the order specified in 4 4.2 using the end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests E and G through DD shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I "

PAGE 32

TABLE IX, Footnote 1/. Delete "L = Low level ≤ 0 4 V." and substitute "L = Low level ≤ 0 5V "

TABLE IX, Footnote 1/ Delete "H = High level ≥ 2 4 V " and substitute "H = High level ≥ 2 5V "

PAGE 78

TABLE XXI, Test condition AA23, C to pin column Delete "17" and substitute "19"

TABLE XXI, Test condition BB2, A to pin column Add "6" and "9"

PAGE 87

FIGURE 37, Note 3 Delete "Frequency = 120Hz" and substitute "Frequency = 1KHz"

Preparing activity
Navy - SH

(Project 5963-N791)

Agent NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:52Z
Check the source to verify that this is the current version before use.