NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

NOTE: This drawing was approved by joint action of the [redacted] AIR FORCE and Navy Departments as the [redacted] AIR FORCE-Navy standard for this product. This drawing supersedes all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies, or for use in new design, not later than six months after the latest date of approval shown.



METHOD OPTIONAL

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.005,
ANGLES ±1/2°

APPROVED 8 Nov 49 REVISED

AIR FORCE-NAVY AERONAUTICAL DESIGN STANDARD

CHAMFER OR RADIUS - VALVE HOLES IN
AIRPLANE WHEEL RIMS

AND10598

NOT A PART NUMBER

THE REPUBLICAN PRESS, HAMILTON, O.
APRIL 13, 1956 1,000

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:29Z
Check the source to verify that this is the current version before use.