MILITARY SPECIFICATION

COUNTER, CHECKOUT, CONVEYOR

This amendment forms a part of Military Specification MIL-C-43584B, dated 23 September 1974, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, line 1: Delete "one type of".

Line 2: Delete "counter" and substitute "counters".

Add:

"1.2 Classification. The counter shall be of the following types, classes, and sizes specified (see 6.2).

Type I - Counter with electronic optical scanner
Type II - Counter without electronic optical scanner
Class A - Right hand
Class B - Left hand

* Size 1 130 to 139 inches (overall length)

* Size 2 140 to 149 inches (overall length)

* Size 3 150 to 159 inches (overall length)

* Size 4 160 to 172 inches (overall length)"

2.1, under "STANDARDS MILITARY": Add

"FEDERAL

FED-STD-595 - Colors"

FSC 7195

Source: https://assist.dla.mil -- Downloaded: 202610-21T21:46Z
Check the source to verify that this is the current version before use.

PAGES 3 and 4

3.5: Delete and substitute:

* "3.5 Design and construction. The checkout counters shall be designed and constructed for electronic optical scanner operations. The checkout counters shall be compatible with all types of scanning equipment such as Data Checker, Data Terminal, IBM, NCR, SWEDA or equal. The checkout counters shall have scanner conversion kits available for all types of scanning. The checkout counters shall be of modular construction with conveyor type belts, one front transport belt and one rear take-away belt. Timing of the front transport belt shall be synchronized with the ability of the particular scanning unit (see 3.5.7). The counters shall include a stainless steel take-away slide to fit between the front and rear belts. The height between the two belts shall provide a sufficient slope for the cashier to slide the items checked onto the rear belt. The rear belt shall move the items, from the cashier, to be accumulated in the bagging area. The front belt shall be operated by a three position electric eye, foot control and toggle switch. The rear belt shall be operated by a separate switch. The base and frame shall be steel and finished as specified in 3.7. The top deck, (excluding belts), shall be made of corrosion resistant steel, reinforced and with at least a 2B finish. When specified (see 6.2), the bagging area shall have a one piece plastic (or similar material) top. The plastic surface shall not show any scratches that catches a fingernail, any cracks or dents deeper than 1/16 of an inch and any deflection more than 1/4 of an inch when tested as specified in 4.5.2. The counters shall enclose all working parts, including paper bag storage at bagging area, and shall have an enclosed base at the floor. Top and edge molding shall be corrosion-resisting steel or anodized aluminum. Cart guards shall be provided along the customer side of the counter and also the front or loading end finish shall be protected from cart damage. Bagging shelves or other pull out shelves shall be rounded or edge molded to prevent injury. When tested as specified in 4.5.1, the completely assembled conveyer shall show that the assembly of components have:

(a) Complete and proper relationship of moving parts.
(b) Motor bearings operating with no evidence of overheating.
(c) Starting and stopping devices operating smoothly and positively.
(d) No structural failures.
(e) No undue vibration or noise.

The type I counter shall be:

(a) With a kit to receive an electronic optical scanner.
(b) A left or right hand power take-away system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:46Z
Check the source to verify that this is the current version before use.

PAGES 3 and 4 (cont'd)

The type II counter shall be:

(a) Without an electronic optical scanner.
(b) Capable of operating in the convention non-scanning mode and a stainless steel scanner housing cover is to be provided for such operation.
(c) A left or right hand power take-away system."

PAGE 4

3.5.1.1: Delete and substitute:

"3.5.1.1 Height overall. The overall height of the counters at the customers loading end shall be 33 to 36 inches.

3.5.1.2 Width, first sentence: Delete and substitute "The overall width of the counter including protective molding shall not exceed 49 inches for the type I and shall not exceed 48 inches for the type II."

3.5.1.3: Delete and substitute:

"3.5.1.3 Length. The overall length of the counter shall be as follows:

Size 1 - 130 to 139 inches

Size 2 - 140 to 149 inches

Size 3 - 150 to 159 inches

Size 4 - 160 to 172 inches"

3.5.2: Delete and substitute:

"3.5.2 Bagging area. The checkout counter bagging area shall have a minimum of 1/4 square feet accumulation area, (exclusive of the rear belt), to accommodate two baggers at the rear of the counter. The bagging area shall be equipped with pullout bagging shelf/shelves of sufficient size to hold a minimum of two bags simultaneously and shall have bag storage bins or dividers to accommodate a minimum of three separate bag sizes."

3.5.3: Delete and substitute:

"3.5.3 Belts. The belts shall be double ply neoprene or triple nylon cord. The front transport belt shall be 22 to 24 inches wide. The minimum length of the exposed surface of the front transport belt shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:46Z
Check the source to verify that this is the current version before use.

PAGE 4 (cont'd)

Size 1 - 48 inches

Size 2 - 55 inches

Size 3 - 60 inches

Size 4 - 72 inches.

The rear take away belt shall be 14 to 16 inches wide with a minimum exposed length of 34 inches."

3.5.4: Delete.

PAGES 4 and 5

3.5.5: Delete and substitute:

"3.5.5 Register stand, type I. The type I register stand shall be of sufficient size to accommodate the cash register, customer receipt printer, journal printer, slip printer, and other ancillary scanning equipment. The cash register for type I shall be equipped with a one-piece stainless steel top and an auxiliary cash drawer with lock and three keys. The stand shall be equipped with a drawer, lock, and three keys. A duplex electrical outlet receptacle shall be provided in an accessible location for use with the cash register and other equipment."

Add:

"3.5.5.1 Register stand, type II. The register stand for type II shall be equipped with a drawer, lock, and three keys. The stand shall be of sufficient size to accommodate a cash register. A duplex electrical outlet shall be provided in an accessible location for use with the cash register and other equipment."

3.5.6: Delete and substitute:

"3.5.6 Switches.

3.5.6.1 Switch, type I. The type I counter front belt shall be operated by a foot control switch and a toggle switch, in addition to the electric eye. The type I counter rear belt shall be actuated by a separate switch.

3.5.6.2 Switch, type II. The type II counter front belt shall be provided with switch to stop the front belt (see 4.5.1). The type II counter rear belt shall be actuated by a switch. All switches including foot controls shall be located in the cashier's area."

Source: https://assist.dla.mil -- Downloaded: 20260-21T21:46Z
Check the source to verify that this is the current version before use.

PAGE 5 (cont'd)

3.5.7: Delete and substitute:

"3.5.7 Drive mechanism. The drive mechanism for the checkout counter shall have integral motor and gear reduction units or separate motors and gear reduction units.

3.5.7.1 Belt speed, type I. The type I counter front transport belt speed shall be 22 to 25 feet per minute and the type I rear belt speed shall be 36 to 44 feet per minute when tested as specified in 4.5.1.

3.5.7.2 Belt speed, type II. The type II counter front and rear belt speeds shall be 43 to 50 feet per minute when tested as specified in 4.5.1."

* 3.5.8: Add "(e) Check writing stand
(f) A swivel scale platform shall be adjustable in height from 14 to 20 inches. The scale platform shall be 17 inches wide by 17 inches long ± 1 inch.
(g) Type I with two upright shelves with blackboard to accept the journal printer and customer receipt printer.
(h) Pull-out or hinged checker seat
(i) Change dispenser platform
(j) Three floating dividing bars to separate orders
(k) Cash register guard"

3.5.9: Delete in its entirety.

3.6.1, line 2, after "minimum of 1/4 horsepower each": Add "or 1/6 horsepower energy efficient split capacitor motors"

* 3.7, line 1, after "base": Add "and frame"

2nd sentence: Delete and substitute: "Unless otherwise specified, for Army use, the color of the counters shall be equal to color No. 13613 (beige) of FED-STD-595."

PAGE 7

* Table I: Delete "Front end of pressure plate (when supplied) not flush with front belt" and "X" and substitute:

"Examine	Defect	Classification Major	Minor
Construction and workmanship"	Type, class, and size not as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:46Z
Check the source to verify that this is the current version before use.

PAGE 8

Table I. (cont'd), under "Defect" and "Classification Major": Delete
"Additional accessories (when specified) X
missing or not as specified"

PAGE 9

4.5.1 (f): Delete: "(pressure plate)"

6.1, line 1: Delete "counter" and substitute "counters".

6.2 (f): Delete and substitute "(f): Type , class and size of counters required (see 1.2)."

6.2 (g), (h), (i) and (j): Delete

Add: "(o) When the accumulation area is other than 14 square feet (3.5.2)."

6.3: Delete.

6.7: Delete.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in the notations. Bidders and contractors are cautioned to evaluate the requirements of this document on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Army - GL

Project No. 7195-0094

Source: https://assist.dla.mil -- Downloaded: 20260-21T21:46Z
Check the source to verify that this is the current version before use.