INCH - POUND
MIL-DTL-43575B
23 November 2018
SUPERSEDING
MIL-L-43575A
01 JUNE 1970

DETAIL SPECIFICATION

LAUNDRY PRESS, COMMERCIAL, CABINET TYPE, SINGLE LAY, AND CABINET , DRYING, FOR WASHABLE TROUSERS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1 SCOPE

1.1 Scope. This specification covers a cabinet type laundry press which will press washable trousers, with a crease (see 6.5) in the front and back of the legs in one lay, and a drying cabinet to completely dry trousers (see 6.1).

1.2 Classification. Items should be selected from the following as specified (see 6.2).

Type 1 - Press
Type 2 - Drying cabinet

2. APPLICABLE DOCUMENTS

2.1 Government Documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

SPECIFICATION

FEDERAL

QQ-N-281 - Nickel-Copper Alloy Bar, Plate, Rod, Sheet, Strip, Wire, Forgings, and Structural and Special Shaped Sections

Comments, suggestions, or questions on this document should be addressed to DLA Troop Support - Industrial Hardware Division (ATTN: Code FHTE), 700 Robbins Avenue, Philadelphia, PA 19111-5096 or email trpsptspecspa@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-24723 - Castings, Nickel-Copper Alloy

MIL-T-152 - Treatment, Moisture and Fungus Resistant, of Communications, Electronic. and Associated Electric Equipment.

STANDARDS

MILITARY

MIL-STD-130 - Identification Marking of US Military Property
MIL-STD-461 - Electromagnetic Interference Characteristics, Requirements for Equipment.

(Copies of these documents are available online at http://quicksearch.dla.mil/.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal should apply.

NATIONAL ELECTRICAL MANUFACTURER' S ASSOCIATION (NEMA)

Publication IC1-1965 - Industrial controls
MG1 - Motors and Generators

(Copies of these documents are available online at www.nema.org.)

UNDERWRITERS LABORATORIES , INC. (U.L.) STANDANDS

(Copies of these documents are available online at www.ul.com)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

Standard No. 70 – National Electrical Code (1968).

(Copies of these documents are available from www.nfpa.org)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section VIII, Unfired Pressure Vessels .

Welding Qualifications of the American Society of Mechanical Engineers .

(Copies of these documents are available from https://www.asme.org)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

ASTM International

ASTM-A240/A240M - Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications

ASTM-A494/A494M - Castings, Nickel and Nickel Alloy

(Copies of these documents are available from http://www.astm.org.)

American National Standards Institute (ANSI)

ANSI Z8.1 - Safety Code for Laundry Machinery and Operations.

(Copies of these documents are available from https://webstore.ansi.org/)

American Society for Quality (ASQ):

ASQ Z1.4 - Sampling Procedures and Tables for Inspection by Attributes..

(Copies of this document are available online from http://asq.org.)

3. REQUIREMENTS

3.1 First article. This specification contains provisions for first article test and approval (see 4.1, 6.2, 6.6).

3.2 Standard product. Trouser presses and drying cabinets covered by this specification shall be the manufacturer's current standard products except for those changes necessary to comply with this specification. All accessories and components normally offered commercially shall be furnished with each laundry press and cabinet.

3.3 Codes and standards.

3.3.1 NFPA. The laundry press and cabinets shall be wired to conform to NFPA Standard No. 70.

3.3.2 UL. All wiring, conduit, and fittings of the laundry press and cabinet shall conform to applicable Underwriters Laboratories (UL) requirements for use in non-hazardous locations.

3.3.3 NEMA. Motor controllers, timers, pushbuttons, starters, and limit switches shall conform to performance requirements of NEMA Standard Publication IC1.

3.3.4 ANSI. The laundry press and cabinets shall conform to the requirements of ANSI Z8.1 - Safety Code for Laundry Machinery and Operations.

3.3.5 ASME. The laundry press and cabinet chest, chambers, and cylinders, shall comply with the provisions of the ASME Unfired Pressure Vessel Code, Section VIII.

3.4 Certification. Prior to approval of the preproduction sample, or if none is submitted, prior to approval of the first shipment, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative, that the laundry presses and cabinets he proposes to furnish meet the requirements specified in 3.3.1, 3.3.2, 3.3,3, 3.3.4, and 3.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

3.4.1 NFPA. Acceptable evidence of meeting requirements of 3.3.1, shall be the manufacturer's certified statement that the presses and cabinets have been wired in accordance with NFPA Standard No. 70.

3.4.2 UL. Acceptable evidence of meeting requirements of 3.3.2 shall be the UL label or Listing Mark or certification from an independent testing laboratory acceptable to the contracting officer or his authorized representative that conduit, fittings, and wiring conform to applicable UL requirements for use in non-hazardous locations.

3.4.3 NEMA. Acceptable evidence .of meeting the requirements of 3.3.3 shall be the manufacturer's certified statement that the motor controller(s) timers, pushbuttons, starters, and limit switches conform to NEMA Standard Publication No. IC1. A tag or label attached to the component stating that the component conforms to this standard is acceptable evidence.

3.4.4 ANSI. Acceptable evidence of meeting the requirements of 3.3.4 shall be the manufacturer's certified statement that the laundry press and cabinets comply with ANSI Z28.1.

3.4.5 ASME. Acceptable evidence of meeting the requirements of 3.3.5 shall be the manufacturer's certified statement that the laundry press and cabinet chests, chambers, and cylinders comply with the ASME Unfired Pressure Vessel Code, Section VIII.

3.5 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for the specified equipment, provided the completed items comply with all provisions of this specification.

3.5.1 Corrosion-resistant metals. Corrosion-resistant metals as specified herein after shall conform to 3.5.1.1, 3.5.1.2, or 3.5.1.3.

3.5.1.1 Corrosion-resisting steel. Corrosion-resisting steel shall conform to ASTM-A240/A240M , as applicable.

3.5.1.2 Nickel-copper alloy. Nickel-copper alloy shall conform to QQ-N-281 or composition M30C of ASTM-A494/A494M and MIL-C-24723

3.5.1.3 Copper alloy castings. Copper alloy castings shall conform to alloy numbers C85200, C85400, C85500 or C85700 per ASTM B30, B271 or B763..

3.5.2 Materials for fasteners. Fasteners shall be of carbon or alloy steel, except where brass or corrosion-resistant metal is to be fastened, in which case the fasteners shall be of brass or corrosion-resistant metal, respectively. Where dissimilar metals are fastened, the fasteners shall be of corrosion-resistant metal and cathodic to base metals.

3.5.3 Pipe, tube, fittings, cylinders, and valves. Pipe, tube, valves, cylinders, and fittings used for air and steam lines shall comply with the accepted manufacturer' commercial practice.

3.5.4 Conduit, fittings, and electric wire. Electrical conduit shall be grounded metallic, rigid, or flexible steel. All electrical wire shall be heat resistant grade, thermoplastic insulated.

3.5.5 Motors. Motors shall conform to the applicable requirements of NEMA MG1,- as applicable, and to the following requirements:

(a) All motors shall have windings impregnated to resist moisture.

(b) Motors shall have the proper starting characteristics and ample power with a reasonable factor of safety for their intended operation under full-load conditions without exceeding the permissible temperature rise.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

(c) Motors shall be equipped with ball bearings, except that motors of 1/2 horsepower or less when used for horizontal application may have sleeve bearings. Motor bearings shall be of the permanently lubricated type or shall have adequate and accessible means for lubrication.

(d) Each rotor shall be provided with automatic reset overload protection.

3.6 Design and construction. Construction of presses and drying cabinets covered by this specification shall conform to the general requirements and the construction details specified herein.

3.6.1 Item 1 - press (cabinet type). The press shall be an air-operated press designed for pressing washable trousers in a single lay. The waist and cuff expanders when being dressed or undressed shall be positioned either completely or partially outside the cabinet. The press shall be capable of simultaneously finishing all outside surfaces of cook's, baker's, and hospital attendant's trousers from white cotton drill, 6.5 ounces per square yard; trousers fabricated of 35 percent cotton or rayon and 65 percent polyester yarns; and standard khaki and fatigue trousers. The press shall have automatic expander to fit waists from 28 to 48 inches, stretch legs with inseam measurements of 24 to 37 inches their full length, and fit cuffs 9-3/4 to 11-1/2 inches wide (measured across the leg from edge to edge at the bottom of the trousers). Presses shall be furnished complete with motors, driving mechanism, including production counter belts and chains, starters and controllers, master switches, timers, cutouts, and other electrical equipment and commercial accessories including anchor bolts, if, and as applicable. All presses furnished under this specification shall show that the assembly of component parts are complete; of proper interrelationship; moving parts evidence no undue vibration, noise, or over heating of bearings; and the opening and closing devices operate smoothly and positively when submitted to the test specified in 4.3.1. In addition to the above, the trousers pressed during the test shall conform to the following:

a. Top

(1) Waist sides free of wrinkles.
(2) Pocket area free of wrinkles.
(3) Fly area free of wrinkles and puckering.
(4) Crotch free of wrinkles or folds.

b. Legs

(1) Outseam free of wrinkles or folds.
(2) Inseam free of wrinkles or folds.
(3) Full length prominent crease (see 6 .5) in both front and back of legs.
(4) Outseam and inseam match within 1/4 inch from cuff to crotch.

3.6.1.1 Performance. Presses furnished under this specification shall be capable of satisfactorily and completely processing approximately 100 trousers per hour when two presses are operated by one operator (see 4.3 .1).

3.6.1.2 Heads, press. The press heads shall be removable steam chambers of cast iron, cast steel, fabricated carbon steel, or corrosion-resistant metal shaped to conform to the contour surfaces against which they press. Cast-steel, cast-iron, or fabricated carbon steel ironing surfaces shall be plated or sprayed with nickel or corrosion-resistant metal. All ironing surfaces shall be polished smooth. Aluminum heads are not acceptable.

3.6.1.3 Safety devices. Each trouser press shall be provided with (1) a touch safety device; or (2) press heads shall be interlocked with a cabinet door that shall automatically be activated stopping the pressing cycle, if the operator places a hand inside the machine; or (3) two manually operated controls may be conveniently located and arranged so that both hands of the operator must be on the controls before the head can be closed (see 4.3 .1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

3.6.2 Item 2 - drying cabinet. The cabinet shall be steam heated and designed for drying approximately 100 washable trousers per hour which are not completely dry when removed from a press. It shall be approximately 23 inches wide, 8 feet long, and 6 feet high; of welded steel construction, and well insulated with batts not less than 1 inch thick. Sufficient heating coils shall be provided for maintaining a temperature between 250 and 275 degrees Fahrenheit (F.) within the cabinet. The cabinet shall be equipped with a conveyor for transporting trousers through the cabinet and shall be compatible with the press with which it is to be used. The conveyor shall be furnished with replaceable trouser holding clips. The conveyor control shall be interlocked with the presses so that when either of the presses goes through a pressing cycle, the conveyor will advance one station, (set of clips or hooks supporting one pair of trousers) or when specified (see 6 .2), the cabinet shall be equipped with a foot pedal controlled, electrically driven gear motor. Cabinets shall be furnished complete with motors, driving mechanism, including belts and chains, starters and controllers, master switches, timers, cutouts, and other electrical equipment and commercial accessories, if, and as applicable. All cabinets furnished under this specification shall show that the assembly of component parts are complete; of proper interrelations: moving parts evidence no undue vibration, noise, or overheating of bearings; and the opening and closing devices operate smoothly and positively when tested as specified in 4.3.1.

3.6.3 Wiring and instructions. Wiring shall be provided between motors, controllers, timers. pushbuttons, starters, and limit switches installed on the equipment and shall be dome with materials specified in 3.5.4, as applicable, except metallic armored cable may be used where required for belt adjustment by moving a motor. All wiring shall terminate in connection boxes with provisions for connection beyond the machine. Each conductor shall be identified by a different color.

3.6.4 Motor control circuit. Controllers shall be of the magnetic across the-line type having a separate pole for each ungrounded conductor. Pushbutton control stations shall be mounted at points readily accessible to operators. Pushbuttons shall be fully protected or recessed to prevent accidental operation.

3.6.5 Applicability for current characteristics. The electrical parts of the machine shall be designed for the voltage, frequency, and number of phases specified (see 6 .2).

3.6.6 Piping. Necessary integral pipe fittings shall be furnished and installed to comply with accepted plumbing practice. Inlet steam and air supply connections shall be supplied with manually operated shutoff valves.

3.6.6.1 Valves and traps. Steam, drain, condensate (with three-valve bypass and trap), pressure reducing, and other operational valves shall be so installed as to be readily accessible for operation and maintenance.

3.6.6.2 Steam and air pressures. Assembly of pipe, tube, fittings, coils, cylinders, chests, and chambers using steam shall be designed for a working steam pressure of 125 p.s.i.g. and shall be capable of withstanding a hydrostatic pressure established in accordance with the provisions of the ASME Unfired Pressure Vessel Code, without any leaks. Air lines and cylinders shall be designed to withstand a minimum of 80 p.s.i.g. without any leaks when tested as specified in 4.3.2.

3.6.7 Equipment bases. Bases shall be constructed so that points of contact with the floor shall be in the same plane. Provisions for anchoring to the floor shall be provided.

3.6.8 Replaceability of bearings. All bearings shall be readily replaceable.

3.6.9 Lubrication. Lubrication for forced type systems shall be provided and accessibly located for lubricating bearings, excluding motors (see 3.5.5), and chain or gear drives. Where lubricant reservoirs are required for chain or gear drives the reservoirs shall be provided with a threaded cap at the top and a drain plug at the bottom.

3.6.9.1 Seals. Seals shall be provided to prevent the lubricant from entering parts of the machine where trousers are handled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

3.6.10 Belts and pulleys. V-belts shall be of the grades commercially known as multiple-drive or variable speed types, except where a single belt is furnished with a fractional-horsepower motor, a V-belt commercially known ae a fractional-horsepower belt may be supplied. Pulleys for V-belts shall be suitably grooved for the type and size belts used. Chain drives shall be of the silent or roller-chain type. Means shall be provided for readily adjusting belt and chain tension.

3.6.11 Spacing and extent of fastenings. The spacing and extent of welds, rivets, bolts, and screws shall prevent bulging of the metals fastened.

3.6.12 Marking for identification. Each machine covered by this specification shall be marked for identification in accordance with MIL-STD-130.

3.6.13 Finish and color. Unless otherwise specified (see 6 .2) each press and drying cabinet shall be finished in accordance with the manufacturer's standard practice except emergency stop pushbuttons shall be red and this color shall be limited to pushbuttons. Exposed surfaces of corrosion-resistant metals shall be finished to a commercial polish in accordance with the manufacturer's standard practice.

3.6.14 Electromagnetic compatibility. When specified (see 6 .2), equipment shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461 (see 4.3.3).

3.6.15 Moisture and fungus resistant treatment. When specified (see 6 .2), electrical components shall be moisture and fungus resistant treated with material conforming to and applied as specified in MIL-T-152.

3.6.16 Welders. The welders performing the welding on assemblies, subassemblies, and on the end item shall be certified welders and shall have passed the qualification test as prescribed by either the "Standard Qualification Procedure of the American Welding Society" or "Welding Qualification of the American Society of Mechanical Engineers". The supplier shall furnish the Government with a list of names of his welders who are certified and have passed the test of either referenced codes and he shall certify that the welding of this equipment was performed by welders on the list.

3.7 Workmanship. Presses and drying cabinets shall be free from defects such as fractures, splits, punctures, tears, dents, creases, or malformations. There shall be no sharp edges, slivers, burrs, or projections.

3.7.1 Application of finish. The finish applied to the and item shall be continuous, smooth, adherent, without discoloration or imbedded foreign material and shall contain no sags, runs, drips, creeps, laps, bubbles, streaks, wrinkles, blisters, scratches, pours, pits, lumps, flux, or orange peel. No rust, rough grinds, or tool marks shall show through the coating.

3.7.2 Welding and brazing. All surfaces of parts to be welded or brazed shall be clean. Welding and brazing shall be accomplished in a manner which will prevent the occurrence of burn holes, cracks, fractures, or incomplete fusion and deformation of material. All scale and flux deposits shall be removed from finished welds, Electrodes or welding rods used for welding shall deposit material compatible with the base metal.

3.7.3 Soldering. Soldering shall be complete and adherent with all flux and residue removed and shall contain no pin holes.

3.7.4 Threaded fasteners. Threaded fasteners shall not be broken, stripped, fractured, or loose.

3.7.5 Rivets. Rivets shall be driven to completely fill the holes, with full size heads neatly finished and in full contact with the surface of riveted members.

3.7.6 Electrical wiring. Wiring shall not be cut, abraded, or have insulation stripped, and shall be properly and tightly joined at terminals. Wiring shall have adequate slack to provide strain relief.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 First article inspection. When a preproduction sample is required it shall be examined for defects listed in table 1, specified dimensions, and tested as specified in 4.3.1, 4.3.2, and when applicable 4.3.3. The presence of any visual defect, any dimension not within the specified requirements, or failure to pass any test shall be cause for rejection of the preproduction sample.

4.2 Inspection. Sampling for inspection shall be performed in accordance with ASQ Z1.4, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. Component and materials shall be. inspected and tested h accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. A lot shall consist of all laundry -presses or all drying cabinets offered for inspection at one time. The sample unit shall be one completely fabricated laundry press or drying cabinet, as applicable.

4.2.2.1 Visual examination. The completely assembled end items shall be examined for defects In table 1. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects.

Examine	Defect	Classification	
		Major	Minor
Finish	Not finished where required.	X	
	Finish not in accordance with manufacturer's standard practice (unless otherwise specified).		
	Ferrous metal ironing surfaces not plated or sprayed as specified.	X	
	Emergency stop button not specified color.	X	
	Rust, rough grinds or tool marks show through coating.		X
	Ironing surfaces not smoothly polished.		X
	Pushbutton color not as specified.	X	
	Sags, runs, drips, creeps, loops, bubbles, streaks, wrinkles, blisters, scratches, pores, lumps, orange peel.		X
	Exposed surfaces corrosion – resisting steel not finished to a commercial polish,	X	X
Construction and workmanship (applicable to all components and assemblies)			
Fabrication			
	Any component missing.	X	
	Kinks and sharp bends in sheet metal.		X
	Any component fractured, split, punctured, torn, dented, bowed or sprung.	X	
	Any burr, sharp edge, sliver or projection.	X	
	Edges not smooth.		X
Bolt connections			
	Bolt holes not accurately punched or drilled.		X
	Burrs around holes not removed.		X
	Washers or lockwashers not provided in accordance with commercial practice.		X
	Bolts, nuts, and screws broken, stripped, fractured, or not drawn tight .		X
Rivets (when applicable)	Missing, loose, broken, or inadequately peened.		X
Welding and Brazing	Missing, incomplete, through burn holes, severe undercut, fractured, porous, or otherwise not fused.	X	
	Slight Slag inclusion, slight undercut, not smooth and uniform, scale or flux deposit not removed.		X
Electrical assembly	Wiring cut, abraded, or not properly joined.	X	
	Adequate slack not provided for wiring to relieve strain, or excessive insulation stripped from wiring.	X	
	Electrical wire Is not heat resistant grade thermoplastic.	X	
	All wiring not terminated in connection box.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects. (con't)

Examine	Defect	Classification	
		Major	Minor
Construction (general)	Motor bearings, where applicable, (general) not accessible for lubrication.	X	
	Pushbuttons not fully protected or recessed, or not mounted at points convenient to operator.	X	
	Bearings not readily replaceable,	X	
	Provisions not made for adjusting chain and belt tension.	X	
	Equipment bases not in same place.		
	Valves not readily accessible for operation and maintenance.	X	
	Head of press not removable or not shaped to conform to pressing surfaces.	X	
	Press head safety device not as specified (see 3,6 .1.3) .	X	
	Panels for inspection and maintenance not readily removable,	X	
	Insulation not as specified.	X	
	Drying cabinet not equipped with foot pedal control (when specified) .	X	
Equipment manual	Missing, incomplete, illegible.	X	
Identification marking	Missing, incomplete, illegible.	X	

4.2.2.2 Dimensional examination. Inspection shall be made of the end items for compliance with dimensions specified. The Inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.2.2.3 Testing of the end item. Each unit of production shall be tested se specified in 4.3.2 find failure to pass this test shall be cause for rejection of the unit. When a preproduction sample is not required, the first unit of production shall be tested as specified in 4.3.1 and when applicable, 4.3.3. The functional test specified in 4.3.1 will be witnessed by a representative of the Government prior to acceptance. The functional test shall be performed, unless satisfactory evidence is produced that the press and cabinet, as applicable, have satisfactorily passed this test either in the manufacturer's plant or in a commercial application. The Government reserves the right to check test such items to determine validity of the evidence produced. Failure to pass any test shall be cause for rejection of the unit.

4.2.3. Examination of preparation for delivery. Examination shall be made for preservation, packaging, packing, and marking in accordance with Section 5.

4 .3.4 Code and standards compliance. Proof of compliance with the requirements of 3.3 shall be made available to the Government representative.

4.3 Tests.

4.3.1 Functional test. The presses shall be capable of satisfactorily and completely processing cook's, baker's, or hospital attendant's trousers; standard khaki trousers; fatigue trousers; and 35 percent cotton or rayon and 65 percent polyester trousers at a rate of 100 per hour when the two presses are operated by one (1) operator. The trousers shall be mixed sizes from large to small. Test is to be made on trousers which have been washed, starched (heavy), and extracted for not less than 12 minutes nor more than 15 minutes when trousers are to be finished without preconditioning. When trousers are to be preconditioned, the trousers shall be extracted for 10 minutes and preconditioned for 4 minutes in a laundry tumbler, air heated to not more than 190°F. Washing, extracting, and pre-conditioning operation

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

shall be performed within a reasonable length of time prior to pressing on the presses. The trousers shall be supplied by the Government under the following conditions:

The cook's, baker's, or hospital attendant's cotton khaki trousers; fatigue trousers, and 35/65 trousers will be shipped to the low responsive bidder at the Government's expense and returned, after completion of the test, at the Government's expense. The bidder shall be responsible for any loss or damage to the trousers which is incurred while in the bidder's possession. Prior to their return, the trousers shall be laundered and packed by the bidder in the same manner in which they were shipped to the bidder. The trouser press and drying cabinet shall be connected to power having the specified characteristics and tested to determine compliance with the following requirements:

(a) The assembly of components; undue vibration or noise; overheating of parts i.e., bearings; opening and closing devices; and structural failures (see 3.6.1 and 3,6.2).

(b) Operation of expanders for waists, legs, and cuffs for compliance with the requirements of 3.6.1.

(c) Operation of applicable safety device for compliance with the requirements of 3.6.1.3.

(d) Operation of conveyor control Interlock, when applicable, far compliance with the requirements of 3.6.2.

(e) Temperature of cabinet for compliance with the requirements of 3.6.2 when applicable.

(f) Seals fail to prevent lubrication leaks (se 3.6.9.1).

(g) Trousers shall be examined to determine conformance with 3.6.1 for the following:

(1) Waist sides free of wrinkles.
(2) Pocket area free of wrinkles.
(3) Fly area free of wrinkles and puckering.
(4) Crotch free of wrinkles or folds.
(5) Leg outseam free of wrinkles or folds.
(6) Leg in8eam free of wrinkles or folds.
(7) Pull length prominent crease (see 6 .5) in both front and back of legs.
(8) Outseam and inseam do match within 114 inch from cuff to crotch.

Any nonconformance to the above shall constitute failure of the test.

4.3.2 Pressure tests. - All air lines and cylinders shall be tested with 80 (+ 10 -0) p.s.i.g. air pressure. The test pressure shall be maintained for 10 minutes to determine that no leaks are present. Nonconformance to 3.6.6.2 shall constitute failure of this test.

4.4.3 Electromagnetic compatibility test. When electromagnetic compatibility is required, the preproduction sample or initial unit of production shall be tested by the supplier in accordance with test methods CE03 and RE02 of MIL-STD-461. The Government reserves the right to witness tests performed by the supplier or his private testing organization. The supplier shall furnish the contracting officer, for approval, the Interference Control Plan, the EM2/SMC Test Plan, and the Electromagnetic Test Report required in MIL-STD-461. Upon approved of the test report by the contracting officer and provided all other requirements of the specification are met the sample or the initial unit of production, as applicable, shall be used as a model for all production units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity

6. NOTES

6.1 Intended use. The trouser press (item 1) is intended for use in pairs without a drying cabinet (item 2) or as a unit (2 presses with each drying cabinet), capable of being operated by one person in a fixed laundry for pressing cook's, baker's, and hospital attendant's trousers; standard cotton khaki trousers; fatigue trousers; and 35/65 trousers.

6.2 Ordering data. Procurement documents should specify the following as applicable:

(a) Title, number, and date of this specification.
(b) Item required (see 1.2).
(c) First article (see 3.1, 4.1, and 6.6)
(d) When a foot pedal controlled, electrically driven gear motor is required (see 3.6 .2).
(e) Power characteristics required (voltage, phase, frequency) (see 3.6,5).
(f) Finish, if other than manufacturer's standard (see 3.6 .13).
(g) When drawings are required for installation purposes, request that successful bidder furnish drawings shoving the exact dimensions of the item, overall floor space requirement, location of hold down bolts, location and size of inlet and outlet lines, the point where electrical connection is to be made, and the electrical characteristics of the motor and any electrical equipment. For Air Force purchases, these drawings are required within 10 days after award to the successful bidder.
(h) When electromagnetic compatibility is required (see 3.6 .14).
(i) When moisture and fungus resistant treatment is required (see 3.6.15).
(j) Selection of applicable levels of preservation, packaging and packing (see 5.1).

6.3 Electromagnetic compatibility. When electromagnetic compatibility is required, the contracting officer should submit a copy of the Interference Control Plan, the SM2/SMC Test Plan, and the test report required (see 4.3 .3) to the Commanding Senera2, U.S. Army Electronics Command, ATTN: AMSEL-GG-EI, Fort Monmouth, New Jersey 07703 for approval.

6.4 Successful commercial operation. No laundry press or cabinet will be acceptable unless the manufacturer has had a laundry press and cabinet of the same type and design as that specified operating successfully in a commercial or institutional laundry establishment for at least one year. Equipment installed for test purposes in a manufacturer's plant or laboratory should not come within the category of successful commercial operation.

6.5 Crease. For Air Force purchases, "crease" is defined as a sharp line made by folding fabric and by means of pressure and heat, creating an acute angle having a thin edge, and not being rounded or obtuse.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.

6.6 First article. The press and cabinet covered by this specification requires first article test and approval under the appropriate provisions of paragraph 7-104.55 of the Armed Services Procurement Regulations. The first article should consist of one unit. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examination, test, and approval of the first article.

6.7 Contract data requirements. Any requirements for equipment rnanuals, drawings, and supervision of installation for the item covered by this specification should be included in DD Form 1423 Contract Data Requirement List and cited in the contract.

6.8 Subject term (key word) listing.

Crease
Inseam
Motor
Outseam
Press heads

6.9 Changes from previous issues. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - GL
Navy - YD

Preparing Activity:
DLA - CQ

(Project 3510-2018-002)

Review activities:
Army – CE,

NOTE: The activities listed above were interested in this document as of the date of document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:44Z
Check the source to verify that this is the current version before use.