MILITARY SPECIFICATION

LINER, TROUSERS, CHEMICAL PROTECTIVE

This amendment forms a part of Military Specification MIL-L-43579C, dated 7 October 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, under "STANDARDS MILITARY": Add "MIL-STD-147-Palletized Unit Loads." Delete "MIL-STD-1188-Commercial Packaging of Supplies and Equipment."

Add new paragraph:

"2.1.1 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)"

PAGE 14

Table I, operation 15.a.: Delete and substitute: "15.a. Trim all ends of stitching to 1/4 inch maximum length throughout (inside and outside) and remove loose threads from the trousers."

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:45Z
Check the source to verify that this is the current version before use.

PAGE 18

4.2., under "Cleanness": Delete defect "b". and substitute "b. Thread ends not trimmed to 1/4 inch maximum length throughout (inside and outside) or loose thread ends not removed from liner (to be scored only when the condition exists on major portion of liner). -Minor B."

PAGE 25

4.2.4: Delete and substitute:

"4.2.4 Packaging inspection. An inspection shall be made to determine that preservation, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, inadequate stapling, or improper taping. Bulged or distorted container. Improperly folded liners, inadequately tied bundles, contents improperly covered with paper.
Content	Number of bundles per container is more or less than required. Number of liners per bundle is more or less than required. 1/ Size shown on one or more liners not as specified on container. 1/

1/ For this defect, one bundle from each container in the sample shall be examined."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:45Z
Check the source to verify that this is the current version before use.

PAGE 25 (cont'd)

Add new paragraph:

4.2.5 Palletization inspection. An inspection shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.

PAGE 26

5.1.2: Delete "MIL-STD-1188" and substitute "ASTM D 3951."

PAGE 27

5.2.3., line 2: Delete "MIL-STD-1188" and substitute "ASTM D 3951."

5.3 and 5.3.1: Delete and substitute:

5.3 Palletization. When specified (see 6.2), liners packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means K and L or film bonding means O or P. Pallet pattern shall be in accordance with load pattern number three of the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:45Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract or purchase order, intermediate packs, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Labels, mixed sized. Each shipping container, packed with mixed sizes only, shall have securely attached to the end and side, directly under the printing or stenciling, a white paper label 5 by 4 inches with the words "MIXED NSN's" plainly stamped or printed thereon and under these words shall be legibly stamped or printed the correct quantity and NSN's contained therein."

6.2: Add new subparagraph:

"(f) When palletization is required (see 5.3)

Custodians:

Army - GL
Navy - NU
Air Force - 99

Preparing activity:

Army - GL

Project No. 8415-0466

Review Activities:

Army - MD
Navy - MC
Air Force - 82
DLA - CT

User Activities:

Navy - OS, CG

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:45Z
Check the source to verify that this is the current version before use.